

## OpenVox SWG-2008 Wireless Gateway with 4 Ports and 2G/GSM (SWG2008-4G)



Product Name: OpenVox SWG-2008 Wireless Gateway with 4 Ports and 2G/GSM (SWG2008-4G)

Manufacturer: -

Model Number: SWG2008-4G

Please Note: This product has been discontinued. Please see the OpenVox VoIP Gateways range for an alternative.

### OpenVox SWG-2008 Wireless Gateway with 4 Ports and 2G/GSM (SWG2008-4G)

The OpenVox SWG2008-4G provides 4 GSM channels and built in Intel 4-core CPU which has incredible processing capacity. It supports multiple codecs, including G.711U, G.711A, GSM, G.722, G.723, G.726, G.729 multiple coding. It also support SMS messages sending, receiving, group sending and SMS to E-mail. The SWG-2008 series gateways are 100% compatible with Asterisk, 3CX, FreePBX, FreeSWITCH SIP server and VOS VoIP operating platform. It can help users reduce telecommunications and communication costs.

### OpenVox SWG2008-4G Key Features

- Support SIP/AX2 Protocol
- Add, Modify & Delete SIP/AX2 Trunk
- SIP/AX2 Registration with Domain
- SIP V2.0 RFC3261 Compliance
- DTMF Mode: RFC2833/Inband/SIP Info
- Multiple SIP/AX2 Registrations modes
- Abundant Codecs: G.711A, G.711U, G.729, G.722, G.723, G.726, GSM
- IPv4/UDP/TCP/DHCP/TELNET/HTTP/HTTPS/TFTP
- PPTP VPN
- HTTP/SSH/Optical Telnet
- Ping & Traceroute Command on the Web
- Simple Security Strategy: white list, black list, security rules Management
- Simple and convenient configuration via Web GUI
- Support maintenance and configuration by SSH
- Support configuration files backup and upload
- Firmware Update by HTTP
- Support Web and SSH login password modification
- Restore Factory Settings
- CDR(More than 200,000 Lines CDRs Storage Locally)
- System log
- SIP/AX2 log
- TCP and SIP capture
- Combine Different SIP/AX2 Trunk into Group
- CLID Display & Hide (Need operators' support )
- Random call interval
- Call Duration Limitation
- Real Open API Protocol (based on Asterisk)
- Support DISA
- SMSC/SMS/USSD
- PIN Identification
- Optional Voice Codec
- Ports Group Management
- SMS features
- USSD transceiver

## OpenVox SWG-2008 Wireless Gateway with 4 Ports and 2G/GSM (SWG2008-4G)

- Support MMP
- Support for custom scripts, dialplans
- Support Openvox cloud manage

### OpenVox SWG2008-4G - Technical Specifications General

- Module Type: GSM
- Module Number: 4
- Channel Number: 4
- Band: 850/900/1800/1900MHz@GSM
- Weight (without antenna): 1.107KG
- Power Consumption (without module): 6W
- Dimension (without antenna): 220mm\*44mm\*192mm
- SIM Card: Hot-Swap
- WAN: 1\*10/100M
- USB: 1(Supports USB storage)
- Operation Temperature: 0~40°C;
- Operation Humidity Range: 10% ~ 90%
- Storage Temperature Range: -20~70°C;

**Please Enquire**

---