

Snom A190 Wireless Multicell DECT Headset (A190)



Product Name: Snom A190 Wireless Multicell DECT Headset (A190)

Manufacturer: Snom

Model Number: A190

Please Note: This product ships with only a US and EU plug.

Snom A190 Wireless Multicell DECT Headset (A190)

The Snom A190 is a wireless multicell DECT headset which revolutionises mobility in the workplace. The Snom A190 Monoaural Headset is a lightweight and comfortable communication solution. It offers adjustable microphone boom, wideband audio, and compatibility with M-series base stations.

Snom A190 Key Features

- Superior wideband sound
- Noise reduction
- Echo cancellation
- Stand-alone and paired mode
- Lightweight design
- Handover and roaming in multi cell setup

With up to 7 hours of talk time, a 300m outdoor range, and DECT encryption, it's perfect for professionals. Easy registration and software updates make it hassle-free, and it's CE and IEC 60950 compliant. Ideal for use with Snom M-series base stations, the Snom A190 is your go-to headset for clear, secure communication.

Snom A190 - Technical Specifications

Headset

- Over-the-head wearing style with adjustable microphone boom
- Monoaural headset with audio controls and LED indicator
- Stand-alone mode: an account is configured to an A190
- Paired mode: an account is shared by the A190 and a DECT-handset
- Wideband audio support
- Talk-time 7h (NB), 6h (WB)
- Light-weight design 45g
- HAC compliant
- Compatible to M-series base station

Battery

- Type: lithium-ion, 320mAh built-in
- Talktime WB: 6h
- Talktime NB: 7h
- Stand-by-time: 100h
- Battery charge time 0-100%: < 4h

Charger

- Input: 5V DC, 350mA
- Integrated weight and rubber feet for solid desktop setup

Power adapter

- Input: 100-240V AC, 50/60Hz, 150mA

Snom A190 Wireless Multicell DECT Headset (A190)

• Output: 5V DC, 350mA
• Plug: interchangeable clips, EU and US clips included
• Charging conditions: +5° C to 45° C

Range

• Indoors: up to 50m
• Outdoors: up to 300m

DECT

• Frequency band: - 1,880–1,900Mhz (EU) - 1,920–1,930Mhz (US)
• Output power: EU<250mW, US<100mW
• Protocols: DECT, DECT 6.0
• Wideband voice
• DECT encryption
• DECT band auto-sensing

User interface

• Voice prompts (English)
• Volume, mute control
• AUX key
• Call control key
• LED status indication

Installation

• Easy registration to compatible base stations
• Software update: over-the-air via the base station

Marking

• CE
• IEC 60950

Compatible base stations

• Snom M900: PN 00004426 (EU version), PN 00004441 (US version)
• Snom M700: PN 00003928 (EU version) PN 00003929 (US version)
• Snom M300: PN 00003986 (EU version), PN 00003985 (US version)

Price: £89.50