

## Snom A190 Wireless Multicell DECT Headset (A190)



Product Name: Snom A190 Wireless Multicell DECT Headset (A190)

Manufacturer: Snom Model Number: A190

Please Note: This product ships with only a US and EU plug.

Snom A190 Wireless Multicell DECT Headset (A190)

The Snom A190 is a wireless multicell DECT headset which revolutionises mobility in the workplace. The Snom A190 Monoaural Headset is a lightweight and comfortable communication solution. It offers adjustable microphone boom, wideband audio, and compatibility with M-series base stations.

Snom A190 Key Features

� Superior wideband sound

ï¿1/2 Noise reduction

� Echo cancellation

ï¿1/2 Stand-alone and paired mode

� Lightweight design

تز1/2 Handover and roaming in multi cell setup

With up to 7 hours of talk time, a 300m outdoor range, and DECT encryption, it's perfect for professionals. Easy registration and software updates make it hassle-free, and it's CE and IEC 60950 compliant. Ideal for use with Snom M-series base stations, the Snom A190 is your go-to headset for clear, secure communication.

Snom A190 - Technical Specifications

Headset

าั¿½ Over-the-head wearing style with adjustable microphone boom

រី¿½ Monoaural headset with audio controls and LED indicator

า๊¿½ Stand-alone mode: an account is configured to an A190

ī¿½ Paired mode: an account is shared by the A190 and a DECT-handset

� Wideband audio support

� Talk-time 7h (NB), 6h (WB)

ï¿1/2 Light-weight design 45g

ï¿1/2 HAC compliant

� Compatible to M-series base station

### Battery

� Type: lithium-ion, 320mAh built-in

าั¿½ Talktime WB: 6h าั¿½ Talktime NB: 7h าั¿½ Stand-by-time: 100h

ï¿1/2 Battery charge time 0-100%: < 4h

#### Charger

� Input: 5V DC, 350mA

ī స్ట్రీ Integrated weight and rubber feet for solid desktop setup

### Power adapter

ï¿1/2 Input: 100-240V AC, 50/60Hz, 150mA



# Snom A190 Wireless Multicell DECT Headset (A190)

ï¿1/2 Output: 5V DC, 350mA

าั¿1/2 Plug: interchangeable clips, EU and US clips included

� Charging conditions: +5° C to 45° C

#### Range

i¿½ Indoors: up to 50mi¿½ Outdoors: up to 300m

#### **DECT**

ī¿½ Frequency band: - 1,880–1,900Mhz (EU) - 1,920–1,930Mhz (US)

ï¿1/2 Output power: EU<250mW, US&lt;100mW

� Protocols: DECT, DECT 6.0

� Wideband voice � DECT encyption

� DECT band auto-sensing

#### User interface

� Voice prompts (English)

ï¿1/2 Volume, mute control

ï¿⅓ AUX key

ï¿1/2 Call control key

� LED status indication

#### Installation

� Easy registration to compatible base stations

ī స్ట్రీ Software update: over-the-air via the base station

#### Marking

CE ½'¿ï

� IEC 60950

## Compatible base stations

 $\ddot{\iota}_{2}$  Snom M900: PN 00004426 (EU version), PN 00004441 (US version)

ī¿½ Snom M700: PN 00003928 (EU version) PN 00003929 (US version)

 $\ddot{i}$  Snom M300: PN 00003986 (EU version), PN 00003985 (US version)

Price: £89.50