



Product Name: Poly CCX 500 Microsoft Teams Edition Business Media Phone

Manufacturer: Polycom / Poly Model Number: 2200-49720-019

Please Note: This item ships without a power supply.

Poly CCX 500 Microsoft Teams Edition PoE Business Media Phone

The Poly CCX 500 is a 2020 desktop phone for Microsoft Teams, with legendary audio sound quality from Poly HD Voice, Poly Acoustic Clarity and Poly Acoustic Fence to eliminate background noise to keep calls quiet in noisy locations such as open plan offices and call centres. Polycom CCX 500 Key Features

- � Native Microsoft Teams experience
- � 5-inch multi-touch LCD display
- � Poly HD Voice
- � Poly Acoustic Clarity
- � Poly Acoustic Fence to eliminate distracting background noise
- ī¿½ Full duplex speakerphone operation with world-class echo cancellation
- � Powerful chipsets to support next-generation features
- าั¿½ Optional WiFi dongle for easy to install anywhere
- � Power over Ethernet
- � Headset options to suit any style (Bluetooth®, USB, RJ9)

The CCX 500 phone is simple and intuitive to use, with a dedicated Microsoft Teams button and one-touch-access to contacts and meetings. It also has robust provisioning and management capabilities for easy telephony deployment and support.

Poly HD Voice

Hear every nuance and keep conversations on track with the industry-leading sound quality, Poly HD Voice.

Poly Acoustic Fence

Eliminate distracting background noise at the source with exclusive, award-winning Poly Acoustic Fence technology.

Native Microsoft Teams Experience

Easily access contacts and meetings one tap away on a color touchscreen with a native Microsoft Teams experience.

Robust provisioning and management

These phones are also easy for IT departments to manage, with robust provisioning and management of telephony deployment and support.

Multiple headset options

Multiple headset options are available to suit any worker's style.

Polycom CCX 500 Technical Specifications

User interface features

- า๊¿½ Gesture-based, multitouch-capable touchscreen
- � 5-inch color LCD (720 x 1280 pixel)
- ï¿⅓ 9:16 aspect ratio
- � Screensaver
- ï¿1/2 On-screen virtual keyboard
- � Voicemail support
- � Adjustable base height
- ī¿½ One USB type-A port (2.0 compliant) for media and storage applications
- ī¿½ One USB Type-C port (2.0 compliant) for media and storage applications
- ï¿⅓ Integrated Bluetooth 4.2



- � Unicode UTF-8 character support
- า๊¿½ Adjustable font size selection (regular, medium, large)
- � Normal and dark mode
- T¿½ Multilingual user interface1 including Chinese, Danish, Dutch, English (Canada/ US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, and Swedish

#### **Audio Features**

- آذِہُ Poly HD Voice technology delivers lifelike voice quality for each audio path: handset, hands-free speakerphone, and optional headset
- آذِن Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression
- าั¿½ TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex)
- ī¿½ Frequency response—100 Hz–20 kHz for handset, optional headset, and handsfree speakerphone modes
- � Codecs: G.711 (A-law and μ-law), G.729AB, G.722 (HD Voice), G.722.1 iLBC
- าั¿½ Individual volume settings with visual feedback for each audio path
- � Voice activity detection
- � Comfort noise generation
- i¿½ DTMF tone generation (RFC 2833 and in-band)
- � Low delay audio packet transmission
- � Adaptive jitter buffers
- � Packet loss concealment
- � OPUS support

### Headset and handset compatibility

- � Dedicated RJ-9 headset port
- រី¿½ Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- آذًا Compliant with ADA Section 508 Subpart B 1194.23 (all)
- ī¿½ Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- ī¿½ Compatible with commercially available TTY adapter equipment
- � USB headset support
- ï¿⅓ Bluetooth headset support

## Network and provisioning

- ï¿1/2 SIP protocol support
- ï¿⅓ SDP
- i¿1/2 IETF SIP (RFC 3261 and companion RFCs)
- � Two-port gigabit Ethernet switch
- i¿1/2 10/100/1000Base-TX across LAN and PC ports
- � Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment
- រីរ៉ូ½ Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- 121/2 Manual or dynamic host configuration protocol (DHCP) network setup
- า๊¿½ Time and date synchronization using SNTP
- Ti21/2 FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- าเป็น Provisioning and call server redundancy supported1
- ii. 1/2 QoS Support— IEEE 802.1p/Q tagging
- ï¿1/2 (VLAN), Layer 3 TOS, and DHCP
- آذاً VLAN—CDP, DHCP VLAN discovery, LLDPMED for VLAN discovery Network address translation support for static configuration and "keep-alive"
- تز½ SIP signaling
- � RTCP and RTP support



- � Event logging
- ï¿⅓ Syslog
- � Hardware diagnostics
- ï¿1/2 Status and statistics reporting
- ï¿⅓ IPv4 and IPv6
- � TCP
- UDP ½⅓ UDP
- ï¿⅓ DNS-SRV

### Security

- า๊¿½ 802.1X authentication and EAPOL media encryption via SRTP
- ï¿⅓ Transport layer security (TLS)
- � Encrypted configuration files
- � Digest authentication
- � Password login
- า๊¿½ Support for URL syntax with password for boot server address
- � HTTPS secure provisioning
- � Support for signed software executables

#### Power

- آذِرًا Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 0) 13 W (Max)
- تزرير External universal AC/DC adapter (optional) 48 VDC @ 0.52 A (25 W)
- � ENERGY STAR® rated

### Approvals

- ï¿1/2 Argentina ENACOM
- ï¿⅓ Australia RCM
- آز½ Brazil ANATEL
- � Canada ICES and NRTLC
- � China CCC and SRRC
- ï¿⅓ EEA CE Mark
- ï¿⅓ Eurasian Customs Union EAC
- ï¿⅓ India WPC
- ï¿⅓ Indonesia SDPPI
- ï¿⅓ Israel MOC
- ï¿⅓ Japan MIC and VCCI
- ï¿⅓ Malaysia SIRIM
- ï¿1/2 Mexico IFETEL and NYCE
- � NZ Telepermit
- ï¿⅓ Saudi Arabia CITC
- ï¿⅓ Singapore IMDA
- ï¿⅓ South Africa ICASA
- ï¿⅓ South Korea KC
- � Taiwan NCC
- � UAE TRA
- � USA FCC and NRTL

## Radio

- ï¿1/2 USA–FCC Part 15.247
- ï¿1/2 Canada–RSS 247 Issue2
- � EU–ETSI EN 300 328



� Japan–Article 2.1 Item 19-2� Australia–AS/NZ4268

#### Safety

� UL 62368-1

ï¿1/2 CAN/CSA C22.2 No. 62368-1-14

ï¿1⁄2 EN 62368-1

ї¿½ IEC 60950-1 and IEC 62368-1

ï¿1/2 AS/NZS 62368-1

#### Operating conditions

� Temperature: 0 to 40 °C (+32 to 104 °F) � Relative humidity: 5% to 95%, noncondensing

## Storage temperature

� -40 to +70 °C (-40 to +160 °F)

#### Contents

� Console

i¿½ Handset with handset cord (handset model only)

� Network (LAN) cable—CAT-5E

ï¿1/2 Desk stand

ï¿⅓ Setup sheet

### Size

 $\ddot{i}_{2}$  With handset: 17.8 cm x 21.6 cm x 5.2 cm WxHxD (7.0 in x 8.5 in x 2.0 in WxHxD)  $\ddot{i}_{2}$  Without handset: 10.5 cm x 21.6 cm x 5.2 cm WxHxD (4.1 in x 8.5 in x 2.0 in WxHxD)

# Weight

ï¿⅓ CCX 500 with handset carton weight: 1.28 kg (2.82 lbs) ï¿⅓ CCX 500 without handset carton weight: 0.73 kg (1.61 lbs)

Master carton quantity

� Ten (10)

Warranty

� One (1) year

Price: £269.60