

Fanvil X3S V2 IP Phone Non PoE (X3S V2)



Product Name: Fanvil X3S V2 IP Phone Non PoE (X3S V2)

Manufacturer: -

Model Number: X3S V2

Please Note: This product has been discontinued. For an alternative, please see the other Fanvil IP Phones.

Fanvil X3S V2 IP Phone Non PoE (X3S V2)

The Fanvil X3S IP Phone is an entry-level colour screen IP Phone. With all the necessary VoIP features and other extended features like EHS headset, it provides a high-quality and convenient experience for users at an affordable price.

Fanvil X3S VoIP Phone Key Features

- 4 SIP lines, 3-way conference, SIP hotspot
- 500 local phonebook, caller ID, call hold, call transfer
- 2.4" main colour display
- HD audio on speakerphone and handset
- Support EHS wireless headset
- Dual Fast ports, integrated PoE
- Stand with 2 adjustable angles of 45 and 50 degrees
- Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc.

2.4" Colour Display Bright 2.4-inch 320x240 colour display on Fanvil X3S new version IP phone, provides high-resolution graphics for the user. **Enhanced HD Audio Communication** With enhanced HD audio, Fanvil X3S/X3SP new version prevents the background noise from the external environment and presents you ideal HD audio in communication. **Support EHS headset** Free your Hands Wireless EHS headset supported by Fanvil X3S/X3SP new version through EHS cable allows you to deal with other issues while making a phone call, which is more productive in many working spaces. **Flexible Installation Mode** Not only can Fanvil X3S/X3SP new version be installed in the desktop stand mode with two different angles but also in a wall-mounted mode by an additional hanging part, addressing the diverse applications.

Fanvil X3S IP Phone - Technical Specifications

Generic

- 4 SIP Lines
- HD Voice
- 2.4-inch colour screen
- Handset / Hands-free / Headset mode
- Desktop Stand / Wall-mounted (need an additional wall hanging parts)
- Optional External Power Supply

Phone Functions

- Local Phonebook (500 entries)
- Remote Phonebook (XML/LDAP, 500 entries)
- Call logs (In/Out/Missed, 600 entries)
- Black/White List Call Filter
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)

Fanvil X3S V2 IP Phone Non PoE (X3S V2)

- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording (Through Server)
- Action URL / Active URI
- uaCSTA

Call Functions

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forward (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (With server)
- 3-way Conference
- Hot Line
- Hot desking

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723, G.726-32K, G.729AB, iLBC
- Wideband Codec: G.722
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band – DTMF-Relay (RFC2833) / SIP INFO

Network

- Physical: 10/100 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4
- IP Configuration: Static IP / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- QoS
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Protocols

- SIP2.0 over UDP/TCP/TLS

Fanvil X3S V2 IP Phone Non PoE (X3S V2)

• RTP/RTCP/SRTP
• STUN
• DHCP
• LLDP
• PPPoE
• 802.1x
• L2TP
• OpenVPN
• SNTP
• FTP/TFTP
• HTTP/HTTPS
• TR-069

Deployment & Management

• Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIPPNP/TR-069
• Web Management Portal
• Web-based Packet Dump
• Configuration Export / Import
• Phonebook Import/Export
• Firmware Upgrade
• Syslog

Physical Specifications

• Main LCD x1: 2.4-inch (320x240) Colour Screen
• Keypad: 34 keys, including: - 4 Soft-keys - 7 Function keys (Hold/Transfer/Conference/Phonebook/MWI/Headset/Redial) - 2 Line keys (With LED Indicator Light) - 4 Navigation keys - 1 OK key - 12 Standard Phone Digits keys - 3 Volume Control keys (Up/Down/Mute (Microphone)) - 1 Hands-free key (With LED Indicator Light)
• HD Handset (RJ9) x1
• Standard RJ9 Handset Wire x1
• 1.5M CAT5 Ethernet Cable x1
• Back Rack x1
• Status Indicator Light x1 (Red)
• RJ9 Port x2: Handset x1, Headset x1
• RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
• Safety Keyhole x1
• DC Power Input: 5V/0.6A
• Power Consumption: Idle 0.9~1.65W, Peak 1.8~2.95W
• Working Temperature: 0~45°C
• Working Humidity: 10~95%
• Installation:- Desktop Stand- Wall-mounted (need an additional wall hanging parts)
• Colour: Black
• Device Dimensions:- Desktop Stand (Angles 1): 169x186.3x174.5 mm- Desktop Stand (Angles 2): 169x177.6x183.7 mm- Wall-mounted: 169x115.6x212.5 mm
• Gift Box Dimensions: 274x215x68 mm
• Outer CTN Dimensions: 450x360x294 mm (10 PCS)

Please Enquire

Fanvil X3S V2 IP Phone Non PoE (X3S V2)

Options available for Fanvil X3S V2 IP Phone Non PoE (X3S V2) :

Need Product Setup / Training / Support?

[Required - 1 Hour \(+£65.00\)](#), [Required - 30 minutes \(+£40.00\)](#), [Not Required](#).

Wired Headset

[Fanvil HT201 \(+£31.00\)](#), [Fanvil HT202 \(+£43.00\)](#), [Not Required](#).

Wireless Headset

[Jabra Pro 920 Mono DECT Headset \(+£163.60\)](#), [Not Required](#).