

# DrayTek VigorAP 1000C Tri-Band 802.11ac Ceiling-Mount Mesh Wireless Access Point (VAP1000C-K)



Product Name: DrayTek VigorAP 1000C Tri-Band 802.11ac Ceiling-Mount Mesh Wireless Access Point

(VAP1000C-K)

Manufacturer: Draytek

Model Number: VAP1000C-K

Please Note: This product is currently on pre-order. For an alternative, pleasee see the VAP903-K

DrayTek VigorAP 1000C Tri-Band 802.11ac Ceiling-Mount Mesh Wireless Access Point (VAP1000C-K)

The DrayTek VigorAP 1000C is a high-performance Mesh Wireless solution, designed to expand the wireless coverage, eliminate WiFi dead zones and significantly reduce the cost of network deployments. It can also be used as a traditional access point either managed or stand alone so has the flexibility to be used how you need it.

DrayTek VigorAP 1000C Key Features

- า๊¿½ Ceiling-mount high capacity Mesh Wireless Access Point
- آذِاً Secondary 5GHz radio Dedicated Mesh backhaul, or higher client density
- تزير AC2200 11ac ' Wave 2' Tri Band Wireless
- าั¿½ Multi-SSID over Mesh Separate internal and Guest network sover Mesh
- � Power through 802.3at PoE+ or DC power adapter
- � 2nd Gigabit Ethernet port
- 17.1/2 Centrally Managed or Standalone operation

The VigorAP 1000C is a Tri-Band 802.11ac Wave 2 Mesh Wireless solution, designed to eliminate wireless drop outs, stuttering videos, slow download speeds, poor signal and WiFi dead zones. One access point acts as the controller (Mesh root) and in total up to 8 access points create an easy to manage wireless mesh. Extend coverage without running expensive cabling. Dedicate a 5Ghz radio as a Mesh Backhaul for increased Mesh performance and client capacity.

#### Mesh Wireless

DrayTek's Mesh system connects and intelligently manages a group of VigorAPs over wireless. The Self-Optimising Mesh ensures your wireless network nodes are always using the fastest path to the Mesh Root.

Tri-Band Access Point

The VigorAP 1000C provides one 2.4GHz and two 5GHz radios. Designate one 5GHz radio as a dedicated Mesh backhaul for improved Mesh network performance. Alternatively, use all 3 radios for wireless access to connect up to 384 clients per AP.

Gigabit Power Over Ethernet

The VigorAP 1000C can be powered through its Gigabit Ethernet interface with standard IEEE 802.3at PoE+ for a tidier and more convenient installation. Connect extra devices to the AP's 2nd LAN port.

Easy to Configure and Manage

The DrayTek Wireless app simplifies setting up your network. Optionally configure and monitor through one of DrayTek's management platforms - VigorACS cloud, VigorConnect, Router AP Management, or directly via the AP's Web Interface.

Ceiling Mounting

The VigorAP 1000C blends well with most home or office interior. Its adaptable deployment options include ceilings and wall mounting. The VigorAP clips into its ceiling plate for secure mounting and easier maintenance.



# DrayTek VigorAP 1000C Tri-Band 802.11ac Ceiling-Mount Mesh Wireless Access Point (VAP1000C-K)

#### Wireless Optimisation

Dedicated Backhaul for Mesh: Improves Mesh performance. 802.11ac Wave 2: Multi-User MIMO improves efficiency Band Steering: Allows 5GHz devices to achieve optimum speeds. AP Assisted Roaming: Helps clients connect to the best AP.

DrayTek VigorAP 1000C Technical Specifications

Physical Interfaces/Controls

تزارد 2 x Gigabit Ethernet LAN Ports, RJ45 (Port 1 accepts PoE Power)

� Factory Reset Button (recessed)

ï¿⅓ DC Power Socket

� 1 x Security Lock

า๊¿1/2 Built-In Temperature & Tumidity Sensor

تز½ USB 2.0 Port

#### Wireless Performance

ï¿1/2 AC2200 Class Wireless Access Point

� 2.4GHz: PHY Rate 400Mb/s

ï¿1/2 5GHz (1): PHY Rate 866Mb/s

آذًا 5GHz (2): PHY Rate 866Mb/s, optional dedicated backhaul for Mesh

# Operating Modes

ï¿⅓ Access Point

ï¿⅓ Mesh Root

آزِيً Mesh Node

ï¿1/2 Range Extender

### Wireless LAN Compatibility

� IEEE 802.11ac (Wave 1 & 2)/a/b/g/ n

īస్ట్ Frequency Band 2.4 GHz & Deration 5.8Ghz - Simultaneous Operation

� Up to 12 SSIDs per AP (4 per radio)

� Up to 128 clients per radio

ï¿⅓ 384 clients in total per AP

## 2.4GHz Wireless LAN Features

� 802.11b, 802.11g, 802.11n

� 20 / 40 MHz

� Up to 400Mb/s total Wi-Fi throughput (PHY Rate):- 802.11b/g/n: 300Mb/s PHY rate (150Mb/s per Spatial Stream)- 256-QAM: 400Mb/s (200Mb/s per Spatial Stream)

#### 5Ghz Wireless LAN Features

ï¿1/2 802.11ac (Wave 1 & Damp; 2) / 802.11n / 802.11a

� 20 / 40 / 80 MHz

� DFS/TPC Support

� Multi-User MIMO

T¿½ Extended 5Ghz Band – Channels:- 5GHz Radio 1: 36-48, 52-64- 5GHz Radio 2: 100-140

T¿½ Up to 866Mb/s WiFi throughput per 5GHz radio, 1733Mb/s total (PHY Rate):- 802.11a/n: 300Mb/s PHY rate (150Mb/s per Spatial Stream)- 802.11ac: 866Mb/s PHY rate (433Mb/s per



# DrayTek VigorAP 1000C Tri-Band 802.11ac Ceiling-Mount Mesh Wireless Access Point (VAP1000C-K)

#### Spatial Stream)

### Security Features

- าั¿½ Wireless Encryption: WPA2/WPA3\* Pre-Shared Key authentication Enterprise 802.1x authentication Also supports WPA/WEP (Not recommended)
- ï¿1/2 MAC Address Filtering (ACL) Up to 256 entries
- تزير Built in 802.1x server (PEAP / EAP-TLS)
- آز½ 802.1x RADIUS Proxy (PEAP / EAP-TLS)
- آزٰ PMK Caching & Pre-authentication
- � Wireless Client Isolation
- 12.1/2 Control Isolation of 2.4GHz and 5GHz bands
- � Hidden SSIDs (Selectable)
- � WPS WiFi Protected Setup
- � Mobile Device Management
- าั¿½ EAPOL Key Retry Disable EAPOL Key Retry to protect unpatched WLAN clients from KRACK

#### Wireless Control Features

- ï¿1/2 802.1q VLAN
- ī స్ట్రీ Up to four distinct SSIDs (for VLANs) for each radio (2.4/5Ghz)
- าั¿½ Multi-SSID over Mesh Separate internal and Guest networks over Mesh\*
- ï¿⅓ Wireless Client Status List in WUI
- � Client Limit per radio
- ī సై Client Limit per SSID
- ï¿⅓ MAC Cloning
- ï¿1/2 Built-in DHCP Server & DHCP Relay
- าั¿½ Trusted DHCP Server IP for WLAN Only specified DHCP server IP can assign IP addresses to WLAN clients
- آذِاً Station Control Time limit wireless connectivity per Station (e.g. 1 hour) & amp; set allowed Reconnection time (e.g. 1 day)
- 12/2 Device Object/Group Control Schedule Internet access for individual devices or groups
- آزا Wireless Auto On/Off Disable Wireless if VigorAP is unable to ping specified host

#### Wireless Performance Optimisation

- ï¿⅓ Airtime Fairness
- ï¿1/2 Band Steering
- ï¿1/2 AP-Assisted Client Mobility
- تزاره WMM (Wireless MultiMedia)
- า๊¿½ Bandwidth Management (Per Station / Per SSID)

# Diagnostic Features

- ï¿1/2 System Log
- ï¿⅓ Speed Test
- ï¿1/2 Traffic Graph
- � Wireless LAN Statistics
- 17.1/2 Interference Monitor Built-in Site Surveyor
- า๊¿½ Integrated Temperature & Emp; Humidity Sensor

# Management



# DrayTek VigorAP 1000C Tri-Band 802.11ac Ceiling-Mount Mesh Wireless Access Point (VAP1000C-K)

- � Web Interface (HTTP/HTTPS)
- � DHCP Client
- า๊ะ/2 TR-069 Control (For VigorACS or other TR-069 platform)
- تز½ CLI (Command Line Interface) Telnet
- า๊¿½ Access Control List for management interfaces
- ï¿1/2 Firmware upgrade by TR-069/HTTP
- īస్ట్ Central AP Management (from compatible DrayTek router/controller)
- ï¿⅓ SNMP v2, v2c, v3
- ï¿1/2 Management VLAN
- า๊ะ่ 2 Configuration File Export (with password) & Tiple Expo

#### Power Requirements

- ï¿1/2 Maximum Power Consumption: 19.2 Watt
- � DC 12V via external 100-240v AC/DC PSU
- � PoE Standards: 802.3at PoE+
- ī¿½ PoE adapter not supplied, requires PoE injector or a PoE switch such as the VigorSwitch

P1092

#### Environmental & amp; Physical

- 12.1/2 Operating Temperature: 0 ° C to 45 ° C
- � Operating Humidity: 10% to 90% (Non-condensing)
- آذِا Physical Dimensions: 176mm (width) x 176mm (depth) x 30mm (height)
- ï¿1/2 Weight: 0.5kg
- � Ceiling or Wall Mountable

# Pack Contents

- � VigorAP 1000C wireless access point
- تز1/2 Ceiling Mount Bracket & Dittings kit
- � Quick Start Guide
- � Ethernet Cable

## Certification

ï¿1/2 ROHS & amp; CE Compliant

# Warranty

تز½ Two (2) Year Manufacturer's RTB

\*Future release by firmware Upgrade

Price: \$281.51