

## Fanvil X7A Android IP Video Phone



Product Name: Fanvil X7A Android IP Video Phone

Manufacturer: Fanvil

Model Number: X7A

### Fanvil X7A Android IP Video Phone

The Fanvil X7A is a high-end intelligent IP phone that combines sound, video and applications. Based on the Android 9.0 system, the interface is easy to use. It adopts a 7-inch color touch screen, built-in Bluetooth 4.2 module and 2.4G/5G Wi-Fi module, and integrates the USB 2.0 interface. X7A provides a rich and flexible desktop-class communication product solution for the communications and scalable value-added services of the enterprise-class user.

### Fanvil X7A Key Features

- 20 SIP lines, 3-way conference, hotspot
- 7" capacity color touch-screen
- HD voice: HD handset, HD speaker
- Built-in Bluetooth 4.2 and 2.4G/5G Wi-Fi
- Up to 112 DSS keys available at the display
- Video Codec H.264 for receiving video calls
- Dual Gigabit ports, integrated PoE
- Stand with 2 adjustable angles of 40 and 50 degrees
- Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc.

### Fanvil X7A- Technical Specifications

#### Generic

- 20 SIP Lines
- HD Voice
- Support receiving Video call
- PoE Enabled
- 7-inch (1024x600) color touch screen
- Handset / Hands-free / Headset mode
- Intelligent DSS Keys(Virtual buttons)
- Optional External Power Supply/Display

#### Phone Features

- Android 9.0 OS
- Local Phonebook (2000 entries)
- Remote Phonebook (XML/LDAP, 2000 entries)
- Call logs (In/out/missed, 1000 entries)
- Black/White List Call Filter
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Built-in Bluetooth 4.2: Support Bluetooth headset
- Built-in Wi-Fi: 2.4GHz, 802.11 b/g/n
- 5GHz, 802.11 a/n/ac
- Support Recording
- Action URL / Active URI
- uaCSTA

#### Call Features

## Fanvil X7A Android IP Video Phone

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial&#61548; Do-Not-Disturb
- Auto-Answering
- Voice Message (On server)
- 3-way Conference
- Hot Line
- Hot desking

### Video

- Wideband codec: G.722
- Narrowband codec: G.711(A&mu;), G.723.1,
- G.729AB, iLBC, AMR
- DTMF: In-band, Out-of-band(RFC 2833) and
- SIP INFO
- Full-duplex hands-free speaker phone with
- AEC (Max filter length &ndash; 128ms)
- Voice Activity Detection (VAD)
- Comfort Noise Generation (CNG)
- Adaptive jitter buffer
- Packet loss concealment (PLC)
- Audio format: WAV/MP3/OGG
- Frame rate selection: 5~30fps
- Video from remote site can be displayed in full screen

### Deployment and Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web Management Portal
- Supports the third party communication APP
- Supports Web, Telnet
- Supports encrypted configuration files download with AES
- Supports Web upgrade
- Supports factory reset data

### Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.729AB, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Noise Reduction (NR)
- Packet Loss Concealment (PLC)

## Fanvil X7A Android IP Video Phone

- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band & DTMF-Relay(RFC2833) / SIP INFO

### Network

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4
- IP Configuration: Static / DHCP
- Network Access Control: 802.1x
- VPN: OpenVPN (Requires third-party app support)
- VLAN
- LLDP
- CDP
- QoS

### Physical Features

- LCD x1: 7 inch (1024x600) color-screen LCD
- Keypad: 26 keys, including
- 5 Function keys (Hold, MWI, Mute, Headset, Redial)
- 4 Navigation keys
- 1 OK key
- 1 Return key
- 12 Standard Phone Digits keys
- 2 Volume Control keys, Up/Down
- 1 Hands-free key
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5 Ethernet Cable x1
- Back Rack x1
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- USB2.0 Port x1: Standard A, Connect with Flash Driver
- Safety keyhole x1
- Power: 5V/2A or PoE
- Power Consumption (PoE): 1.596~11.86W
- Power Consumption (Adapter): 0.907~9.38W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation: Desktop Stand
- Color: Black
- Device Dimensions
- Desktop Stand (Angles 1): 268x185x189mm
- Desktop Stand (Angles 2): 268x201x168mm
- Gift Box Dimensions: 304x297x66mm
- Outer CTN Dimensions: 616x358x329mm (10 PCS)

### Protocols

- SIP2.0 over
- UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP/CDP

## Fanvil X7A Android IP Video Phone

ï¿½ LLDP  
ï¿½ PPPoE  
ï¿½ 802.1x  
ï¿½ OpenVPN (Requires third-party app support)  
ï¿½ SNTP  
ï¿½ FTP/TFTP  
ï¿½ HTTP/HTTPS  
ï¿½ TR-069

**Price: £207.00**

Options available for Fanvil X7A Android IP Video Phone :

### Headset

Plantronics CS520 binaural headset and adapter cable (+£265.89), Jabra Pro 920 headset and adapter (+£143.40), Fanvil HT202 binaural wideband headset (+£33.00), - Not Required -, Plantronics CS540 monaural headset and adapter cable (+£220.00), Fanvil HT201 monaural wideband headset (+£20.00).

### UK PSU

Not Required, Required (+£8.60).

### Fanvil CM60 USB Camera

Not Required, Required (+£43.00).