

Fanvil H2U Compact IP Phone

Product Name: Fanvil H2U Compact IP Phone Manufacturer: Fanvil Model Number: H2U

Please Note: Customise the label of the phone free of charge for orders of 200 or more. For smaller orders, there will be a fee of £50. Lead time of 14 days applies. Contact us for more information.

Fanvil H2U Compact IP Phone

The Fanvil H2U possesses brand new features including 2 SIP lines, 10 speed dial keys, 1 programmable DSS key and a HD speaker on handset. Supporting desktop and wall-mounted mode, PoE and power supply charging mode, Fanvil H2U is more than a hotel phone and also can be applied in multiple scenarios, such as school, hospital, supermarket and residence. Fanvil H2U Key Features

ï¿1∕2 2 SIP Lines


- ï¿1/2 HD Audio with wideband Codec: G.722, Opus
- ï¿1/2 10 speed dial keys, 1 programmable DSS Key
- ï¿1/2 3-way Conference
- ï¿1/2 Desk/wall-mounted mode
- ï¿1/2 Handset / Hands-free mode
- ï¿1/2 10/100 Mbps
- ï¿¹/₂ PoE/Power adaptor
- ï¿1/2 Exquisite and fashionable product appearance
- ï¿1/2 Easy installation and configuration
- i¿1/2 Economical and Environmental friendly product concepts
- ï¿1/2 Can store 10 shortcut numbers, long press to achieve speed dial
- ï¿¹/₂ Adaptive 10/100Mbps network port, support POE power supply
- � Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc.

Considerate Design for Varied ScenariosTiny and fully-featured, Fanvil H2U supports PoE/power supply charging as well as desktop/wall-mounted mode,which can be applied in different scenarios flexibly.Customisable Keys, One-click Communication10 speed dial keys to customise different services, 1 programmable DSS keys for different functions and speed dial list.Support SIP HotspotFanvil H2U IP phones can share one number from the server. When a call comes in, each extension phone will ring together to make sure you won't miss a call. Fanvil H2U - Technical Specifications Generic

i¿½ 2 SIP Lines
i¿½ HD Voice
i¿½ PoE Enabled
i¿½ Handset / Hands-free mode
i¿½ Intelligent DSS Keys
i¿½ Desktop/wall mount mode
i¿½ Optional External Power Supply

Phone Functions

� Call logs (In/Out/Missed, Max support 600 records in the web)
 � Programmable DSS
 � Action URL / Active URI
 � Web dial





Fanvil H2U Compact IP Phone

Call Functions

� Call out / Answer
� Mute / Unmute
� Hands-free / Cancel hands-free
� Call Hold / Resume
� Speed Dial
� Redial
� Auto-Answering
� 3-way Conference
� Hot Line
� Hot desking

Audio

i¿½ Narrowband Codec: G.711a/u, G.726, G.729A, iLBC
i¿½ Wideband Codec: G.722, Opus
i¿½ Acoustic Echo Canceller (AEC)
i¿½ Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise
Estimation (BNE) / Noise Reduction (NR)
i¿½ Packet Loss Concealment (PLC)
i¿½ Dynamic Adaptive Jitter Buffer
i¿½ DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

Network

i¿½ 10/100 Mbps Ethernet i¿½ IP Mode:IPv4/IPv6/IPv4&IPv6 i¿½ IP Configuration: Static / DHCP / PPPoE i¿½ Network Access Control: 802.1x i¿½ VPN: L2TP / OpenVPN i¿½ VLAN i¿½ QoS i¿½ RTCP-XR (RFC3611), VQ-RTCPXR(RFC6035)

Protocols

� SIP2.0 over UDP/TCP/TLS
� RTP/RTCP/SRTP
ï½ STUN
ï½ DHCP
ï½ LDP
ï½ LLDP
ï½ 802.1x
ĩ½ 22TP
ï½ OpenVPN
ï½ SNTP
ĩ½ FTP/TFTP
ĩ½ HTTP/HTTPS
ĩ½ TR-069

Deployment & amp; Management



Fanvil H2U Compact IP Phone

ïز¹/₂ Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069

ï¿1/2 Web Management Portal

ï¿1⁄2 Web-based Packet Dump

 $\ddot{\imath}_{\mathcal{E}}^{1/_{\!\!2}}$ Configuration Export / Import

ï¿1/2 Firmware Upgrade

� Syslog

Physical Specifications

i¿½ Keypad: 19 keys, including:- 12 Standard Phone Digits keys(0-9: Speed dial configuration on webpage) - 3 Function keys (Hands-free , Redial ,Hold) - 3 Volume Control keys, Up/Down/Mute(with red colour LED) - 1 DSS key
i¿½ Status indicator (two-colour LED) ×1
i¿½ HD Handset (RJ11) ×1
i¿½ Standard RJ11 Handset Cord ×1
i¿½ RJ11 Port ×1
i¿½ RJ45 Port ×1
i¿½ Power Consumption(PoE): 1.58W~3.47W
i¿½ Power Consumption(Adapter): 0.87~2.23W
i¿½ Working Temperature: 0~45°C
i¿½ Installation: Desktop/wall mount
i¿½ Colour: Black/white

ı
 $\gtrsim 12$ Device Dimensions: 55.8 x 215 x 57.8mm

Price: £27.80

Options available for Fanvil H2U Compact IP Phone :

Need Product Setup / Training / Support?

Required - 30 minutes (+£40.00), Not Required, Required - 1 Hour (+£65.00).

Power supply unit

Not Required, UK-PSU-5V-2A (+£6.30).