

Fanvil H3 Hotel VoIP Phone - White



Product Name: Fanvil H3 Hotel VoIP Phone - White

Manufacturer: Fanvil

Model Number: H3 White

Please Note: Customise the front panel of the phone free of charge for orders of 200 or more. For smaller orders, there will be a fee of £200. Lead time of 14 days applies. Contact us for more information.

Fanvil H3 Hotel VoIP Phone - White

The Fanvil H3W is an IP hotel phone with HD voice and 6 programmable soft keys. The H3W has a full duplex, hands free speaker phone with echo cancellation, and many more standard phone features such as call transfer, call holding, and call waiting. This product also comes with a power supply included.

Fanvil H3W VoIP Phone Key Features

- 1 SIP line
- 1 USB Port for Phone Charging
- 6 Programmable Keys for Speed Dial Functions
- Support PoE
- Indicator Light
- Call hold, Redial, Call Transfer, Hotline, Voice Mail etc.
- Easy installation and configuration
- High Interoperability - Compatible with major platforms: 3CX, Broadsoft, Elastix, Asterisk, Xorcom, etc.

Elegant Outlook Fanvil H3W is the IP Phone designed for hotels. With stylish, fresh appearance, excellent voice quality, and matching integrated communication platform, it can become a new generation of hotel intelligent terminal equipment.

6 Programmable Soft Keys The H3W comes with 6 programmable soft keys for maximum flexibility. Choose from a wide range of options, such as housekeeping, ticketing, switchboard, or room service.

Fanvil H3W Technical Specification

Generic

- 1 SIP Line
- POE Enabled
- Handset / Hands-free mode
- Intelligent DSS Keys (speed dial key)
- Desktop
- Optional External Power Supply

Call Features

- Call out / Answer
- Mute / Unmute (microphone)
- Call Hold / Resume
- Call Waiting
- Call Transfer (Attended/Unattended)
- Speed dial
- Intercom
- Redial
- Voice Message (on server)

Fanvil H3 Hotel VoIP Phone - White

- 1/2 Hot Line
- 1/2 Hot desking

Phone Features

- 1/2 Call logs with missed calls/ incoming calls/ outgoing calls
- 1/2 Max support 600 records(web)
- 1/2 Dial without registration
- 1/2 LED light
- 1/2 Programmable DSS keys
- 1/2 Custom LCD display text and logo(Only support for H5)
- 1/2 Action URL / Active URI
- 1/2 Web dial

Audio

- 1/2 Audio CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB, G.722
- 1/2 Full-duplex Acoustic Echo Canceller (AEC)
- 1/2 Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- 1/2 Packet Loss Concealment (PLC)
- 1/2 Dynamic Adaptive Jitter Buffer up to 300ms
- 1/2 DTMF: In-band, Out-of-Band - DTMF(RFC2833) / SIP INFO

Networking

- 1/2 10/100Mbps Ethernet, dual bridged port for PC bypass
- 1/2 IP Configuration: Static / DHCP / PPPoE
- 1/2 Network Access Control: 802.1x
- 1/2 VPN: L2TP / OpenVPN
- 1/2 VLAN
- 1/2 QoS

Protocols

- 1/2 SIP2.0 over UDP/TCP/TLS
- 1/2 RTP/RTCP/SRTP
- 1/2 STUN
- 1/2 DHCP
- 1/2 PPPoE
- 1/2 802.1x
- 1/2 L2TP
- 1/2 OpenVPN
- 1/2 SNTP
- 1/2 FTP/TFTP
- 1/2 HTTP/HTTPS
- 1/2 TR-069

Deployment & Maintenance

- 1/2 Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069
- 1/2 Web Management Portal
- 1/2 Web-based Packet-dump
- 1/2 Configuration Export / Import
- 1/2 Firmware Upgrade

Fanvil H3 Hotel VoIP Phone - White

1/2 Syslog

Physical Specifications

1/2 Keypad: 26 keys, including:- 6 DSS Key- 4 Function keys (Hold, Call Transfer, Redial, MWI)- 12 Standard Phone Digits keys- 3 Volume Control keys, Lower/Increase/Mute (Microphone)- 1 Hands-free

1/2 HD Handset (RJ9) x1

1/2 Standard RJ9 Handset Wire x1

1/2 1.5M CAT5 Ethernet Cable x1

1/2 RJ9 Port x1: Handset x1

1/2 RJ45 Port x2: Network x1, PC x1 (Bridged to Network)

1/2 USB Port x1: Standard A, Only used for mobile phone charging

1/2 DC Power Input: 5V / 1A

1/2 Power Consumption: Idle 1.8W~2.5W, Peak 3W~4.5W

1/2 Working Temperature: 0~40°C

1/2 Working Humidity: 10~95%

1/2 Installation: Desktop Stand

1/2 Colour: Black/White

1/2 Device Dimensions: 151.7x193.2x131.7mm

Price: £46.40

Options available for Fanvil H3 Hotel VoIP Phone - White :

Need Product Setup / Training / Support?

Not Required, Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00).

Power supply unit

UK-PSU-5V (+£7.10), Not Required.