

# Draytek VigorSwitch G2540x 54-Port Layer 2+ Managed 10G Switch

- Harting Harting Har

Product Name: Draytek VigorSwitch G2540x 54-Port Layer 2+ Managed 10G Switch

Manufacturer: -

Model Number: VSG2540X-K

Please Note: This product has been discontinued. Please see the Draytek VigorSwitch P2540x.

Draytek VigorSwitch G2540x 54-Port Layer 2+ Managed 10G Switch

The Draytek VigorSwitch G2540x is a Layer 2+ Managed 10 Gbps switch. With 48x Gigabit Ethernet PoE+ ports providing 400W power budget and 6x SFP+ 10Gbps Fiber links. Supporting advanced Layer 3 features, DHCP Server and VLAN Routing, VigorSwitch P2540x improves network efficiency and helps your LAN network to work continuously even when the gateway is offline, which is ideal to be placed as the core switch in SME/SMB.

Draytek VigorSwitch G2540x Key Features

ï¿1/2 48x GbE 10/100/1000Mbps Ethernet, RJ-45

آز½ 6x 10G SFP+ 1000Mbps/10Gpbs fiber slot

� 216 Gbps Switching Capacity

� 160.7 Mpps Forwarding Rate

� 16 Mbit Buffer Size

� Auto Surveillance & mp; Voice VLAN

� ONVIF-Friendly

ï¿⅓ Wire-Speed VLAN Routing

ï¿⅓ IP Conflict Prevention

ï¿1/2 Access Control

� QoS

ï¿⅓ IPv6 Ready

ï¿⅓ Web-Based GUI

� Multiple Admin Accounts

� Central Switch Management

� Energy-Efficient Ethernet

DHCP Server & amp; VLAN Routing

In a large LAN network, much traffic doesn't go to Internet, but to the servers in LAN. For example, IP cameras store videos to NVR, IP phones register to PBX, clients access to file server, etc.

L2+ switch with DHCP server and VLAN routing functionalities, as the device receiving traffic before the router, is ideal to share the loading of your router and to help your LAN network to work continuously even when the router is offline.

As a DHCP server, VigorSwitch assigns dynamic IP addresses for up to 8 VLANs. With VLAN routing, VigorSwitch supports up to 512 routes.

Bind IP to MAC

As a DHCP Server, layer 2+ VigorSwitch helps reserving IP addresses for your important devices that most users will access frequently.

**ONVIF-Friendly** 

Recognise the ONVIF devices in different VLANs, display surveillance topology, provide UI for video streaming and device maintenance.

Draytek VigorSwitch G2540x Technical Specifications Interface

� LAN Port: - 48x 10/100/1000Mbps Ethernet, RJ-45- 6x 1000Mbps/10Gbps SFP+ slot � Console Port: 1x RJ-45



# Draytek VigorSwitch G2540x 54-Port Layer 2+ Managed 10G Switch

� Button: 1x Factory Reset Button

### Capacity

ï¿1/2 Buffer Size: 16 Mbit

ï¿⅓ Switching Capacity: 216 Gbps

าั¿½ Forwarding Rate: 160.7 Mpps (64 bytes)

� MAC Address Table: 32k � Jumbo Frame: Up to 12 KB � L3 Routing Table: Max. 2k

#### **Networking Standards**

ï¿1/2 IP Version: IPv4, IPv6

T¿½ Ethernet Standards:- 802.3 10Base-T- 802.3u 100Base-T- 802.3ab 1000Base-T- IEEE802.3ae 10GBase-X- 802.3x Flow Control- 802.3 Auto-Negotiation- 802.1q Tag-based VLAN- 802.1p Class of Service- 802.1d STP- 802.1w RSTP- 802.1s MSTP- 802.3ad LACP-802.1ad QinQ- 802.1x Port Access Control- 802.1AB LLDP- 802.3az EEE

## **VLAN**

ï¿⅓ Max.Number of VLAN: 256

าั¿½ VLAN Type:- 802.1q Tag-based- MAC-based- Protocol-Based- Management VLAN- Voice

VLAN- Surveillance VLAN

i¿½ 802.1x Guest VLAN: Yes

i¿½ Port Isolation: Yes

i¿½ GVRP: Yes

� Q-in-Q: Basic

### **ONVIF Surveillance**

� Discovery: Yes

ï¿⅓ Surveillance Topology: Yes ï¿⅓ Real-Time Video Streaming: Yes

تزاير ONVIF Device Maintenance: Device Info, Reset Factory Default, Time Settings, Reboot

#### QoS

ï¿1/2 Number of QoS Queues: 8

� Queue Scheduling: SPQ, WRR

าั¿½ CoS (Class of Service): 802.1p CoS, DSCP, CoS-DSCP, IP Precedence

� Rate Limit & Shaping: Yes

## Security

ï¿1/2 Access Control List: MAC, IPv4, IPv6

าั¿1/2 Storm Control: Broadcast, Unknown Multicast, Unknown Unicast

� DoS Defense: Yes

� 802.1x Port Access Control: Yes

� IP Source Guard: Yes � IP Conflict Detection: Yes



# Draytek VigorSwitch G2540x 54-Port Layer 2+ Managed 10G Switch

- ï¿⅓ IP Conflict Prevention: Yes
- ï¿1/2 Loop Protection: Yes
- � Dynamic ARP Inspection: Yes
- � DHCP Snooping with Option 82: Yes

# Link Aggregation

- � Max. Number of Group: 8
- � Max. Number of Member in Each Group: 8
- ï¿1/2 Type: Static, LACP
- آذًا Traffic Load Balancing: MAC Address, IP/MAC Address

#### Multicast

- ï¿1/2 IGMP Snooping: v2, v3 (BISS)
- ï¿⅓ IGMP Querier: Yes
- � MLD Snooping: v1, v2 (Basic)
- � Max. Number of Multicast Group: 256
- تزار Group Throttling: Yes
- i¿½ Group Filtering: Yes
- � MVR (Multicast VLAN Registration): Yes

### Layer 3 Features

� Static Route: Yes � VLAN Route: Yes � DHCP Server: Yes

# AAA

- ï¿1/2 Authentication Server: RADIUS, TACACS+
- � Port Authorisation: Yes � Management Account: Yes
- � RADIUS Attribute Assignment: User Privilege, VLAN
- � Accounting: Yes
- ïز½ Multiple Server: Yes

# Management

- ï¿1/2 Web Interface: HTTP, HTTPS
- آذِ1/2 Command Line Interface: Telnet, SSH
- � OpenVPN Client: Certificate-based authentication
- าั¿1/2 User Authentication: Local Database, RADIUS, TACACS+
- تز½ sFlow: Yes
- ï¿⅓ SNMP: v1, v2c, v3
- تزير Private MIB: Yes
- ï¿⅓ RMON Group: 1, 2, 3, 9
- 17.1/2 LLDP: LLDP-MED, Media Endpoint Discovery Extension
- ī¿½ Mail Alert: Port Status, Port Speed, System Restart, IP Conflict
- ï¿⅓ Syslog: Yes
- � 2-Level Admin Privilege: Yes
- � Multiple Admin Accounts: Yes
- ï¿⅓ Managed by VigorRouter SWM: Yes



# Draytek VigorSwitch G2540x 54-Port Layer 2+ Managed 10G Switch

- ï¿⅓ Managed by VigorConnect: Yes
- ï¿⅓ Managed by VigorACS 2: Yes
- ï¿⅓ Config File Export/Import: Yes
- ï¿⅓ Dual Image: Yes
- ï¿⅓ SNTP (Simple Network Time Protocol): Yes
- า๊¿½ Diagnostics Tools: Port Mirroring, Ping, Cable Test

# Physical

- � 19-inch Rack Mountable: Mounting Kit Included
- ï¿⅓ Max. Power Consumption: 52 watts
- � Dimension (mm): 441(W) x 270(D) x 45(H)
- ï¿1/2 Weight: 3.97 kg (8 lb)
- � Operating Temperature: 0 to 50°C
- ï¿1/2 Storage Temperature: -20 to 70°C
- � Operating Humidity: 10 to 90% non-condensing
- า๊¿½ Storage Humidity: 5 to 90% non-condensing
- ï¿⅓ Certificate: CE

# **Please Enquire**