

Yealink T30P Entry Level IP Phone (SIP-T30P)



Product Name: Yealink T30P Entry Level IP Phone (SIP-T30P)

Manufacturer: -

Model Number: SIP-T30P

Please Note: This product has been discontinued. For an alternative, please see the SIP-T31P.

Yealink T30P Entry Level IP Phone (SIP-T30P)

The Yealink T30P is a classic IP phone for small business users. The SIP-T30P delivers a fashionable and user-friendly dialing experience. It has a generously large 132x64-pixel graphical LCD that guarantees an easier access to much more visual information at a glance. Dual 10/100 Mbps network ports with integrated PoE makes the SIP-T30P an ideal choice for extended network use. The SIP-T30P offers support for single VoIP account and includes 5-way local conferencing. It includes EHS35 support for Yealink wireless headset plus adjustable multi-angle stand support and has been designed very specifically for efficient work.

Yealink T30P Key Features

- Yealink HD Voice
- 132x64-pixel graphical LCD
- Two-port 10/100M Ethernet Switch
- PoE support
- Opus codec support
- One SIP account
- Local 5-way conferencing
- Support EHS Wireless Headset
- Unified Firmware
- Support YDMP/YMCS
- Stand with 2 adjustable angles
- Wall mountable

Stronger Performance, More Possibilities

Equipped with a powerful chip, the T3 series features a stronger computing ability and more upgraded functions, which ensures a higher productivity and smoother office experience. Due to great performance, T3 series is capable of offering more services for different business demands.

Superior HD Audio, Better Communication

The Yealink T3 series provides distraction-free communications with industry leading Smart Noise Filtering Technology, which delivers excellent sound quality without extraneous noises and allows fluent conversations.

Classic Design, Practical Details

Designed by Yealink original team, T3 series inherits the design concept of Yealink IP phone family. The advanced design including modern appearances and ergonomic details enables an easier and friendly operation experience to users.

All in One Platform, Convenient Management

Proven reliability and integrations for Yealink Device Management Platform, installed the unified firmware, T3 series is simple to deploy and manage, which allows a significant reduction in the operation and maintenance cost.

Yealink T30P - Technical Specifications

Audio Features

- HD voice: HD handset, HD speaker
- Smart Noise Filtering
- Wideband codec: Opus, G.722
- Narrowband codec: G.711(Aμ), G.723.1, G.729AB, G.726, iLBC

Yealink T30P Entry Level IP Phone (SIP-T30P)

- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- One VoIP account
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 5-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan
- XML Browser, action URL/URI
- Integrated screenshots
- RTCP-XR, VQ-RTCPXR
- Enhanced DSS Key

Directory

- Local phonebook up to 1000 entries
- Black list
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

IP-PBX Features

- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating
- Call park, call pickup
- Executive and Assistant
- Centralised call recording
- Visual voice mail
- Call recording

Display and Indicator

- 2.3" 132x64-pixel graphical LCD
- LED for call and message waiting indication
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Power saving

Feature keys

- 6 features keys: transfer, message, headset, redial, mute, hands-free speakerphone
- 5 navigation keys

Yealink T30P Entry Level IP Phone (SIP-T30P)

• 1/2 Volume control keys

Interface

• 1/2 2 x RJ45 10/100M Ethernet ports
• 1/2 Power over Ethernet (IEEE 802.3af), class 2
• 1/2 1 x RJ9 (4P4C) handset port
• 1/2 1 x RJ9 (4P4C) headset port

Other Physical Features

• 1/2 Colour: Classic Grey
• 1/2 Wall mountable
• 1/2 External Yealink AC adapter AC 100~240V input and DC 5V/600mA output
• 1/2 Power consumption (PSU): 2-3W
• 1/2 Power consumption (PoE): 3-4W
• 1/2 Dimension (W*D*H*T): 185mm*189mm*162mm*50mm
• 1/2 Operating humidity: 10~95%
• 1/2 Operating temperature: -10~50°C (+14~122°F)

Management

• 1/2 Configuration: browser/phone/auto-provision
• 1/2 Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
• 1/2 Auto-provision with PnP
• 1/2 Zero-sp-touch, TR-069
• 1/2 Phone lock for personal privacy protection
• 1/2 Reset to factory, reboot
• 1/2 Package tracing export, system log

Network and Security

• 1/2 SIP v1 (RFC2543), v2 (RFC3261)
• 1/2 Call server redundancy supported
• 1/2 NAT traversal: STUN mode
• 1/2 Proxy mode and peer-to-peer SIP link mode
• 1/2 IP assignment: static/DHCP
• 1/2 HTTP/HTTPS web server
• 1/2 Time and date synchronisation using SNTP
• 1/2 UDP/TCP/DNS-SRV (RFC 3263)
• 1/2 QoS: 802.1p/Q tagging (VLAN), Layer 3 ToSDSCP
• 1/2 SRTP for voice
• 1/2 Transport Layer Security (TLS)
• 1/2 HTTPS certificate manager
• 1/2 AES encryption for configuration file
• 1/2 Digest authentication
• 1/2 OpenVPN, IEEE802.1X
• 1/2 IPv6
• 1/2 LLDP/CDP/DHCP VLAN
• 1/2 ICE

Package Features

• 1/2 Package content:- Yealink SIP-T30P IP phone- Handset with handset cord- Ethernet Cable (1.5m CAT5E UTP Cable)- Stand- Quick Start Guide- Power Adapter (Optional)

Yealink T30P Entry Level IP Phone (SIP-T30P)

ï¿½ Qty/CTN: 10 PCS
ï¿½ N.W/CTN: 9.48 kg
ï¿½ G.W/CTN: 10.45 kg
ï¿½ Giftbox size: 213 mm*210 mm*103 mm
ï¿½ Carton Meas: 535 mm*443 mm*227 mm

Please Enquire

Options available for Yealink T30P Entry Level IP Phone (SIP-T30P) :

Need Product Setup / Training / Support?

Required - 1 Hour (+Â£75.00), Not Required.

Power Supply Required?

UK PSU Required (+Â£3.70), Not Required.

Headset

YHS33 Headset (+Â£25.00), Not required.