

Yeastar P570 VoIP PBX



Product Name: Yeastar P570 VoIP PBX

Manufacturer: Yeastar Model Number: P570

Yeastar P570 VoIP PBX

The Yeastar P570 VoIP PBX is an adaptive, professional, reliable PBX phone system for SMEs. It alllows businessses to to have uninterruped communications in at all times in a fully fledged system.

Yeastar P570 Key Features

ï¿1/2 Users 300 / 500

ï¿1/2 Max Concurrent Calls 60 / 120

i¿1/2 Max Call Centre Agents 300 / 500

آز½ Max FXS Ports 16

آزٰ½ Max BRI Ports 16

ï¿1/2 Max GSM/4G Ports 6

ï¿1/2 Max E1/T1/J1 Ports 2

� Expandable D30 2

PBX Plus Call CentreP-Series PBX System introduces an inbound call center solution to improve agent efficiency, responsiveness, and ultimately customer satisfaction for SMEs running service centers. Besides standard communications features, Call Distribution, Queue Panel, Wallboard, SLA, and Call Reports are all designed to support more proactive performance monitoring, reporting, and management.

PBX Plus UC ClientsDesigned to enhance communication experience and efficiency, Linkus UC Clients allow P-Series PBX users to easily access a comprehensive suite of calling, conference, voicemail, presence, enterprise contacts, collaboration from a single interface using mobile phones, desktops, and web browsers. Employees can stay connected with colleagues and customers where, when, and however they prefer.

Contacts DirctoryP-Series PBX System makes it easy and intuitive to organise contacts for SMEs. Users can both add external contacts to create a centralized, company-wide directory and manage their personal contact entries, benefiting from the caller ID match and speed dial. Either company or personal contacts will be synced across Linkus UC Clients, enabling easy access and dialing for in-office, mobile, and remote workers

Remote WorkingP-Series PBX System helps SMEs adapt to the new normal of working from home by enabling BYOD mobility, reducing security and network administration challenges, supporting remote control and management, and combining team collaborations. With teleworkingfriendly features available out of the box, the dispersed teams unified under the same PBX system can remain engaged and productive.

Yeastar P570 - Technical Specifications General

ï¿1/2 Users 300 / 500

ï¿1/2 Max Concurrent Calls 60 / 120

ï¿1/2 Max Call Center Agents 300 / 500

آزٰ½ Max FXS Ports 16

ï¿1/2 Max FXO/BRI Ports 16

ï¿1/2 Max GSM/3G/4G Ports 6

ï¿1/2 Max E1/T1/J1 Ports 2

� Expandable D30 2

17.1/2 Transport Protocol UDP, TCP, TLS, SRTP

آذِرُ Voice Codec G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC

ï¿1/2 Video Codec H263, H263P, H264, MPEG4

� DTMF In-band, RFC4733, RFC2833, SIP INFO



Yeastar P570 VoIP PBX

- آزٰ NFC Read/Write
- � Ethernet interfaces 2 x (10/100/1000 Mbps)
- ï¿1/2 Hard disk 1 SATA (Up to 2TB)
- ï¿⅓ USB 1 (up to 2TB)
- ї
¿½ Power Supply AC 100-240V 50/60HZ 1.5A max
- \ddot{i} ¿½ Size (L x W x H) (cm) 44 x 25.2 x 4.4
- ï¿⅓ Weight 2.38 kg
- ï¿⅓ Form Factor 1U Rack-mount
- ï¿1/2 Environment
- $\ddot{i}_{\dot{c}}$ Operation Range: 0°C to 40°C, 32°F to 104°F $\ddot{i}_{\dot{c}}$ Storage Range: -20°C to 65°C, -4°F to 149°F
- � Humidity: 10-90% non-condensing

Price: £2,749.20