

# Dinstar UC2000-VF-8T GSM/LTE VoIP Gateway

Product Name: Dinstar UC2000-VF-8T GSM/LTE VoIP Gateway

Manufacturer: Dinstar

Model Number: UC2000-VF-8T

#### Dinstar UC2000-VF-8T GSM/LTE VoIP Gateway

The Dinstar UC2000-VF-8T is a 16 channels wireless gateway based on DINSTAR new hardware platform and powerful embedded CPU, leveraging state-of-art and latest VoIP / SIP technology, which enables the smooth transit between 4G/3G/2G mobile network and VoIP networks. Supporting up to 16 concurrent calls in a single 1U box, makes it an ideal choice for users. Moreover, with open API, it allows users to build their own application software to send SMS/USSD messages or bulk SMS messages, or push their text messages from email, HTTP etc. It is suitable for enterprises, multi-site organisations, call centers and areas with limited landline like rural area to cut down telephony costs and enable easy & Dinstar UC2000-VF-8T Key Features

ï¿1/2 Up to 16 Channels GSM or LTE

� Powerful Embedded CPU

าั¿½ Compatible with LTE-FDD/LTE-TDD/WCDMA/GSM Networks

تز½ Compatible with Mainstream VoIP Platform

ï¿⅓ Hot Swappable SIM Cards

� Voice over LTE (VoLTE)

تز½ HTTP API for SMS Application Integration

า๊¿1/2 SMS to Email & SMS; Email to SMS

17.1/2 Flexible Dial Rules & Manipulation Rules

آزِ½ Auto CLIP

� Remote SIMs Management (optional)

Dinstar UC2000-VF-8T - Technical Specifications Hardware Interfaces

� Mobile: 16 Channels � SIM Card slots: 16

� Antennas Connectors: SMA

� Ethernet Interfaces: 2\*10/100/1000 Base-T, RJ45 � LED Indicators: Power, RUN, Channel indicator

ï¿1/2 Console: 1\* RS232 (USB-B connector)

ï¿1/2 RST/PWR Button

VoIP & amp; Media

ï¿1/2 Protocol: SIP v2.0, RFC3261

� SIP UDP/TCP/TLS

آزِ½ RTP/SRTP

Τέ.½ Codecs: G.711A/U, G.723.1, G.729A/B, G.722, AMR, OPUS(TBD)

ï¿⅓ Silence Suppression

� Comfort Noise Generator(CNG)

� Voice Activity Detection(VAD)

� Echo Cancellation � Dynamic Jitter Buffer

� DTMF: RFC2833, SIP Info

� Call Progress Tone Generation

� Programmable Gain Control

آذِ NAT: STUN, Dynamic NAT, Static NAT



# Dinstar UC2000-VF-8T GSM/LTE VoIP Gateway

### Frequency Bands(2G/3G)

- าั¿½ UC2000-VF-16G: GSM Gateway: 850/900/1800/1900MHz
- � UC2000-VF-16W: WCDMA Gateway with two options
- ї¿½ A: WCDMA 850/1900MHz and GSM 850/900/1800/1900MHz;
- ï¿1/2 B: WCDMA 900/2100MHz and GSM 900/1800MHz

## LTE Frequency Bands

- ï¿1/2 Type A:- FDD: B2/B4/B12- WCDMA: B2/B4/B5
- � Type E:- FDD:B1/B3/B5/B7/B8/B20- TDD: B38/B40/B41- WCDMA: B1/B5/B8-

GSM:900/1800MHz

- � Type V: FDD:B4/B13 � Type J:- FDD:B1/B3/B8/B18/B19/B26- TDD:B41- WCDMA:B1/B6/B8/B19
- Ti¿1/2 Type AU:- FDD:B1/B2/B3/B4/B5/B7/B8/B28- TDD:B40- WCDMA: B1/B2/B5/B8- GSM:

850/900/1800/1900

#### Software Features

- ï¿1/2 Mobile to VoIP, VoIP to Mobile
- � SIP Trunk and Trunk Group
- � Caller/Called Number Manipulation Rules
- � SIP Codes Mapping
- ï¿1/2 White/Black List
- ï¿⅓ PSTN Hotline
- تز½ VoIP Hotline
- � Abnormal Call Monitor
- � Minutes Limitation for Ports/Single Call
- � Balance Check
- � Low Balance Alarm
- � Auto Update SIM Number
- � Random Call Interval
- � Auto CLIP Routing
- � Signaling & Encryption(DBO)
- ï¿1/2 Auto SIP Account
- � PPTP/L2TP/OpenVPN

### Mobile Features

- � SMS/USSD/PIN
- � Encoding: Unicode/ASCII
- آزٰ½ HTTP API for SMS
- � SMPP for SMS
- � Polarity Reversal
- � CID/CLIR
- ï¿1/2 SMS Send and Receive
- آز½ SMS to Email
- ï¿1/2 Email to SMS
- ï¿1/2 Auto SMS/Call Generation
- ï¿1/2 Call Waiting/Call Back
- تز½ Call Forward
- ï¿1/2 Call Conference
- آذ½ GSM Audio Coding: HR, FR,EFR, AMR\_FR,AMR\_HR



# Dinstar UC2000-VF-8T GSM/LTE VoIP Gateway

#### Maintenance

- � Web/Telnet Configuration
- � Configure Backup/Restore
- � Firmware Upgrade by HTTP
- ï¿⅓ Factory Reset
- ï¿1/2 CDR (10000 CDRs Storage Locally)
- ï¿⅓ Syslog/Filelog
- � Ping and Tracert
- ï¿⅓ Traffic statistics: TCP,UDP,RTP
- آزٰء VoIP Call Statistics
- ï¿1/2 PSTN Call statistics: ASR,ACD,PDD
- � Voice Diagnose with Loopback
- ï¿⅓ IVR Customisation
- � SIP/RTP/PCM Capture
- ï¿1/2 SIMCloud Management
- � Centralised Management(DMS)

### **Physical Features**

- ï¿1/2 Power Supply: 100-240V,50-60Hz@DC12V4A
- � Power Consumption: 38w
- ገሪ½ Temperature:- Operation: 0 ℃ ~ 40 ℃- Storage: -20 ℃ ~80 ℃
- � Operation Humidity: 10%-90% � Dimension(W/D/H): 440x270x44mm
- ï¿⅓ Unit Weight: 3.7kg

Price: £813.00