

Product Name: OpenVox IX160 Series IP PBX

00:8: Quite...

Manufacturer: OpenVox Model Number: IX160

OpenVox IX160 Series IP PBX

The OpenVox IX160 is a standard 19" 1U high-performance PBX solutions. Designed and rigorously tested for optimal performance, this appliance allows users to integrate up to 2 pieces of OpenVox PCI-E telephony interface cards, with any combinations of FXS/FXO, BRI, E1/T1/J1 or transcoding interfaces. The IX160 adds support for motherboards to provide more powerful performance and can handle up to 600 concurrent calls and hundreds of user extensions. In addition, IX160 can integrate a variety of high-definition audio/video codecs, bringing users a high-fidelity, high-definition audio/video call experience.

OpenVox IX160 Key Features

� A standard 19" 1U IP PBX

i¿½ 1.83GHz Intel® Celeron® N2930

� Up to 600 concurrent calls

� Optional Pre-loaded Free Open Source IPPBX System

آزا Combination of FXS/FXO, BRI, E1/T1/J1 Interface

ï¿1/2 PRI/SS7/R2 to SIP Gateway

i¿½ PRI/SS7/R2/BRI/FXS/FXO Signaling Converter

� PRI/SS7/R2 TDMoE Gateway

ī స్ట్రీ Flexible Applications Selection (IPPBX or Firewall)

17.1/2 Zero Touch IP Phones Auto-Provisioning

� User Control Panel

The IX160 supports comprehensive protocol conversion, including SIP, IAX2 protocols in IP side and BRI, PRI, SS7, R2 in CPE side. Taking the full advantages of open source platform, the IX160 will be preloaded with OpenVox UC system, Issabel, FreePBX, VitalPBX, PBX in a Flash, Elastix® IPPBX software. The default pre-installed OpenVox UC system makes the deployment, configuration, and use of a PBX system ever easier. Getting started is a breeze with a user-friendly GUI. Powerful IX devices allow enterprises to grow while minimizing communication costs.

OpenVox IX160 is a risk-free solution with built-in Redundant Power Supply (RPS) and Uninterruptible Power Supply (UPS) that keeps your system and data away from damage or lost caused by unexpected power failure. The optional hardware RAID 1 support provides better data backup for your system. When RAID1 is installed, thus users can see the status of the storage devices and be alerted when hard drive(HDD/SSD) is crashed, then simply replace a backup hard drive ASAP.

OpenVox IX160 Technical Specifications General

� Max Analog Ports: 48 � Max BRI Ports: 8

� Max E1/T1/J1 Ports: 4 � Recommended User Capacity: 200 Users

าั¿½ Max Concurrent Calls*:- 600 Concurrent Calls with G.711 Codec- 200 Concurrent Calls with

ï¿1/2 Recommended Call Capacity: 120 Calls

� Protocol: SIP (RFC3261), IAX2

12.1/2 Transport Protocol: UDP, TCP, TLS, SRTP

ī¿½ Codec: G711 (alaw/ulaw), G722, G723.1 G726, G729, GSM, ADPCM, iLBC, H263, H263P,

H264

G.729 Codec

า๊¿½ DTMF: In-band, RFC2833, SIP INFO



آذًا IP Services: Static IP, DHCP, VPN, Firewall, PPPoE, Bridge

� Firewall: Yes � T.38 Fax: Yes

� CPU: 1.83GHz Intel® Celeron® N2930

ϊ¿½ RAM: Up to 8GB DDR3L 1333

าั¿1/2 Storage: MSATA SSD and 2.5 inch SATA HDD

� RAID: Yes (Optional)

آز½ Mini PCI-E: 2

� NIC: 2* 10/100/1000M � UPS: Yes (Optional)

� Power Supply: 100-240V AC

ï¿1/2 Redundant Power Supply: Yes (Optional)

� Display: HDMI � LCD Display: No � USB: 2 USB2.0

� Power Consumption: 20W

าั¿½ Operating Temperature: 0°C to 50 °C าั¿½ Storage Temperature: -40 °C ~ 125 °C

� Humidity: 10 ~ 90% NON-CONDENSING

� Dimension: 440*370*66.7mm

� Net Weight: 4.13kg � Warranty: 2 Years

Combination Options

Users can choose two module accessories to customise

ï¿1/2 A400E/A(E)810E/A(E)1610E/A(E)2410E

� B(E)200E/B(E)400E

ї¿½ D(E)130E/D(E)230E/D(E)430E/D(E)830E/D(E) 1630E

Except A400E, all compatible cards can be applied together with EC module.IX160/160P supports combination of two cards for example:

ï¿1/2 A(E)1610E + B(E)400E

ϊ¿½ D(E)430E + B(E)400E

� D(E)430E+A(E)2410E

� D(E)430E + A(E)1610E

ï¿1/2 A(E)810E + A(E)810E

Features

� G.711(a-law &μ-law), G.722, OPUS, AMR-NB/WB, SILK, G723.1, G726, G729, GSM, ADPCM, iLBC, H263, H263P, H264, VP8, etc.

� Support SIP & SIP & IAX2

� Echo canceller

า๊¿½ Simple and Convenient Configuration via Web GUI

آزِيً User Portal

12.1/2 Extension User Privileges

ï¿1/2 System Administrators Monitor

آذِ Event Notification

� Support Backup/Restore

� Remote Management

^{*}Maximum number of calls tested under laboratory conditions



- ï¿1/2 Hot Standby
- � System resource monitoring
- � Network configuration
- ï¿⅓ Support VLAN
- ï¿1/₂ Support Static Route
- � DHCP server for dynamic IP
- ï¿⅓ Support Fail2ban
- ī¿1/2 Secure communications (SRTP & Dryption)
- īస్ట్ Support Multiple VPN protocols including OpenVPN, L2TP, N2N, SSTP
- � Import/Export Extensions
- ï¿1/2 Support SIP Forking
- ï¿1/2 Call Transfer/Forwarding/Waiting
- า๊¿½ Follow-Me (Find me calling)/Ring Group/Queue
- � Quickly Auto Provision IP Phones
- ï¿⅓ Support IMS VoLTE
- ï¿1/2 Flexible Inbound/Outbound Route
- � Call Blacklisting
- � Support international call restrictions
- ï¿⅓ AutoCLIP
- ï¿⅓ Time Condition
- PIN List يُرْخ
- � Automated Attendant (IVR)
- ï¿⅓ Phonebook
- ï¿1/2 LDAP Service
- � DISA (Direct Inward System Access)
- ï¿⅓ Conference bridge/service
- � Call Back
- � Call Parking
- � Paging and Intercom
- ï¿⅓ Speed Dials
- ï¿⅓ Call Recording
- � Customizable announcements
- ï¿⅓ Music On Hold
- آذِ Support Open API Protocol (based on Asterisk)
- � Click2call
- � WebPhone
- ï¿1/2 Access Control Interface based on ACL
- Al TTS ½ کا
- ï¿1/2 Support for video calls and presence
- ï¿1/2 SIP Instant Messaging
- آز½ Voicemail
- ï¿⅓ Missed Calls Notification
- � Remote SMTP Email Server
- آز½ Antispam support
- ï¿⅓ Support Mail Relay
- آزِ½ Fax to Email
- � Hotel & Service Wakeup Service
- � Call Detail Records (CDR)
- ï¿⅓ Billing Report

Price: 866.19EUR

