

Ubiquiti UniFi Access Door Entry Starter Kit (UA-SK-Kit)



Product Name: Ubiquiti UniFi Access Door Entry Starter Kit (UA-SK-Kit)

Manufacturer: -

Model Number: UA-SK-Kit

Please Note: This Ubiquiti product is no longer available from VoiPon. For our full range of Ubiquiti products, please see the website 4Gon.co.uk.

Please Note: Ubiquiti UniFi Dream Machine Pro is included as part of this kit.

Ubiquiti UniFi Access Door Entry Starter Kit (UA-SK-Kit)

The Ubiquiti UniFi Access Starter Kit contains everything you need to set up the next generation, state-of-the-art access control system for your business.

Ubiquiti UniFi Starter Kit Key Features

- 1x UniFi Access Hub
- 1x UniFi Access Reader Pro
- 1x UniFi Access Reader Lite
- 1x UniFi Access Card (20 count)
- 1x UniFi Dream Machine Pro

Compatible with most Electric Bolts/Strikes and Magnetic Locks, the UniFi Access Starter Kit is easily installed with minimal effort and offers the convenience of the UniFi Access Controller, which allows you to easily manage users, visitors, schedules, and access policies. The UniFi Access Starter kit is powered by native PoE technology, PoE switch is not included.

Ubiquiti UniFi Starter Kit Technical Specifications

UniFi Access Hub

- Dimensions: 190 x 126 x 33 mm (7.48 x 4.96 x 1.29")
- Weight: 457 g (16.12 oz)
- Enclosure Characteristics: Plastic Enclosure with Metal Mount Plate
- Mounting Options: DIN Rail
- Networking Interface: (4) 1 Gbps Ethernet
- Max. Power Consumption: 40W
- Power Method: 802.3bt PoE
- Input Relays- REX - Request to Exit- REN - Request to Enter- REL - Remote Release- DPS - Door Position Sensor
- Dry Output Relay:- Lock: Rated 30VDC, up to 1A- Aux: Rated 30VDC, up to 1A
- Powered Output Relay:- Lock: 12VDC, up to 1A- Aux: 12VDC, up to 0.33- Line: A12VDC, up to 0.33A
- LEDs:- (1) System, (3) PoE Out, (4) Input- (2) Output Relays, (1) 12VDC Out
- Buttons: Terminal Blocks, Reset
- Operating Temperature: 0 to 40°C; C (32 to 104°F)
- Operating Humidity: 5 - 90% Noncondensing
- Certifications: CE, FCC, I

UniFi Access Reader Pro

UA-PRO

- Dimensions 73.40 x 62.28 x 26.55 mm (2.89 x 2.45 x 1.05")
- Networking Interface 85 g (2.99 oz)

Ubiquiti UniFi Access Door Entry Starter Kit (UA-SK-Kit)

- Mounting Options Wall-Mount or Alloy Clamp Holder
 - Networking Interface 10/100 Mbps Ethernet
 - Camera Viewing Angle 147.5° ± 3°
 - Max. Power Consumption 8.3W
 - Power Method 802.3af PoE
 - Button (1) Reset
 - IP Rating IP54
 - LEDs Blue, White
 - Connectivity Ethernet, BLE 4.2
 - Operating Temperature -10 to 40°C (14 to 104°F)
 - Operating Humidity 5 to 90% Noncondensing
 - Certifications CE, FCC, IC
-
- 1x UniFi Access Reader Pro
 - 1x UniFi Access Reader Lite
 - 1x UniFi Access Card (20 count)

NFC

- Frequency 13.56 MHz
- Read Range <30 mm
- Standards ISO 14443A, 14443B, 15693
- Technology - NFC Tag 1, 2, 3, 4, 5- MIFARE Classic- MIFARE Plus- MIFARE Ultralight- MIFARE DESFire EV1/EV2

UniFi Access Reader Lite UA-Lite

- Dimensions: 94.91 x 40.00 x 31.10 mm (3.74 x 1.57 x 1.22")
- Weight: 65 g (2.29 oz)
- Mounting Options: Wall-Mount
- Networking Interface: 10/100 Mbps Ethernet
- Max. Power Consumption: 6W
- Power Method: 802.3af PoE
- IP Rating: IP54
- Button: (1) Reset
- LEDs: White/Blue
- Connectivity: Ethernet, BLE 4.1
- Operating Temperature: -40 to 40°C (-40 to 104°F)
- Operating Humidity: 5 to 90% Noncondensing
- Certifications: CE, FCC, IC

NFC

- Frequency: 13.56 MHz
- Read Range: <30mm
- Standards: ISO 14443A, 14443B, 15693
- Technology:- NFC Tag 1, 2, 3, 4, 5- MIFARE Classic- MIFARE Plus- MIFARE Ultralight- MIFARE DESFire EV1/EV2

Ubiquiti UniFi Access Door Entry Starter Kit (UA-SK-Kit)

UniFi Access Card UA-Card UA-Card

Dimensions: 85.6 x 53.98 x 0.84 mm (3.37 x 2.13 x 0.033")
Weight: 5 g (0.18 oz)
Format: ISO 7810 ID-1

NFC

Frequency: 13.56 MHz
Technology:- ISO/IEC 14443 Type A - MIFARE DESFire EV2 - UniFi Access Proprietary Security Protocol

UniFi Dream Machine Pro UDM-Pro

Dimensions: 442.4 x 43.7 x 285.6 mm (17.42 x 1.72 x 11.24")
Weight: 3.90 kg (8.60 lb)
Weight with Brackets: 3.99 kg (8.80 lb)
Interfaces:- Networking: (8) 10/100/1000 RJ45 LAN Ports, (1) 10/100/1000 RJ45 WAN Port, (1) 1/10G SFP+ LAN Port, (1) 1/10G SFP+ WAN Port- Management: Ethernet In-Band, (1) Bluetooth BLE
IDS/IPS Throughput: 3.5 Gbps*
Processor: Quad ARM Cortex-A57 Core at 1.7 GHz
System Memory: 4 GB DDR4
On-Board Flash Storage: 16 GB eMMC
Maximum Power Consumption: 33W
Voltage Range: 100 to 240VAC
Power Method:- (1) Universal AC Input, 100-240VAC, 50/60 Hz- (1) RPS DC Input
Power Supply: Internal 50W/12V
LEDs:- HDD: Activity- RJ45: Link/Speed/Activity- SFP+: Link/Speed/Activity
ESD/EMP Protection: Air: ±16 kV, Contact: ±12 kV
Operating Temperature: -10 to 40°C (14 to 104°F)
Operating Humidity: 5 to 95% Noncondensing
Certifications: CE, FCC, IC

Please Enquire