

## Ubiquiti UniFi Access Hub (UA-Hub)



Product Name: Ubiquiti UniFi Access Hub (UA-Hub)

Manufacturer: -

Model Number: UA-Hub

Please Note: This Ubiquiti product is no longer available from Voipon. For our full range of Ubiquiti products, please see the website [4Gon.co.uk](http://4Gon.co.uk).

### Ubiquiti UniFi Access Hub (UA-Hub)

The Ubiquiti UA-Hub is an intelligent IP networked single door controller, a part of UniFi Access solution. The UniFi Access Hub comes with versatile interfaces, including support for most electric bolts/strikes, magnetic locks, and 12V access accessories such as motion sensors, push buttons, and alarms. The three Ethernet PoE powered reader interfaces minimize need for wiring work and offer a convenient way to add a UniFi G3-Flex surveillance camera for additional security. The seamlessly integrated UniFi Access solution is managed with UniFi Access Controller software. Easily manage users, visitors, schedules, and access policies with the intuitive browser-based interface.

### Ubiquiti UA-Hub Key Features

- Powered by 802.3bt (PoE++) switch
- Three 802.3af PoE ports for UniFi readers and G3 Flex surveillance camera
- 12V powered and dry relays compatible with most locks
- Four inputs for motion sensors, request-to-exit devices and door position switch
- Managed with UniFi Access Controller in UDM-Pro
- DIN-rail mounting

### Ubiquiti UA-Hub - Technical Specifications

#### General

- Dimensions: 190 x 126 x 33 mm (7.48 x 4.96 x 1.29")
- Weight: 457 g (16.12 oz)
- Enclosure Characteristics: Plastic Enclosure with Metal Mount Plate
- Mounting Options: DIN Rail
- Networking Interface: (4) 1 Gbps Ethernet
- Max. Power Consumption: 40W
- Power Method: 802.3bt PoE
- Input Relays:- REX - Request to Exit- REN - Request to Enter- REL - Remote Release- DPS - Door Position Sensor
- Dry Output Relay:- Lock: Rated 30VDC, up to 1A- Aux: Rated 30VDC, up to 1A
- Powered Output Relay:- Lock: 12VDC, up to 1A- Aux: 12VDC, up to 0.33A- Line: A12VDC, up to 0.33A
- LEDs:- (1) System, (3) PoE Out, (4) Input- (2) Output Relays, (1) 12VDC Out
- Buttons: Terminal Blocks, Reset
- Operating Temperature: 0 to 40°C (32 to 104°F)
- Operating Humidity: 5 - 90% Noncondensing
- Certifications: CE, FCC, IC

## Ubiquiti UniFi Access Hub (UA-Hub)

**Please Enquire**

---