

Ubiquiti UniFi Protect G4 Doorbell (UVC-G4-DoorBell)



Product Name: Ubiquiti UniFi Protect G4 Doorbell (UVC-G4-DoorBell)

Manufacturer: -

Model Number: UVC-G4-DoorBell

Please Note: This Ubiquiti product is no longer available from VoIPon. For our full range of Ubiquiti products, please see the website 4Gon.co.uk.

Ubiquiti UniFi Protect G4 Doorbell (UVC-G4-DoorBell)

The Ubiquiti UniFi Protect G4 Doorbell is a WiFi video doorbell with a built-in display and real-time two-way audio communication. The camera features a high-quality 5MP sensor with enhanced night vision. Image streams can be viewed in up to 1600x1200 (2MP) HD at 30 FPS. UniFi Protect G4 Doorbell includes a PIR sensor for instant motion detection alerts. Integration with UniFi Protect provides an easy-to-use interface.

Ubiquiti UniFi Protect G4 Doorbell Key Features

- 1600x1200 (2MP) HD stream with night vision
- Integrated entrance lighting
- Real-time two-way audio with echo cancellation
- Built-in display
- Dual-band 802.11ac WiFi
- PIR motion detection sensor
- Weather-resistant
- UniFi Protect integration

Ubiquiti UniFi Protect G4 Doorbell Technical Specifications

Mechanical

- Dimensions: 118.3 x 46.8 x 25.8 mm (4.66 x 1.84 x 1.02")
- Weight: - Without Mount: 130 g (4.59 oz)- With Flat Wall Mount: 178 g (6.28 oz)- With 20° Wedge Mount: 200 g (7.05 oz)
- Enclosure Material: Polycarbonate
- Mount Materials: - Flat Wall Mount: Aluminum Alloy- 20° Wedge Mount: Polycarbonate
- Weatherproofing: IPX4

Optics

- Sensor: 5 MP CMOS Sensor
- Lens: Fixed Focal Length
- View Angle: H: 138°, V: 114°, D: 155°
- Night Mode: Built-in IR LED Illumination and IR Cut Filter

Video

- Video Compression: H.264
- Resolution: 1600 x 1200 (4:3)
- Maximum Frame Rate: 30 FPS

System

- Processor Specs: Ambarella Advanced Image Processing SoC
- Memory Information: 512 MB
- Management Interface: UniFi Protect
- Networking Interface: 802.11 ac WiFi

Ubiquiti UniFi Protect G4 Doorbell (UVC-G4-DoorBell)

• Flash Memory Support: 256 MB
• Max. Power Consumption: 12VA
• Power Requirements: 16-24VAC, 20VA
• Link/Activity LED: Yes
• Button: Factory Reset
• Mounting: Flat Wall/20°; Wedge (Kits Included)
• Operating Temperature: -10 to 40°C (14 to 104°F)
• Operating Humidity: 0 to 90% Noncondensing
• Certifications: FCC, IC, CE

Audio

• Microphone: Yes (Can be Disabled in Software)
• Speaker: Yes

Software

• Controller Software: UniFi Protect
• Mobile Apps: UniFi Protect iOS and Android

Please Enquire
