

## 2N Access Unit 2.0 Touch Keypad (916032)



Product Name: 2N Access Unit 2.0 Touch Keypad (916032)

Manufacturer: 2N Telecommunications

Model Number: 916032

2N Access Unit 2.0 Touch Keypad (916032)

The 2N Access Unit 2.0 Touch Keypad is equipped with a capacitive touch keypad which reliably registers and evaluates each touch. After entering the correct access PIN, the unit opens the door. Each user can have their own access code, or several users can share one PIN. The unit is designed for indoor or outdoor installation.

2N Access Unit 2.0 Touch Keypad Key Features

Capacitive touch technology
Adjustable backlighting brightness
Silent alarm activation
Regular automatic calibration
Remote configuration
Tamper protection
Security Relay
Simple Installation

Web interface administration and remote control

2N Access Unit 2.0 Touch Keypad Technical Specifications Interface

ï¿1/2 Power supply: PoE and/or 12V/1A DC

� PoE: 802.3af (Classe 0-12.95W)

Ti.1/2 LAN: 10/100BASE-TX with Auto-MDIX, connecting block or RJ-45 pigtail

ï¿1/2 Recommended cabling: Cat-5e or higher

آذِرُ Supported protocols: DHCP opt. 66, SMTP, 802.1x, TFTP, HTTPS, Syslog

آذِ Passive switch: NO/NC contact, up to 30 V / 1 A AC/DC

 $i \gtrsim 1/2$  Active switch output: 8 to 12 V DC according to power supply (PoE: 10 V; adapter: source voltage minus 2 V), up to 550 mA

آذِ 1⁄2 Tamper switch is part of the 2N Access Unit

� Inputs: Passive / active mode (-30 V to +30 V DC)

## Touch Keypad

تز1/2 Technology: Capacitive touch technology

าั¿½ Reliability: Regular automatic calibration (SmartSence) Does not detect false touches on wet surface

ī¿½ Signalling:- Configurable backlighting intensity- Indication using multicoloured LEDs- Acoustic response for every keypad touch

## Mechanical properties

าั¿½ Cover: Robust zinc cast with surface finish (nickel and black colour)

i¿½ Operating temperature: -40°C to 60°C

า๊¿½ Storage temperature: -40°C to 70°C

i¿½ Operating relative humidity: 10%-95% (non-condensing)

ī¿½ Dimensions:- Wall (surface) mounting frame 1 module: 107 (W) x 130 (H) x 28 (D) mm- Flush mounting frame 1 module: 130 (W) x 153 (H) x 5 (D) mm- Flush mounting box (minimum hole dimensions) 1 module: 108 (W) x 131 (H) x 45 (D) mm

� Weight max 0.8kg

� Cover rating IP54 and IK08



## 2N Access Unit 2.0 Touch Keypad (916032)

Price: \$476.39