

## PORTech MT-358 - 8 channel FXO/FXS/GSM Fixed Wireless Terminal



Product Name: PORTech MT-358 - 8 channel FXO/FXS/GSM Fixed Wireless Terminal

Manufacturer: -

Model Number: MT-358

Please Note: This product has been discontinued. Please see the VoIP GSM Gateways for an available alternative.

### PORTech MT-358 FWT with FXS/FXO/GSM Interfaces

Please Note: This product may have a lead time of up to 1-2 weeks. Please call 0330 088 0195 and speak to our sales team who can confirm the current available stock for your requirement

The PORTech MT-358 is a Fixed Wireless Terminal that supports FXS, FXO and GSM interfaces and can connect to a VoIP system, PSTN or VoIP gateway. The MT-358 supports 8 GSM concurrent channels, up to 8 calls can be live when 8 SIM cards are inserted.

### Features

- 1/2 Auto-select most economic route - The MT-358 automatically routes calls out over GSM or PSTN, depending on the destination.
- 1/2 8 Channel - Up to 8 SIM cards allow for eight GSM channels to be active at a time.
- 1/2 Polarity Reversing function
- 1/2 Set GSM dial-out code amount
- 1/2 Limit of communicating time
- 1/2 GSM simulated echo-bell function
- 1/2 Follow Me - PSTN to GSM and GSM to PSTN

The PORTech MT-358 can connect to your analogue phone line and divert calls to your mobile via its SIM card. Call forwarding rates to mobiles via the PSTN are typically expensive, therefore - when out of the office - calls to the office analogue line would be missed or forwarded to your mobile at considerable cost.

The MT-358 FWT can transfer all incoming calls using its FXO port to GSM and connect calls directly to your mobile using more cost-effective mobile-to-mobile tariffs.

Many mobile operators offer great value deals on same network calls. Thus, if a SIM of the same network as your mobile is used, these inclusive minutes or low call rates can be used when routing calls to your mobile.

The MT-358 also works in reverse - routing incoming GSM calls to a PSTN number using the analogue line.

When a telephone is connected via FXS, calls can also be routed by either GSM or PSTN. The MT-358 can automatically check if the dialed number is on the network and if so, then the call will go out over the lower cost GSM rate; if not the call will go out over PSTN.

### Specification

- 1/2 Phone impedance : Below DC 1kΩ; AC 600Ω; (not include line)
- 1/2 Phone Ring Output Voltage : 45v rms
- 1/2 Phone Signal (DTMF) Standard : -3dbm 24dbm
- 1/2 Phone Signal (DTMF) Time: 50 100ms
- 1/2 DTMF Frequency Rate Error: ±1%
- 1/2 Feeder Voltage: 48v
- 1/2 AC Adapter: Input 110V AC, Output 12V DC 1A

### GSM Specification

## PORTech MT-358 - 8 channel FXO/FXS/GSM Fixed Wireless Terminal

• GSM Frequency bands : Dual Band EGSM 900 and GSM 1800(GSM Phase 2+)  
• GSM class : Small MS  
• Transmit power :  
• Class 4(2W) for EGSM 900  
• Class 1(1W) for GSM 1800  
• SIM card reader : External &ndash; connected via interface connector  
• Antenna : 50 Ohm antenna coaxial connector  
• Temperature range :  
• Normal operation : -20°C to +55°C;  
• Restricted operation : -25°C to -20°C; and +55°C to 70°C;  
• Storage : -40°C to +85°C;

**Please Enquire**

---