



Product Name: Draytek Vigor 2765ac VDSL and Ethernet Router with Wi-Fi 5 AC1300 Wireless

Manufacturer: -

Model Number: V2765AC-K

Please Note: This product has been discontinued. For an alternative, please see the DrayTek V2763AC-K.

Draytek Vigor 2765ac VDSL and Ethernet Router with Wi-Fi 5 AC1300 Wireless
The Draytek Vigor V2765AC-K is a VDSL and Ethernet VPN router that's ideal for small office and home office networks. It features powerful Firewall andContent Filtering, configurable Quality of Service and an array of VPN capabilities, with the performance to make full use of FTTP Fibre Broadband. Incorporating Wireless and VoIP features in '2765ac' and '2765Vac' models, the Vigor 2765 series provide a reliable, highly integrated and reliablenetwork solution for SoHo environments.

Draytek Vigor V2765AC-K Key Features

រ៉េះ/៉ូ VDSL2 (Superfast Fibre) or Gigabit Ethernet WAN Router with Failover

ii/2 Up to 950Mbps Firewall Throughput for Ethernet WAN

� 4 Gigabit LAN Ports

Ti. 1/2 AC1300 - 11ac ' Wave 2' Dual Band Wireless (' ac' models)

i¿½ 2 LAN Subnets with VLANs (Port-based / 802.1q)

12.1/2 SPI Firewall and Content Filtering

� Up to 200Mbps IPsec VPN Throughput

� 2 Dial-Out LAN-to-LAN or Remote Teleworker VPN Tunnels

� DrayTek SSL VPN and OpenVPN support

� Optional VigorCare Available

ī¿½ Compatible with VigorACS central management platform

VDSL and Ethernet Router Connect the Vigor 2765 to Superfast Fibre with its integrated VDSL modem. Or connect to VirginMedia Cable and Ultrafast FTTP with Ethernet WAN.Benefits: Suitable for all Broadband services. DrayTek Firewall, Content Filtering and Quality of Service.Powerful SoHo VPN Router Connect remote locations with 2 VPN tunnels for Remote Dial-In User Teleworker and Dial-Out LAN to LAN VPN. Up to 200Mbps IPsec performance, with SSL and OpenVPN support. Benefits: Securely access resources remotely. Connect to VPN services for secure browsingAC1300 Wireless with Mesh Connect DrayTek VigorAP Access Points to the router in a wireless Mesh. DrayTek's Self-Optimising Mesh ensures access points are always connecting through best path to your Router. Benefits: Easily expand wireless coverage. Reduces the need for cable installation.4 Gigabit LAN Ports with VLANsAttach Computers, Servers and Network Attached Storage. Use VLANs to provide a fully separated Guest network, with up to 2 LAN subnets.Benefits: Improve quality of service for private and guest data traffic

Draytek Vigor V2765AC-K - Technical Specifications Physical Interfaces

آزا WAN1: VDSL2 / VDSL2 35b / ADSL2+, RJ-11

าั¿½ WAN2/LAN Switchable Port: 1x Gigabit Ethernet (1G/100M/10M), RJ-45

าั¿½ WAN3: USB 2.0 Port for 3G/4G Modem (not included)

าั¿½ LAN Ports: 4x Gigabit Ethernet (1G/100M/10M), RJ-45 (3x with WAN2 enabled)

تزير 2x PSTN RJ-11 Telephone Ports (' Vac' model)

� 2x USB 2.0 Port for USB storage, thermometer or Printer

i¿½ 2x Removable Wireless antennas (wireless models)



� Wireless On / Off / WPS button � Recessed Factory Reset button

#### Performance

ī¿½ Router Performance: - 100 Mb/s Max Sync Rate with VDSL2 - 300 Mb/s Max Sync Rate with VDSL2 35b - 950 Mb/s NAT Throughput for Ethernet WAN with Hardware Acceleration - 700 Mb/s NAT Throughput per WAN without Hardware Acceleration - 50,000 NAT Sessions ī¿½ VPN Performance: - 200 Mb/s IPsec (AES256) VPN Throughput - 80 Mb/s SSL VPN Throughput - Max. 2 Concurrent VPN Tunnels

#### Internet Connection

ï¿1/2 Hardware Acceleration

ï¿1/2 Failover / Backup WAN

ï¿1/2 802.1p/q Multi-VLAN Tagging

� Multi-VLAN/PVC

រី¿½ WAN Active on Demand: Link Failure, Traffi c Threshold

12.1/2 Connection Detection: PPP, ARP Detect, Ping Detect

� WAN Data Budget

� Dynamic DNS

آذِرُ DrayDDNS – with automated LetsEncrypt Certifi cates – New!

T¿½ Full Feature-set Hardware Acceleration (requires f/w 4.3.0): - Hardware Accelerated Quality of Service - Multi-WAN Data Budget - Traffi c Graph & Data Flow Monitor - Bandwidth Limit

าั¿½ IPv4 Connection Types: PPPoE, DHCP, Static IP, PPTP/L2TP

T¿½ IPv6 Connection Types: - DSL & Ethernet: PPP, DHCPv6, Static IPv6, TSPC, AICCU, 6rd, 6in4 Static Tunnel - USB 4G/LTE Modem: TSPC, AICCU

### VDSL and ADSL Features

ï¿1/2 BT Infi nity Option 1 & Dption 2 Compatible

ï¿1/2 Compliant with Openreach SIN 498

ï¿1/2 Auto Detection of VDSL and ADSL line modes

� Support for G.INP & amp; Vectoring

� VDSL Standards: - ITU-T G.993.1 VDSL- ITU-T G.993.2, G.997.1 VDSL2 - Band Plan: G.998, G.997 - Annex A, Annex B, Annex C - VDSL2 Profi le: 8a, 8b, 8c, 8d, 12a, 12b, 17a, 35b - OLR, UPBO, DPBO Supported - USO Supported - Loop Diagnostic Mode - DSL Forum WT-114 � ADSL Standards: - ANSI T1.413 Issue2 - ITU-T G.992.1 G.dmt (ADSL) - ITU-T G.992.2 G.lite - ITU-T G.992.3 ADSL2 - ITU-T G.992.5 ADSL2+

าั¿½ ATM Protocols: - RFC-2684/RFC-1483 Multiple Protocol over AAL5 - RFC-2516 PPP over Ethernet - RFC-2364 PPP over AAL5 - Support for RFC4638 for MTU up to 1500

### Firewall and Content Filtering

� IP-based or User-based Firewall Policy

ï¿1/2 User-based Time Quota

ï¿.½ DoS Attack Defence

ï¿⅓ Spoofing Defence

ī సై Content Filtering: - Application Content Filter - URL Content Filter- DNS Keyword Filter - Web



#### Features - Web Category Filter (requires GlobalView subscription)

#### NAT features

� NAT Port Redirection

ï¿1/2 Open Ports

ï¿1/2 Port Triggering

ï¿⅓ DMZ Host

UPnP ½ ′′5ï

تزير ALG (Application Layer Gateway): SIP (configurable), RTSP (configurable), FTP, H.323

تزر VPN Pass-Through: PPTP, L2TP, IPsec

#### LAN Management

تز 1/2 802.1q Tag-based, Port-based VLAN

� Up to 2 LAN Subnets

آز½ Up to 8 VLANs

آذًا DHCP Server: - Multiple IP Subnet - Custom DHCP Options - Bind-IP-to-MAC - DHCP Pool

Count up to 253 addresses per subnet - Wired 802.1x Port Authentication

آز½ Port Mirroring

ï¿1/2 Local DNS Server

� Conditional DNS Forwarding

## **Networking Features**

� Policy-based Routing: Protocol, IP Address, Port, Domain/Hostname, Country - New!

� DNS Security (DNSSEC)

ï¿1/2 Local RADIUS server

าั¿½ SMB File Sharing (Requires external USB storage)

آزا Multicast: IGMP Proxy, IGMP Snooping & East Leave, Bonjour

ī¿1/2 Compatible with IPTV and ISP Video on Demand services (YouView,Sky Q)

ī¿½ Routing Features: IPv4 & IPv6 Static Routing, Inter-VLAN Routing

## **VPN** Features

� 2 Concurrent active VPN Tunnels

ï¿1/2 LAN-to-LAN - Dial-Out VPN Client

าั¿½ Teleworker-to-LAN – Dial-In VPN Server

ï¿1/2 User Authentication: Local, mOTP

آذًا IKE Authentication: Pre-Shared Key and Digital Signature (X.509)

� Encryption: MPPE, DES, 3DES, AES (128/192/256)

ï¿1/2 Authentication: SHA-256, SHA-1

� Dead Peer Detection (DPD)

� IPsec NAT-Traversal (NAT-T)

าั¿½ Virtual IP Mapping – Resolve VPN IP subnet/range conflicts

� DHCP over IPsec

าั¿½ DrayTek VPN Matcher – Connect to a VPN router that's behind NAT/ CG-NAT

� VPN Protocols: - IPsec IKEv1, IKEv2, IKEv2 EAP - IPsec-XAuth - DrayTek SSL VPN - OpenVPN - PPTP for legacy applications - L2TP, L2TP over IPsec

#### **Bandwidth Management**



ï¿1/2 IP-based Bandwidth Limit

� IP-based Session Limit

ï¿1/2 User-based Data Quota

� QoS (Quality of Service):- Classify via TOS, DSCP, 802.1p, IP Address, Service Type- 4 Priority Queues- App QoS- VoIP Prioritization

### Management

آذِر Local Service: HTTP, HTTPS, Telnet, SSH, FTP, TR-069

� Config File Export & Import

าั¿1/2 Import Config from Vigor 2760 and Vigor 2762

آزار Auto Backup Config to USB Storage – New!

� Firmware Upgrade via TFTP, HTTP, TR-069

� 2-Level Administration Privilege

ī సై Access Control Features: Access List, Brute Force Protection

ï¿⅓ Syslog

ï¿⅓ SMS, E-mail Notification Alert

ï¿⅓ SNMP: v1, v2c, v3

ï¿1/2 Managed by VigorACS

ī¿½ Router Central Management Features:- AP Management: Up to 2 VigorAP access points-Switch Management: Up to 2 VigorSwitch network switches- DrayTek Mesh: Up to 7 VigorAP access points – New! (requiresf/w 4.3.0)

### Operating Requirements

ï¿1/2 Wall or Shelf Mountable

ï¿1/2 Temperature Operating: 0 °C ~ 45 °C

ï¿1/2 Storage: -25 °C ~ 70 °C

� Humidity 10% ~ 90% (non-condensing)

าั¿½ Power Consumption: 21.8 Watts maximum (Vac model)

าั¿½ Dimensions:- 207mm Width - 131mm Depth - 42mm Height

تز½ Operating Power: DC 12V (via external PSU, supplied)

ï¿1/2 Warranty: Two (2) Years RTB

� Power Requirements: 220-240VAC

#### **Box Contents**

ï¿1/2 Vigor 2765 router

� Quick Start Guide

تز1/2 Screws & amp; wall plugs for wall mounting

� 2m Cat-5e RJ-45 Network Cable



 $\ddot{i}_2$ 2x Detachable Wireless LAN Antennas ('ac' models)  $\ddot{i}_2$ 2 DC 12V Power Supply with UK Plug

Price: £211.70