



Product Name: Yealink W73P DECT Phone System

Manufacturer: Yealink Model Number: W73P

Yealink W73P DECT Phone System

The Yealink W73P, being a high-performance SIP cordless phone system, which can register 10 Yealink DECT W73H handsets, is the ideal solution for small and medium-sized businesses. It allows you to enjoy superb mobility and efficient flexibility immediately as well as significantly eliminates additional wiring troubles and charges. Featuring more functions, lines and mobility, it supports up to 10 SIP accounts and 20 simultaneous calls, improving signal strength and responsiveness to provide a stable and good experience for your mobile communications. Yealink W73P Key Features

17:1/2 High-performance SIP cordless phone system

ī¿½ 1.8" 128 x 160 TFT color screen with intuitive user interface

� Up to 20 simultaneous calls

� Up to 10 DECT cordless handsets

� Up to 10 SIP accounts

� Support Opus audio codec

ï¿1/2 Noise Reduction System

ï¿⅓ FNR (Flexible Noise Reduction)

آذِرُ Up to 35-hour talk time (in ideal conditions)

12/2 Up to 400-hour standby time (in ideal conditions)

12.1/2 Quick charging: 10-min charge time for 2-hour talk time

ï¿1/2 TLS and SRTP security encryption

� Headset connection via 3.5 mm jack

� Charger wall mountable

You can enjoy clearer, high-quality voice calls because of the new Noise Cancellation technology. By supporting Opus codec, W73P consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions. It brings a seamless call management for our users while "on-the-go" with combining DECT technology with SIP capabilities. Enjoy the convenience of wireless communication anytime, anywhere, as well as the extensive benefits and feature richness of IP voice phones.

The Yealink DECT IP phone W73P supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings, which makes it simple to deploy, easy to maintain and upgrade, saving even more time and IT costs for businesses.

Yealink W73P Technical Specification Phone Features

ï¿⅓ Up to 20 simultaneous calls

� Up to 10 handsets

� Up to 10 SIP accounts

ï¿1/2 Up to 2 simultaneous calls per handset

� Up to 5 repeaters per base station (RT20U)

� Up to 6 repeaters per base station (RT30)

12.1/2 Handset selection for receiving call

า๊¿1/2 Handset and number selection for placing call

i¿1/2 Paging, intercom, auto answer, dial plan

ï¿1/2 Call hold, call transfer, 3-way conference

� Switching between calls

� Call waiting, mute, silence, DND



- ï¿1/2 Caller ID with name and number
- تز1/2 Anonymous call, Anonymous call rejection
- � Call forward (always/busy/no answer)
- ï¿1/2 Speed dial, voicemail, redial
- � Message Waiting Indication (MWI)
- � Music on hold (server-based)
- าั¿½ Local phonebook for up to 1000 entries(store in the base)
- آزٰ½ Remote phonebook/LDAP/XML phonebook
- � Phonebook search/import/export
- า๊¿½ 100 call history per handset: All/Placed/Missed/Received
- ï¿1/2 Direct IP call without SIP proxy
- � Reset to factory, reboot
- � Keypad lock, emergency call
- � Broadsoft directory, BroadSoft call log
- � Broadworks feature key synchronization
- ï¿1/2 Shared Call Appearance (SCA)
- ï¿⅓ XML browser

Personalization

- تزير 9 ringer melodies
- ï¿1/2 Screen saver
- � Multilingual user interface

Management

- า๊ะู่ 1/2 Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
- ïز½ Auto-provision with PnP
- � Handset upgrade: OTA (Over-The-Air)
- $\"{\it i}\ \ifmmode {\it i}\ \ifmmode {\it$
- � Trace package and system log export

Audio Features

- ï¿1/2 Full-duplex speakerphone
- � Hearing Aid Compatibility (HAC) compliant
- ï¿⅓ FNR (Noise Cancellation)
- � Receiver volume control: 5 steps
- � Ringer volume control: 5 steps+off
- � Multiple advisory tones
- ï¿1/2 Acoustic warning for low battery status
- آزٰ½ DTMF
- آذِ1/2 Wideband codec: Opus, AMR-WB (optional), G.722
- � Narrowband codec: PCMU, PCMA, G.726, G.729, G.729A, iLBC
- � VAD, CNG, AGC, PLC, AJB
- � AEC (supported by W73H)
- � Support VQ-RTCPXR (RFC6035), RTCP-XR

Network Features

- ï¿1/2 SIP v1 (RFC2543), v2 (RFC3261)
- ï¿⅓ SNTP/NTP
- � VLAN (802.1Q and 802.1P)
- ï¿1/2 802.1x, LLDP
- ï¿1/2 STUN Client (NAT Traversal)



- � UDP/TCP/TLS
- ï¿1/2 IP assignment: static/DHCP
- � Support outbound proxy server backup

Security

- ï¿⅓ Open VPN
- � Transport Layer Security (TLS)
- � HTTPS (server/client), SRTP (RFC3711)
- � Digest authentication
- � Secure configuration file via AES encryption
- ï¿1/2 Support SHA256/SHA512/SHA384
- าั¿½ Three-level configuration mode: Admin/Var/User

DECT

เว้ Frequency bands: 1880 – 1900 MHz (Europe), 1920 – 1930 MHz (US)

Interface

- ï¿1/2 1 x RJ45 10/100M Ethernet port
- ï¿1/2 Power over Ethernet (IEEE 802.3af), Class 1
- � Headset jack (3.5 mm)

Physical Features

- آذِ1/2 Indoor Range: 50m (in ideal conditions)
- ï¿1/2 Outdoor Range: 300m (in ideal conditions)
- i¿½ Standby Time: 400 hours (in ideal conditions)
- � Talk Time: 35 hours (in ideal conditions)
- ï¿1/2 1.8" 128 x 160-pixel TFT colour display
- � Desktop or wall mountable
- ï¿1/2 LCD backlight, key backlight
- � Energy-saving ECO mode/ECO Mode+
- ï¿1/2 Backlit keypad with 25 keys:
- ï¿⅓ Standard ITU telephone keypad, 12 keys, 4x3, with star and pound key
- � 5 navigation keys (left, right, up, down, OK)
- � 2 softkeys
- آذًا 6 function keys (Speaker, message, Off-hook, Cancel, TRAN, Mute)
- � 6 shortcut keys
- ï¿1/2 Three LED indicators on W70B:
- تزير 1 x Registration LED
- � 1 x Network Status LED
- ï¿1/2 1 x Power Indicator LED
- آذِرًا External Yealink AC adapter:AC 100-240V Input and DC 5V/0.6A Output
- า๊¿1/2 Colour: Handset: Space Grey; Base: Classic Grey
- ï¿1/2 Handset size: 144.5 mm x 48 mm x 21 mm
- i¿1/2 Base station size: 130mm x 100mm x 25.1mm
- � Operating humidity: 10~95%



 $i\frac{1}{2}$ Operating temperature: -10~+50°C (+14~122°F) $i\frac{1}{2}$ Storage temperature: -30 ~ 70°C (-22 ~ 158°F)

Package Features

� Package contents:

ï¿1/2 W73H Handset

ï¿1/2 W70B Base Station

ï¿1/2 Base Stand

� Charger Cradle

ï¿⅓ Two Power Adapters

ï¿1/2 Ethernet Cable

ï¿⅓ Belt Clip

� Rechargeable Battery

ï¿⅓ Quick Start Guide

� Qty/CNT: 10 PCS

፲¿½ Giftbox size: 502 mm × 362 mm × 215 mm ፲¿½ Carton meas: 205 mm × 176 mm × 95 mm

� N.W: 6.854 kg � G.W: 7.53 kg

Price: £70.10

Options available for Yealink W73P DECT Phone System:

DECT Repeater Required

Not Required, Yealink DECT Repeater RT30 (RT30-repeater) (+£79.10).

Need Product Setup / Training / Support?

Required - 30 minutes (+£40.00), Not Required, Required - 1 Hour (+£65.00).

Additional Handset

Not Required, Yealink W73H Additional Handset (+£49.50).