

Lifesize Icon 800 Video System (LS-ICON800)



Product Name: Lifesize Icon 800 Video System (LS-ICON800)

Manufacturer: Lifesize

Model Number: LS-ICON800

Lifesize Icon 800 Video System (LS-ICON800)

The Lifesize LS-ICON800 is designed to radically simplify video conferencing with its intuitive "heads up" UI, six-button remote and touchscreen Lifesize Phone HD. With the additional video inputs the Lifesize Icon 800 provides users incredible flexibility. Connect multiple video devices, such as PTZ cameras, laptops or DVRs, as well as audio devices, such as MP3 players, to the Lifesize Icon 800 and deliver an unprecedented immersive experience. And when paired to the Lifesize cloud-based service, there simply isn't a more powerful, yet easy-to-use video conferencing solution in the world.

Lifesize LS-ICON800 Key Features

- Four Full HD video inputs
- Two Full HD video outputs
- Seven audio inputs
- Four audio outputs
- Two USB 3.0 data inputs
- Secure connectors for server racks

Lifesize LS-ICON800 - Technical Specifications

System Components

- Lifesize Icon 800 video system, 2RU 48.3 cm (19") with rack mounts attached
- Lifesize Camera 10x
- Lifesize Phone HD or Phone 2nd Generation
- Lifesize link adapter
- Remote control
- Cables

Communications

- SIP, H.323, 128 Kbps - 6.0 Mbps
- 1 x RJ-45 Network LAN 10/100/1000
- 1 x Lifesize Link for Lifesize Phone HD or Phone 2nd Generation

Support for up to two displays

- Any 720p or 1080p HD displays
- Video Out 1 (primary) supports DVI-D/HDMI
- Video Out 2 (secondary) supports DVI-I/HDMI/ VGA

HD 1080P60 PTZ Camera 10X

- Wide-angle zoom lens with:- Diagonal field of view: 81 degrees- Horizontal field of view: 73 degrees - Vertical field of view: 44 degrees
- Up to 10x optical zoom
- Auto focus/automatic gain control
- 10 camera presets (near or far end)
- Standard 3.0 m HDMI cable

Video Specifications

Lifesize Icon 800 Video System (LS-ICON800)

- Maximum resolution 1920x1080, 16:9 aspect ratio
- All resolutions progressive scanning up to 60 frames per second
- Over 200 resolutions supported
- Example bitrates and resolutions (H.264 High Profile, AAC-LD):- 600 Kbps (720p30) - 820 Kbps (720p60) - 1.2 Mbps (1080p30)- 1.7 Mbps (1080p60)

Video Standards

- H.264 High Profile, H.264 Baseline Profile, H.263+, H.263

Video Inputs (4)

- 4x HD Video In (up to 1080p60) DVI/HDMI/VGA enabled

Video Outputs (2 Outputs)

- Video Out 1 (primary) supports DVI-D/HDMI
- Video Out 2 (secondary) supports DVI-I/HDMI/ VGA

Fully Integrated, HD Audio Conference Phone

- 90 Hz up to 22 kHz frequency support
- Audio pickup range up to 4.57 m (15'ࣘ)
- Powered by Lifesize Icon 800 directly through Lifesize Link Cable
- Touchscreen user interface
- Manage HD video, audio and presentation
- Additional support for up to two Lifesize Digital MicPods
- Included 9 m (30'ࣘ) Lifesize Link cable
- Optional 4 m (13'ࣘ) and 15 m (49'ࣘ) cables available

Lifesize Link Adapter

- Passive adapter converts Lifesize Link to Cat5e/ 6 cabling
- Supports cable distances: Shielded 24 AWG Cat5e: 46 m (150'ࣘ), Shielded 23 AWG Cat 6: 61 m (200'ࣘ)
- LEDs ensure proper installation
- Supports locking RJ45 connectors

Audio Features

- WebRTC NetEQ packet loss concealment
- Full duplex for natural conversations
- Echo cancellation for echo-free calls
- Automatic gain control
- Automatic noise reduction

Audio Standards

- G.711, G.722, G.722.1 and G.722.1C licensed from Polycom®, MPEG-4-AAC-LC, MPEG-4 AAC-LD, Opus

Audio Inputs (4 Inputs)

- 2 x Line In balanced (Phoenix)
- 1 x Lifesize Link (Lifesize Phone HD or Phone 2nd Generation, with optional Lifesize Digital

Lifesize Icon 800 Video System (LS-ICON800)

MicPods)

- 4 x HDMI via Video inputs

Audio Outputs (4 Outputs)

- 1 x Line Out balanced (Phoenix)

- 1 x Lifesize Link (Lifesize Phone HD or Phone 2nd Generation)

- 2 x HDMI via Video outputs

Other Supported Standards

- H.221, H.224, H.225, H.231, H.239/BFCP, H.241, H.242, H.245, H.281, RFC 3261, RFC 3264, RFC 2190, RFC 3407, RFC 2833

User Interface and Features

- Simplified user interface

- Heads-up remote control

- Video input selection

- Seamless call escalation to a group call

- Graphical user interface administration console

- Multiple languages supported

- Do Not Disturb mode

- Video mute

- Picture-in-picture

Lifesize Cloud-based Service

- Seamless call escalation for video and voice participants

- Calendar, meeting directory, favorites, unified searchable directory

- Automatic provisioning

- Guest calling

- Single button recording and sharing

- Mobile calling

- Video network management

- Secure firewall traversal, plus NAT

- Automatic software updates

Security

- Ability to disable HTTP, SSH services

- H.235 (AES) encryption support including strict compliance

- TLS/SRTP support

Networking Features

- Adaptive motion control (AMC) including forward error correction (FEC) for superior video quality in all network conditions

- NAT/firewall traversal (H.460/SIP)

- Auto bandwidth detection

- IPv4 and IPv6 support

Directory and Address Book

- Up to 10,000 directory entries

Lifesize Icon 800 Video System (LS-ICON800)

- Global search tool
- LDAP support/H.350 compliant
- Calendar/meeting directory support
- H.323 URI dialing support (Annex O)

System Management

- Web interface
- Auto configuration
- SNMP
- Backup and restore capability
- 2x USB 3.0

Power

- AC voltage 100-240VAC +/- 5%, 50–60 Hz, 2.5A via internal power supply

Environmental Data

- Operating temperature: 0°C (32°F) to 40°C (104°F)
- Operating humidity: 15% to 85%, noncondensing
- Storage temperature: –20°C (–4°F) to 60°C (140°F)
- Storage humidity: 10% to 90%, noncondensing

Video Device Dimensions

- Width: 440 mm (17.32”)
- Depth: 310 mm (12.2”)
- Height: 85 mm (3.35”)
- Weight: 6.99 Kg (15.42 lbs)

Price: Â£12,048.80