

Snom D862 VoIP Phone



Product Name: Snom D862 VoIP Phone

Manufacturer: Snom

Model Number: D862

Snom D862 VoIP phone

The Snom D862 is a beautifully designed entry-level device. Its elegant design makes it suitable for use on any desk. Equipped with a beautiful, 40° continuously adjustable LCD screen of 5" size, it offers a very good overview, regardless of the lighting situation at the workplace. The 8 function keys can be programmed to store speed dials or call groups.

At an incredible price, the Snom D862 combines sophisticated technology, superb voice quality, and an optimal design in one device. As a result, the D862 is an excellent entry point into the world of professional IP telephony.

Key Features

- Large tiltable 5 inch IPS color display

- USB 2.0 high speed connection

- 8 programmable function keys

- Optimised noise reduction

- HD Audio

- On-Screen Smart Labels

Self-labelling function keys You can customise your Snom desk phone to fit your needs with the 8 programmable function keys, which will allow you to make calls or carry out other crucial tasks quickly and easily at the touch of a button.

Elegant Design The D8xx series are an eye-catcher on any desk thanks to their high-quality design with a gunmetal finish.

High-resolution colour display The 1280 x 720-pixel tiltable 5-inch TFT colour display ensures the best possible visibility of the screen content in any lighting.

Innovative technical features Enjoy features including On-Screen Smart Labels, Gigabit Ethernet, HD Audio, Wide Headset Compatibility, IPv6 & IPv4 Protocols, an Ambient Light Sensor, OpenVPN Upgradeability and PoE Power.

Snom D862 Desk Phone - Full Technical Specifications

Basics

- Operating system: Linux

- 3-year warranty

- Wall mountable

- Part number/s: D862 | PN 00004535

Dimensions and Weight

- Dimensions (D x W x H, approx.)

- - 45mm x 243mm x 210mm w/o footstand

- - 165mm x 243mm x 193mm with footstand

Snom D862 VoIP Phone

- Weight (approx.)
- - 1,12kg with footstand

Display and Indicators

• Display

- - TFT liquid crystal display (LCD), tiltable, truecolour, backlit
- - Display size (W x H) 110 mm x 62 mm
- - 5" (127 mm) display size (diagonal)
- - Resolution 1280 x 720 Pixel
- 13 LED indicators
- - Call indication (1 x red LED)
- - Message waiting indication (MWI) (1 x red LED message key)
- - Function key indication (8 x multicolour LEDs)
- - Audio key indication (1 x red LED, 2 x green LED)

Keypad and Function Keys

- 39 hard keys in total
- Standard ITU telephone keypad: 12 keys with star and pound/hash key
- 5-way navigation key
- 12 function keys
- - 4 context-sensitive function keys
- - 8 freely programmable line / function keys (maximum 28 on 4 sides) with multicolor LEDs
- 5 dedicated audio keys
- - Mute key (1 x red LED), speakerphone key (1 x green LED), headset key (1 x green LED), volume control key
- 5 dedicated function keys
- - Cancel key, message key, transfer key, hold key, redial key
- Related features
- Keyboard lock

Directory support and call features

- 8 SIP identities / accounts
- - Up to 8 simultaneous calls
- Directory support
- - LDAP (server-based directory)
- - Local directory with up to 10,000 entries
- - Import/export phone book (CSV, XML)
- - XML phonebook support
- Outgoing call features
- - Speed dialling via function keys

Snom D862 VoIP Phone

- īċ½ - Speed dialling via keypad: 10 numbers
- īċ½ - URL dialling Local dial plan
- īċ½ - Redial (via dialed calls list)
- īċ½ - Automatic redial on busy
- īċ½ - Caller identification (CLIP)
- īċ½ - Calling Line Identification Restriction (CLIR)
- īċ½ - Call completion (busy/unreachable)
- īċ½ - Intercom
- īċ½ - Multicast paging
- īċ½ Incoming call features
 - īċ½ - Call waiting/swapping
 - īċ½ - Call blocking (deny list)
 - īċ½ - Dynamic central blacklist check
 - īċ½ - Blocking of anonymous calls
 - īċ½ - Auto answer
 - īċ½ - Call forwarding
 - īċ½ - Call deflection
 - īċ½ - Do Not Disturb (DND) mode
- īċ½ Active calls
 - īċ½ - Mute microphone
 - īċ½ - Hold
 - īċ½ - Music on hold 2
 - īċ½ - Blind call transfer
 - īċ½ - Attended call transfer
 - īċ½ - 2 + 1 local conferencing
 - īċ½ - Call park / unpark 2
 - īċ½ - Client Matter Code (CMC) 2
- īċ½ Related features
 - īċ½ - Call history lists of missed, received, dialed, rejected, and deflected calls
 - īċ½ - Extension monitoring, call pickup

Audio devices, codecs, and features

- īċ½ Casing speaker
 - īċ½ - Wideband audio
 - īċ½ - Hearing aid compatible (HAC)
 - īċ½ - Frequency range 150 Hz - 8 kHz
 - īċ½ - Noise cancellation
- īċ½ Speakerphone mode
 - īċ½ - Wideband audio
 - īċ½ - Frequency range 100 Hz - 8 kHz
 - īċ½ - Full duplex
 - īċ½ - 2 x dedicated microphones
- īċ½ Audio Codecs
 - īċ½ - G.711 (A-law, μ-law), G.722, G.723.1, G.726, G.729, Opus
- īċ½ Dual-tone multi-frequency signalling (DTMF)
 - īċ½ - In-band, out-of-band, SIP-INFO
 - īċ½ - Related features
 - īċ½ - Comfort noise generator (CNG)
 - īċ½ - Voice activity detection (VAD)
 - īċ½ - Audio response time

Snom D862 VoIP Phone

- Adaptive jitter buffer
- Packet loss concealment (PLC)

Interfaces and Connections

• D862 Power Options

- D862 power options
- Power over Ethernet (PoE), IEEE 802.3af, class 3
- Power adapter 100 - 240 V AC / 50 - 60 Hz | 5 V DC (SELV) / 2 A / 10 W 1

• Wired Interfaces

- 1 x coaxial power adapter connector
- 2 x 1 Gbit RJ45-8P8C Ethernet port
- 1 x USB 2.0 Typ A
- 1 x RJ9-4P4C standard receiver connector
- 1 x RJ9-4P4C standard connector or USB port for wired headset connection
- 1 x RJ12-6P6C proprietary EHS connector1
- 1 x RJ12-6P6C proprietary EHS connector1

• Wireless Interfaces

- Bluetooth optional via USB Bluetooth dongle
- WLAN optional via Snom USB WLAN Dongle 1
- DECT optional via Snom USB DECT Dongle 1

• Sensors

- Ambient light sensor
- Hook switch sensor

• Technologies and Protocols

• Network Technologies

- OpenVPN, VLAN (IEEE 802.1Q)
- VoIP related protocols and techniques
- SIP (RFC 3261), SDP (RFC 3261), RTP (RFC 8866), RTCP (RFC 3550), RTCP-XR, SIP REFER method (RFC 3515), rport (RFC 3581), ENUM, ICE, STUN (RFC 5389)

• Secure VoIP protocols

- SIPS (SIP over TLS), SRTP (RFC 3711), SRTCP

• Network protocols

- IPv4 / IPv6 (Dual Stack), DHCP, NTP, LDAP, LLDP-MED, HTTP, TFTP, L2TP
- Secure network protocols - TLS V1.3 incl. ciphers (forward secret & authenticated), HTTPS, IEEE 802.1X (EAP-TLS - RFC 5216)

• Remote management protocols

- TR-069, TR-069 Annex G (formerly TR-111), TR-369 (USP)

• Environmental Conditions

- Operating ambient temperature: 0 °C bis 35 °C
- Nonoperating temperature: - 10 °C bis 45 °C
- Humidity (non-condensing): 5% - 95%

Package Contents

- 1 x desk phone unit
- 1 x footstand
- 1 x corded receiver
- 1 x 1,5 m (5 ft) Ethernet cable

Snom D862 VoIP Phone

1 x Quick Installation Guide

Accessories

00004544 | Wall mount kit (D8XX)
00004561 | Corded wideband receiver (D8XX)
00004570 | 10 W Power adapter
00004341 | A100M | Monaural Headset
00004342 | A100D | Binaural Headset
00004388 | A150 | DECT-Headset
00004387 | A170 | DECT-Headset
00002362 | EHS Advanced 2.0
00004384 | A210 | USB WLAN dongle
00004386 | A230 | USB DECT dongle

Price: £120.80

Options available for Snom D862 VoIP Phone :

Need Product Setup / Training / Support?

Required - 30 minutes (+£40.00), Not Required, Required - 1 Hour (+£65.00).

Headset

Snom A170 DECT (+£120.50), Snom A100D (+£33.90), Snom EHS Wireless Headset Adapter (+£65.40), Not required, Snom A150 DECT (+£98.40), Snom A100M (+£27.60).

USB Dongle

Snom A230 DECT Adapter (+£33.90), Not required, Snom A210 USB WiFi Dongle (+£23.20).

Mounting Options

Not required, Snom 8 Series Wall Mounting Bracket (+£33.60).