

Snom D862 VoIP Phone



Product Name: Snom D862 VoIP Phone

Manufacturer: Snom

Model Number: D862

Snom D862 VoIP phone

The snom D862 is a beautifully designed entry-level device. Its simple design makes it suitable for use on any desk. Equipped with a beautiful, 40° continuously adjustable LCD screen of 5" size, it offers a very good overview, regardless of the lighting situation at the workplace. The 8 function keys can be programmed to store speed dials or call groups.

At an incredible price, the Snom D862 combines sophisticated technology, superb voice quality, and an optimal design in one device. As a result, the D862 is an excellent entry point into the world of professional IP telephony.

Key Features

- Large tiltable 5 inch IPS color display

- USB 2.0 high speed connection

- 8 programmable function keys

- Optimized noise reduction

Snom D862 Desk Phone - Technical Specifications

Basics

Operating system: Linux 3-year warranty Wall mountable Part number/s: D862 | PN 00004535

Dimensions and Weight

Dimensions (D x W x H, approx.) - 45mm x 243mm x 210mm w/o footstand - 165mm x 243mm x 193mm with footstand Weight (approx.) - 1,12kg with footstand

Display and Indicators

Display - TFT liquid crystal display (LCD), tiltable, truecolour, backlit - Display size (W x H) 110 mm x 62 mm - 5" (127 mm) display size (diagonal) - Resolution 1280 x 720 Pixel 13 LED indicators - Call indication (1 x red LED) - Message waiting indication (MWI) (1 x red LED message key) - Function key indication (8 x multicolour LEDs) - Audio key indication (1 x red LED, 2 x green LED)

Keypad and Function Keys

39 hard keys in total Standard ITU telephone keypad: 12 keys with star and pound/hash key 5-way navigation key 12 function keys - 4 context-sensitive function keys - 8 freely programmable line / function keys (maximum 28 on 4 sides) with multicolor LEDs 5 dedicated audio keys - Mute key (1 x red LED), speakerphone key (1 x green LED), headset key (1 x green LED), volume control key 5 dedicated function keys - Cancel key, message key, transfer key, hold key, redial key Related features Keyboard lock

Directory support and call features

8 SIP identities / accounts - Up to 8 simultaneous calls Directory support - LDAP (server-based directory) - Local directory with up to 10,000 entries - Import/export phone book (CSV, XML) - XML phonebook support Outgoing call features - Speed dialling via function keys - Speed dialling via keypad: 10 numbers - URL dialling Local dial plan - Redial (via dialed calls list) - Automatic redial on busy - Caller identification (CLIP) - Calling Line Identification Restriction (CLIR) - Call completion (busy/unreachable) - Intercom - Multicast paging Incoming call features - Call

Snom D862 VoIP Phone

waiting/swapping - Call blocking (deny list) - Dynamic central blacklist check - Blocking of anonymous calls - Auto answer - Call forwarding - Call deflection - Do Not Disturb (DND) mode Active calls - Mute microphone - Hold - Music on hold 2 - Blind call transfer - Attended call transfer - 2 + 1 local conferencing - Call park / unpark 2 - Client Matter Code (CMC) 2 Related features - Call history lists of missed, received, dialed, rejected, and deflected calls - Extension monitoring, call pickup

Audio devices, codecs, and features

Casing speaker - Wideband audio - Hearing aid compatible (HAC) - Frequency range 150 Hz - 8 kHz - Noise cancellation Speakerphone mode - Wideband audio - Frequency range 100 Hz - 8 kHz - Full duplex - 2 x dedicated microphones Audio Codecs - G.711 (A-law, μ-law), G.722, G.723.1, G.726, G.729, Opus Dual-tone multi-frequency signalling (DTMF) - In-band, out-of-band, SIP-INFO - Related features - Comfort noise generator (CNG) - Voice activity detection (VAD) - Audio response time - Adaptive jitter buffer - Packet loss concealment (PLC)

Interfaces and Connections

D862 Power Options - D862 power options - Power over Ethernet (PoE), IEEE 802.3af, class 3 - Power adapter 100 - 240 V AC / 50 - 60 Hz | 5 V DC (SELV) / 2 A / 10 W 1 Wired Interfaces - 1 x coaxial power adapter connector - 2 x 1 Gbit RJ45-8P8C Ethernet port - 1 x USB 2.0 Typ A - 1 x RJ9-4P4C standard receiver connector - 1 x RJ9-4P4C standard connector or USB port for wired headset connection - 1 x RJ12-6P6C proprietary EHS connector1 - 1 x RJ12-6P6C proprietary EHS connector1 Wireless Interfaces - Bluetooth optional via USB Bluetooth dongle - WLAN optional via Snom USB WLAN Dongle 1 - DECT optional via Snom USB DECT Dongle 1 Sensors - Ambient light sensor - Hook switch sensor

Technologies and Protocols

Network Technologies - OpenVPN, VLAN (IEEE 802.1Q) VoIP related protocols and techniques - SIP (RFC 3261), SDP (RFC 3261), RTP (RFC 8866), RTCP (RFC 3550), RTCP-XR, SIP REFER method (RFC 3515), rport (RFC 3581), ENUM, ICE, STUN (RFC 5389) Secure VoIP protocols - SIPS (SIP over TLS), SRTP (RFC 3711), SRTCP Network protocols - IPv4 / IPv6 (Dual Stack), DHCP, NTP, LDAP, LLDP-MED, HTTP, TFTP, L2TP Secure network protocols - TLS V1.3 incl. ciphers (forward secret & authenticated), HTTPS, IEEE 802.1X (EAP-TLS - RFC 5216) Remote management protocols - TR-069, TR-069 Annex G (formerly TR-111), TR-369 (USP)

Environmental Conditions

- Operating ambient temperature: 0 ° C bis 35 ° C - Nonoperating temperature: - 10 ° C bis 45 ° C - Humidity (non-condensing): 5% - 95%

Package Contents

- 1 x desk phone unit - 1 x footstand - 1 x corded receiver - 1 x 1,5 m (5 ft) Ethernet cable - 1 x Quick Installation Guide

Accessories

- 00004544 | Wall mount kit (D8XX) - 00004561 | Corded wideband receiver (D8XX) - 00004570 | 10 W Power adapter - 00004341 | A100M | Monaural Headset - 00004342 | A100D | Binaural Headset - 00004388 | A150 | DECT-Headset - 00004387 | A170 | DECT-Headset - 00002362 | EHS Advanced 2.0 - 00004384 | A210 | USB WLAN dongle - 00004386 | A230 | USB DECT dongle

Please Enquire