

Yeastar TG400L 4 Ports 4G LTE Gateway



Product Name: Yeastar TG400L 4 Ports 4G LTE Gateway

Manufacturer: Yeastar Model Number: TG400L

Yeastar TG400L 4 Ports 4G LTE Gateway

The Yeastar TG400L connects 4G LTE to VoIP networks to provide 2-way communication: GSM/3G/4G to VoIP and VoIP to GSM/3G/4G. It allows you to connect most IP-based telephone systems including Yeastar IP Phone Systems, and soft switches to a 4G LTE; which can provide a sophisticated fallback solution when landlines go down, or be used to increase call traffic capacity by providing additional dial-tone.

Yeastar TG400L Key Features

� VoLTE for HD Calls

ï¿1/2 Maximum Cost Reduction

� Top Quality and Reliability

� Mobile Connectivity for SMB

ī¿1/2 Simple and intuitive Web-based configuration saves you loads of time

าั¿½ Add GSM/WCDMA trunkings for business making high number of calls to mobile networks

T¿½ Great tool for enterprises to manage customer relations and introduce special offers with a low cost

آذِرًا Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server

Easy to use

Simple and intuitive Web-based configuration saves you loads of time

Mobile Trunkings

Add GSM/WCDMA trunkings for business making high number of calls to mobile networks Bulk SMS Service

Great tool for enterprises to manage customer relations and introduce special offers with a low cost

Interoperability

Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server Yeastar TG400L Technical Specifications

General

� Ports: 4 LTE

ï¿1/2 GSM Frequency: 850/900/1800/1900 MHz

T¿1/2 UMTS Frequency: 850/1900 MHz, 850/2100 MHz, 900/2100 MHz

� 4G LTE Band: Yes

ï¿⅓ CDMA Frequency: 800 MHz

آزٰ Protocol: SIP, IAX2

� Transport: UDP, TCP, TLS, SRTP

12/2 Voice Codec: G.711 (alaw/ulaw), G.722, G.726, G.729A, GSM, ADPCM, Speex

� Echo Cancellation: ITU-T G.168 LEC

آزا DTMF Mode: RFC2833, SIP INFO, In-band

i¿½ Calling Type: Termination (VoIP to GSM/CDMA/UMTS), Origination (GSM/CDMA/UMTS to

/oIP)

12.1/2 Network Protocol: FTP, TFTP, HTTPS, SSH

� NAT Traversal: Static NAT, STUN

آذِرُ Network: DHCP, DDNS, Firewall, OpenVPN, Static IP, QoS, Static Route, VLAN

ï¿1/2 Power Supply: AC 100-240V



Yeastar TG400L 4 Ports 4G LTE Gateway

- � Operation Range: 0°C to 40°C, 32°F to 104°F i¿½ Storage Range: -20°C to 65°C, -4°F to 149°F
- � Humidity: 10-90% non-condensing

System Features

- آزٰ Mobile Ports Groups
- ï¿⅓ VoIP Trunk Group
- ï¿⅓ Incoming /Outgoing Routing rules
- ï¿⅓ Black List
- ï¿⅓ Hotline
- ï¿⅓ AutoCLIP
- � Call Duration Limitation
- � Call Transfer
- ï¿⅓ Call Back
- ï¿1/2 Call Detail Record (CDR
- � Call Status Display
- NTP ½'i∃
- ï¿⅓ IP Blacklist
- � Network Attack Alert
- � Packet Capture
- ï¿⅓ System Logs

Physical

� Size (mm): 213x160x44 � Power Supply: AC 100-240V

Price: 2,132.79EUR