

Yeastar TG400L 4 Ports 4G LTE Gateway



Product Name: Yeastar TG400L 4 Ports 4G LTE Gateway

Manufacturer: Yeastar

Model Number: TG400L

Yeastar TG400L 4 Ports 4G LTE Gateway

The Yeastar TG400L connects 4G LTE to VoIP networks to provide 2-way communication: GSM/3G/4G to VoIP and VoIP to GSM/3G/4G. It allows you to connect most IP-based telephone systems including Yeastar IP Phone Systems, and soft switches to a 4G LTE; which can provide a sophisticated fallback solution when landlines go down, or be used to increase call traffic capacity by providing additional dial-tone.

Yeastar TG400L Key Features

½ VoLTE for HD Calls

½ Maximum Cost Reduction

½ Top Quality and Reliability

½ Mobile Connectivity for SMB

½ Simple and intuitive Web-based configuration saves you loads of time

½ Add GSM/WCDMA trunkings for business making high number of calls to mobile networks

½ Great tool for enterprises to manage customer relations and introduce special offers with a low cost

½ Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server

Easy to use

Simple and intuitive Web-based configuration saves you loads of time

Mobile Trunkings

Add GSM/WCDMA trunkings for business making high number of calls to mobile networks

Bulk SMS Service

Great tool for enterprises to manage customer relations and introduce special offers with a low cost

Interoperability

Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server

Yeastar TG400L Technical Specifications

General

½ Ports: 4 LTE

½ GSM Frequency: 850/900/1800/1900 MHz

½ UMTS Frequency: 850/1900 MHz, 850/2100 MHz, 900/2100 MHz

½ 4G LTE Band: Yes

½ CDMA Frequency: 800 MHz

½ Protocol: SIP, IAX2

½ Transport: UDP, TCP, TLS, SRTP

½ Voice Codec: G.711 (alaw/ulaw), G.722, G.726, G.729A, GSM, ADPCM, Speex

½ Echo Cancellation: ITU-T G.168 LEC

½ DTMF Mode: RFC2833, SIP INFO, In-band

½ Calling Type: Termination (VoIP to GSM/CDMA/UMTS), Origination (GSM/CDMA/UMTS to VoIP)

½ Network Protocol: FTP, TFTP, HTTP, HTTPS, SSH

½ NAT Traversal: Static NAT, STUN

½ Network: DHCP, DDNS, Firewall, OpenVPN, Static IP, QoS, Static Route, VLAN

½ Power Supply: AC 100-240V

Yeastar TG400L 4 Ports 4G LTE Gateway

½ Operation Range: 0°C to 40°C, 32°F to 104°F
½ Storage Range: -20°C to 65°C, -4°F to 149°F
½ Humidity: 10-90% non-condensing

System Features

- ½ Mobile Ports Groups
- ½ VoIP Trunk Group
- ½ Incoming /Outgoing Routing rules
- ½ Black List
- ½ Hotline
- ½ AutoCLIP
- ½ Call Duration Limitation
- ½ Call Transfer
- ½ Call Back
- ½ Call Detail Record (CDR)
- ½ Call Status Display
- ½ NTP
- ½ IP Blacklist
- ½ Network Attack Alert
- ½ Packet Capture
- ½ System Logs

Physical

½ Size (mm): 213x160x44
½ Power Supply: AC 100-240V

Price: £1,875.00