

## Yeastar TA200 VolP Telephone Adapter



Product Name: Yeastar TA200 VoIP Telephone Adapter

Manufacturer: Yeastar Model Number: TA200

Yeastar TA200 VoIP Telephone Adapter

Yeastar TA Series analog telephone adapters provide 1 or 2 analog interfaces for residential users and small business to convert existing analog equipment to IP-based networks cost effectively.

Yeastar TA200 VoIP Telephone Adapter Key Features

ï¿1/2 3-way Conference

ï¿1/2 Auto Provisioning with MyPBX

ï¿1/2 Blind Transfer

� Call Forward (Always, Busy, No Answer)

� Caller ID Display

ï¿⅓ Distinctive Ringtones

تز½ Firewall

ï¿⅓ Hotline

� MWI (FSK, Polarity Reversal)

� Packet Capture Tool

ï¿⅓ System Logs

� Web-based Management

API ي∕′¿ï

� Attended Transfer

� Backup and Restore

� Call Detail Records

تز½ Call Waiting

� Direct IP Dialing

آزِہِ Do Not Disturb

� Firmware Upgrade by HTTP/TFTP

ï¿1/2 IP Blacklist

ï¿1/2 Nat Traversal

آز½ Speed Dial

� Voice Menu for Basic Configuration

It is ideal for small business to achieve quick and easy connections to existing analog devices within a VoIP network. Use these in conjunction with both Yeastar and non-Yeastar manufactured IP Phone systems to connect fax machines, and analog telephones.

Yeastar TA200 VoIP Telephone Adapter Technical Specifications General

� Ports: 2 FXS Ports

ï¿1/2 Telephony Interfaces: RJ11

� Network Interfaces: 1 10/100Base-T Ethernet

ϊ¿½ USB: 1 Micro USB Port ϊ¿½ Protocol: SIP (RFC3261)

Ti21/2 Transport: UDP, TCP, TLS, SRTP

� Codec: G.711 (alaw/ulaw), G.729A/B

17:1/2 DTMF Mode: RFC2833, SIP Info, In-band

ī సైస్తో Voice Capability: ITU-T G.168 LEC Echo Cancellation, Dynamic Jitter Buffer

ï¿1/2 Fax: T.30 Pass-through

ï¿1/2 QoS: DiffServ, ToS, 802.1 P/Q VLAN tagging

آذِر Network: DHCP, OpenVPN, PPPoE, Static Route, VLAN

آذً Network Protocol: FTP, TFTP, HTTP, HTTPS, SSH



## Yeastar TA200 VoIP Telephone Adapter

- ï¿1/2 Management Protocol: TR-069
- ï¿1/2 Signaling: FXS Loop Start, FXS Kewl Start
- آزار Caller ID: BELL202, ETSI (V23), NTT (V23-Japan), and DTMF-based CID
- า๊¿½ Disconnect Methods: Busy Tone, Polarity Reversal
- � Power: DC 5V 1A
- $\ddot{i}_{2}$  Dimensions (LxWxH): 85 x 58 x 24 mm  $\ddot{i}_{2}$  Humidity: 10-90% non-condensing
- $\ddot{\imath}$ ى Storage Range: -20°C to 65°C, -4°F to 149°F
- ازن $^{1}$  Operation Range:0°C to 40°C, 32°F to 104°F
- ï¿⅓ Mounting: Desktop
- ī¿½ Compatibility: Interoperable with 3CX, Asterisk, Lync Server, FreePBX and certified with

Elastix and BroadSoft

Price: £46.90