

## Yeastar TA200 VoIP Telephone Adapter



Product Name: Yeastar TA200 VoIP Telephone Adapter

Manufacturer: Yeastar

Model Number: TA200

Yeastar TA200 VoIP Telephone Adapter

Yeastar TA Series analog telephone adapters provide 1 or 2 analog interfaces for residential users and small business to convert existing analog equipment to IP-based networks cost effectively.

Yeastar TA200 VoIP Telephone Adapter Key Features

- 3-way Conference
- Auto Provisioning with MyPBX
- Blind Transfer
- Call Forward (Always, Busy, No Answer)
- Caller ID Display
- Distinctive Ringtones
- Firewall
- Hotline
- MWI (FSK, Polarity Reversal)
- Packet Capture Tool
- System Logs
- Web-based Management
- API
- Attended Transfer
- Backup and Restore
- Call Detail Records
- Call Waiting
- Direct IP Dialing
- Do Not Disturb
- Firmware Upgrade by HTTP/TFTP
- IP Blacklist
- Nat Traversal
- Speed Dial
- Voice Menu for Basic Configuration

It is ideal for small business to achieve quick and easy connections to existing analog devices within a VoIP network. Use these in conjunction with both Yeastar and non-Yeastar manufactured IP Phone systems to connect fax machines, and analog telephones.

Yeastar TA200 VoIP Telephone Adapter Technical Specifications

General

- Ports: 2 FXS Ports
- Telephony Interfaces: RJ11
- Network Interfaces: 1 10/100Base-T Ethernet
- USB: 1 Micro USB Port
- Protocol: SIP (RFC3261)
- Transport: UDP, TCP, TLS, SRTP
- Codec: G.711 (alaw/ulaw), G.729A/B
- DTMF Mode: RFC2833, SIP Info, In-band
- Voice Capability: ITU-T G.168 LEC Echo Cancellation, Dynamic Jitter Buffer
- Fax: T.30 Pass-through
- QoS: DiffServ, ToS, 802.1 P/Q VLAN tagging
- Network: DHCP, OpenVPN, PPPoE, Static Route, VLAN
- Network Protocol: FTP, TFTP, HTTP, HTTPS, SSH

## Yeastar TA200 VoIP Telephone Adapter

- Management Protocol: TR-069
- Signaling: FXS Loop Start, FXS Kewl Start
- Caller ID: BELL202, ETSI (V23), NTT (V23-Japan), and DTMF-based CID
- Disconnect Methods: Busy Tone, Polarity Reversal
- Power: DC 5V 1A
- Dimensions (LxWxH): 85 x 58 x 24 mm
- Humidity: 10-90% non-condensing
- Storage Range: -20&deg;C to 65&deg;C, -4&deg;F to 149&deg;F
- Operation Range: 0&deg;C to 40&deg;C, 32&deg;F to 104&deg;F
- Mounting: Desktop
- Compatibility: Interoperable with 3CX, Asterisk, Lync Server, FreePBX and certified with Elastix and BroadSoft

**Price: Â£46.90**

---