

Grandstream GRP2670 12-Line IP Phone



Product Name: Grandstream GRP2670 12-Line IP Phone

Manufacturer: Grandstream

Model Number: GRP2670

Grandstream GRP2670 12-Line IP Phone

The Grandstream GRP2670 is an executive-quality 12-line model with a 7-inch touch screen designed with zero-touch provisioning for mass deployment and easy management. Part of the GRP series of Professional Carrier-Grade IP Phones, the GRP2670 is an executive-quality 12-line model designed with zero-touch provisioning for mass deployment and easy management. It features a sleek design and a suite of next-generation features including a 7 inch touch screen, built-in dual-band Wi-Fi, Bluetooth support, 5-way voice conferencing, integrated PoE, full HD audio and more.

Grandstream GRP2670 Key Features:

- 12 lines, 6 SIP accounts

- Supported by GDMS which provides a centralized interface to configure, provision, manage and monitor Grandstream devices

- 7-inch (1024x600) capacitive touch screen

- Full-duplex speakerphone with HD audio to maximise audio quality and clarity

The GRP series offers carrier-grade security features to provide enterprise-level security, including secure boot, dual firmware images and encrypted data storage. For cloud provisioning and centralized management, the GRP2670 is supported by Grandstream's Device Management System (GDMS), which provides a centralised interface to configure, provision, manage and monitor deployments of Grandstream endpoints. With 64 Virtual Multi-Purpose Keys (VPK), an easy-to-use 7-inch capacitive touch screen, and support for Bluetooth, EHS (Plantronics) and USB headsets, the GRP2670 is the perfect choice for busy professionals, executives, and receptionists who manage high call volumes. Designed for easy mass deployment by enterprises, service providers and other high-volume markets, the GRP2670 offers a high-end, easy-to-use and easy-to-deploy voice endpoint.

Grandstream GRP2670 Technical Specifications

General

- Protocols/Standards SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6

- Network Interfaces Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE

- Graphic Display 7 inch (1024x600) capacitive touch screen TFT LCD

- Wi-Fi Yes, integrated dual-band (2.4Ghz & 5Ghz) Wi-Fi

- Bluetooth Yes, integrated

- Feature Keys 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HEADSET, HOLD MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL

- Auxiliary Port RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets

- Voice Codecs and Capabilities Support for G.729A/B, G.711µ-law, G.726, G.722(wide-band), G.723, iLBC, OPUS, inband and out-of-band DTMF(in audio, RFC2833, SIP INFO)

- Telephony Features Hold, transfer, forward, 5-way conference, call park, call pickup, shared-callappearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call log(up to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over

Grandstream GRP2670 12-Line IP Phone

- HD Audio Yes, HD handset and speakerphone with support for wideband audio
- Extension Module Yes
- Base Stand Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)
- QoS Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS
- Security User and administrator level passwords, MD5 and MD5-session based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.
- Multi-language English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more
- Upgrade/Provisioning Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR069 or AES encrypted XML configuration file.
- Power & Green Energy Efficiency Universal power adapter included: Input:100-240V ; Output: +12V, 1A ; Integrated Power-over-Ethernet(802.3af) Max power consumption 6.5W(power adapter)
- Temperature and Humidity Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing
- Package Content GRP2670 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license
- Physical Dimension: Unit weight:1.1kg ; Package weight:1.65kg Dimension: 267mmx 220mmx 82mm
- GRP2670 Compliance FCC: Part 15 Subpart B(Class B), Part 15 Subpart C 15.247, Part 15 Subpart C 15.407, Part 15 Subpart I, Part 68. 316/317; IC: RSS-247, RSS-Gen, RSS-102, ICES-003, CS-03 Part V; CE: EN 55032, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 62368-1, EN 62311, EN 301 489-1, EN 301 489-17, EN 300 328, EN 301 893; RCM: AS/NZS CISPR 32, AS/NZS 62368.1, AS/NZS 4268, AS NZS 2772.2, AS/CA S004.

Price: Â£155.20

Options available for Grandstream GRP2670 12-Line IP Phone :

Need Product Setup / Training / Support?

Required - 30 minutes (+Â£40.00), Required - 1 Hour (+Â£65.00), Not Required.