

Fanvil X3U IP Phone - White Label



Product Name: Fanvil X3U IP Phone - White Label

Manufacturer: Fanvil

Model Number: X3U-WL

Please Note: This product is white label and available for you to add your own branding. We have a minimum order quantity of 10 on this unit. Please enquire or give us a call on 0330 088 0195 for more information.

Fanvil X3U IP Phone - White Label

The Fanvil X3U is a feature-rich entry-level IP Phone with colour screen. The X3U offers businesses the highest quality, convenience and user experience at an affordable price.

Fanvil X3U IP Phone Key Features

- ½ 3 Line keys on the main display
- ½ 2.8" main colour display
- ½ HD audio on speakerphone and handset
- ½ Opus voice
- ½ Supports EHS wireless headsets
- ½ Dual Gigabit ports, integrated PoE
- ½ Stand with 2 adjustable angles of 45 and 50 degrees
- ½ Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc.

Supports EHS Wireless Headsets The Fanvil X3U supports EHS wireless headsets, for a professional VoIP phone experience

Fanvil X3U IP Phone - Technical Specifications

Generic

- ½ 6 SIP Lines
- ½ HD Voice
- ½ PoE enabled
- ½ 2.8 inch colour screen
- ½ Handset / Hands-free / Headset mode
- ½ Desktop stand/ Wall-mounted installation (needs additional wall handing parts)
- ½ Optional external power supply

Phone functions

- ½ Local Phonebook (1000 entries)
- ½ Remote Phonebook (XML/LDAP, 1000 entries)
- ½ Call logs (In/Out/Missed, 600 entries)
- ½ Black/White List Call Filter
- ½ Screen saver
- ½ Voice Message Waiting Indication (VMWI)
- ½ Programmable DSS/Soft keys
- ½ Network Time Synchronization
- ½ Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)
- ½ Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- ½ Support Recording (Through Server)
- ½ Action URL / Active URI
- ½ uaCSTA

Call functions

Fanvil X3U IP Phone - White Label

• Call out / Answer / Reject
• Mute / Unmute (Microphone)
• Call Hold / Resume
• Call Waiting
• Intercom
• Caller ID Display
• Speed Dial
• Anonymous Call (Hide Caller ID)
• Call Forward (Always/Busy/No Answer)
• Call Transfer (Attended/Unattended)
• Parking/Pick-up (Depending on server)
• Redial
• Do-Not-Disturb
• Auto-Answering
• Voice Message (With server)
• 3-way Conference
• Hot Line
• Hot desking

Audio

• HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
• HAC handset
• Wideband ADC/DAC 16KHz Sampling
• Narrowband Codec: G.711a/u, G.726-32K, G.729A, iLBC
• Wideband Codec: G.722, Opus
• Full-duplex Acoustic Echo Canceller (AEC)
• Voice Activity Detection (VAD) / Comfort Noise Generation (CNG)/ Background Noise Estimation (BNE) / Noise Reduction (NR)
• Packet Loss Concealment (PLC)
• Dynamic Adaptive Jitter Buffer
• DTMF: In-band, Out-of-Band & DTMF-Relay (RFC2833) / SIP INFO

Networking

• Physical: 10/100 Mbps Ethernet, dual bridged port for PC bypass
• IP Mode: IPv4/IPv6/IPv4&IPv6
• IP Configuration: Static IP / DHCP / PPPoE
• Network Access Control: 802.1x
• VPN: L2TP / OpenVPN
• VLAN
• LLDP
• QoS
• RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Protocols

• SIP2.0 over UDP/TCP/TLS
• RTP/RTCP/SRTP
• STUN
• DHCP
• LLDP
• PPPoE
• 802.1x
• L2TP

Fanvil X3U IP Phone - White Label

- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP/OPT66/SIP PNP/TR069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

Physical Specifications

- Main LCD x1: 2.8-inch (320x240) Color Screen Keypad: 37 keys, including - 4 Soft-keys - 9 Function keys (Hold/Transfer/Conference/Phonebook /MWI/Headset/Redial) - 2 Line keys (With LED Indicator Light) - 4 Navigation keys - 1 OK key - 12 Standard Phone Digits keys - 3 Volume Control keys (Up/Down/Mute (Microphone)) - 1 Hands-free key
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5 Ethernet Cable x1
- Back Rack x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- Safety Keyhole x1
- DC Power Input: 5V/0.6A
- Power Consumption: Idle 0.9~1.65W, Peak 1.8~2.95W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation: - Desktop Stand - Wall-mounted (need an additional wall hanging parts)
- Color: Black - Device Dimensions: - Desktop Stand (Angles 1): 169x186.3x174.5 mm - Desktop Stand (Angles 2): 169x177.6x183.7 mm - Wall-mounted: 169x115.6x212.5 mm
- Gift Box Dimensions: 274x215x68 mm
- Outer CTN Dimensions: 450x360x294 mm (10 PCS)

Please Enquire