

## Snom D717 Entry-Level IP Phone - White Label



Product Name: Snom D717 Entry-Level IP Phone - White Label

Manufacturer: Snom

Model Number: D717-WL

Please Note: This product is white label and available for you to add your own branding. We have a minimum order quantity of 10 on this unit. Please enquire or give us a call on 0330 088 0195 for more information.

### Snom D717 Entry-Level IP Phone - White Label

The Snom D717 features an intuitive design with advanced technology and connectivity. Three self-labelling programmable feature keys sit next to a 2.8-inch, 320 x 240 pixel color LCD display. Opus codec support gives you the freedom to enjoy crystal-clear audio or high-quality narrowband audio, depending on your network conditions.

#### Snom D717 Key Features

- High-resolution 2.8" graphical TFT display
- 3 self-labelling function keys
- Wideband hands-free talking (speakerphone)
- Digital Signal Processor (DSP) enhanced audio quality
- 2-port Gigabit Ethernet switch (RJ45)
- Power over Ethernet IEEE 802.3af, Class 2
- USB headset ready
- D7 Expansion Module ready
- Support for USB WiFi stick
- Electronic Hook Switch (EHS)(1) support for wireless headsets
- Dual-angle footstand: 46° and 28°

Zero touch provisioning eliminates the need for manual labor typically involved with installation. Power over Ethernet (PoE) support and dual Ethernet ports makes the system cost-effective and easy to use. The USB port allows additional connectivity, including up to three D7 expansion modules for increased visibility and one-button options. The system features multiple configurations, including three programmable feature keys, four soft keys and 14 dedicated feature keys. You'll feel safe with powerful security features like VPN support.

#### Snom D717 Technical Specifications

##### Phone Features

- 6 SIP identities / accounts
- XML browser
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP PBX Platforms
- Speed dialing
- URL dialing
- Local dial plan
- Automatic redial on busy
- Call completion (busy/unreachable)
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold

## Snom D717 Entry-Level IP Phone - White Label

- Music on hold
- Blind and attended transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup
- Call park, call unpark
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC)
- Unified Communications ready

### Audio

#### • Codecs:

- G.711 A-law,  $\mu$ -law
- G.722 (wideband)
- G.726, G.729AB, GSM 6.10 (FR)

- Built-in assignable ringtones
- Comfort noise generator (CNG)
- Voice activity detection (VAD)

### Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

### User Interface

- Localisation (language, time, dial tone)
- Red LED for call indication / message waiting
- 4 context sensitive keys
- 3 programmable line / function keys with multicolour LEDs
- Dedicated keys for: Message, DND, directory, menu, transfer, hold, page
- Audio keys with LED indication: Mute, speakerphone, headset
- Volume key
- 5-way navigation key
- OK and cancel keys
- Sensor-assisted user interface

### Security

- 802.1X Authentication and EAPOL
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- HTTPS server/client
- Password-protected web interface
- VPN support
- VLAN (IEEE 802.1Q)

## Snom D717 Entry-Level IP Phone - White Label

• LLDP-MED, RTCP-XR

Specifications, Weights and Dimensions

• Dimensions (approx.):

• 7.28" x 3.54" x 8.66"

• With desk stand: "7.28" x 8.46" x 6.81"

• Weight (approx.): 1.8 lbs

• Input voltage: 5V DC (SELV)

• Power supply: PoE or 5Vdc power adapter(1), 10 Watts

• Handset: 4P4C

• Headset: 4P4C; Support for Snom EHS Advanced

• Hearing aid compatible (HAC) handset

• 1 x USB 2.0 host port, Type A

• Environmental conditions:

• Ambient temperature: 0°C to 35°C (32°F to 95°F)

• Storage temperature: -10°C to 45°C (14°F to 113°F)

• Humidity: 5% to 95% (non-condensing)

• Included in delivery:

• Phone Unit

• Foot stand

• Handset with cord

• Ethernet cable

• Quick Start Guide

• Color: Black

• Warranty: 3 years

• Part Number: 00004397 (all markets)

• APN: 80-S065-00

**Please Enquire**

---