

Snom D735 IP Phone - Black - White Label



Product Name: Snom D735 IP Phone - Black - White Label

Manufacturer: Snom Model Number: D735-WL

Please Note: This product is white label and available for you to add your own branding. We have a minimum order quanity of 10 on this unit. Please enquire or give us a call on 0330 088 0195 for more information.

Snom D735 IP Phone - Black - White Label

The Snom D735 business VoIP phone is on the cutting edge in terms of technical features and appearance. The high-resolution 2.7" colour display is surrounded by eight multicoloured function keys that you can label yourself. In order to constantly show the user all the important information they could need, the Snom D735 has a built-in motion sensor – the first VoIP telephone in the world to have such a feature!

Snom D735 Key Features

- า๊ะ่ 1/2 High-resolution 2.7" graphical TFT display
- � 32 self-labelling function keys (8 physical)
- ï¿1/2 Sensor technology enables responsive UI
- i¿½ Wideband hands-free talking (speakerphone)
- าั¿1/2 Digital Signal Processor (DSP) enhanced audio quality
- � 2-port Gigabit Ethernet switch (RJ45)
- 17.1/2 Power over Ethernet IEEE 802.3af, Class 2
- � USB headset ready
- � D7 Expansion Module ready
- $\ddot{\imath}$ Support for USB WiFi stick
- า๊¿½ Electronic Hook Switch (EHS) support for wireless headsets
- � Dual-angle footstand: 46° and 28°

As soon as the user's hand approaches the display or the function keys, the display springs to life and automatically shows all the relevant key assignment information. When you move your hand away again, the display reverts to its normal mode. This smart sensor expands the functionality of the D735 enormously and supports the user in their day to day activities. Of course, the Snom D735 also benefits from the tried and tested HD audio quality that has become standard for our telephones. Thanks to this quality, you would be excused for thinking that the person you're talking to was sitting right next to you! This is made possible due to the integrated 'Digital Signal Processors' (DSP), which optimise sound quality in real time, filter out background noise and do so much more. Three-way conferences are also possible with next to no effort.

The Snom D735 also has an integrated gigabit switch with Power over Ethernet (PoE) functionality, as well as a USB port so you can swiftly connect accessories, like USB headsets, to the device.

The Snom D735 is a compact all-rounder and is perfect for all possible uses thanks to its modern and smart functions, as well as the timeless design and colour variants. The new optimised firmware allows each user to forward calls at the touch of a button, initiate conference calls or mute the telephone temporarily.

Snom D735 - Technical Specifications Features

ï¿1/2 12 SIP identities / accounts

� XML browser

ï¿1/2 Call lists for dialled, received, missed calls

ï¿1/2 Local directory with 1000 entries



Snom D735 IP Phone - Black - White Label

- � Multiple language support
- آزٰ DTMF in-band / out-of-band / SIP-INFO
- آذ½ Interoperable with all major IP PBX platforms

Call Features

- ï¿⅓ Speed dialling
- ï¿⅓ URL Dialling
- ï¿1/2 Local dial plan
- ï¿1/2 Automatic redial on busy
- � Call completion (busy/unreachable)(
- � Caller identification
- ï¿1/2 Call waiting
- � Call blocking (deny list)
- � Auto answer
- Hold ½;ï
- ï¿1/2 Music on hold
- � Blind and attended transfer
- ï¿1/2 Call forwarding
- ï¿⅓ 3-way conferencing on the phone
- � Extension monitoring, call pickup
- � Call park, call unpark
- ï¿⅓ Multicast paging
- � DND mode (do not disturb)
- � Keyboard lock
- ï¿1/2 Client matter code (CMC)
- � Unified Communications ready

Audio

ï¿⅓ Codecs:

- ï¿1/2 G.711 A-law, µ-law
- ï¿⅓ G.722 (wideband) ·
- ï¿1/2 G.726, G.729AB, GSM 6.10 (FR)
- � Built-in assignable ringtones
- ï¿1/2 Comfort Noise Generator (CNG)
- � Voice Activity Detection (VAD)

Setup

- ï¿1/2 Configurable through a web interface
- าั¿½ Provisioning: Automatic loading of settings via HTTP/HTTPS/TFTP
- ï¿1/2 DHCP Options 66/67
- ï¿⅓ Snom Redirection Service
- ï¿1/2 Remote management via TR-069 / TR-111

Protocols

- � SIP (RFC3261)
- آز½ DHCP, NTP
- آذِ½ HTTP / HTTPS / TFTP
- � LDAP (Directory



Snom D735 IP Phone - Black - White Label

� Dual Stack IPv4 / IPv6

User Interface

- � Localisation (language, time, dial tone)
- า๊¿½ Red LED for call indication/message waiting
- � 4 context-sensitive keys
- ī సై 32 (8 physical)programmable line/function keys with multicolour LEDs
- $\ddot{\iota}$ Dedicated keys for Message, DND, Directory, Menu, Transfer, Hold, Page
- īస్ట్ Audio keys with LED indication: Mute, Speakerphone, Headset
- ï¿⅓ Volume key
- � 5-way navigation key
- � OK and Cancel keys
- ï¿1/2 Sensor-assisted user interface

Security

- ï¿1/2 802.1X authentication and EAPOL
- � Transport layer security (TLS)
- ï¿1/2 SRTP (RFC3711), SIPS, RTCP
- ï¿1/2 HTTPS server/client
- � password-protected web interface
- � VPN-support
- � VLAN (IEEE 802.1Q)
- � LLDP-MED, RTCP-XR

Type Approvals

- � CE Mark
- ï¿1/2 Safety IEC 60950

Phone Features

- � Dimensions (approx.):
- � 205 x 185 x 40 mm (LxWxD) w/o foot stand
- \ddot{i} ¿½ 205 x 185 x 200/220 mm (LxWxD) with foot stand
- � Weight (approx.): device 450g, footstand 120g
- � Input voltage: 5Vdc (SELV)
- า๊ะ่ Power supply: PoE or 5Vdc power adapter(1), 10 Watts
- ï¿1/2 Handset: 4P4C
- آذِاتِ Headset: 4P4C; Support for Snom EHS Advanced
- تزار Hearing-aid compatible (HAC) handset
- � 1 x USB 2.0 host port, Type A
- � Environmental conditions:
- រី¿½ Ambient temperature: 0°C to 35°C (32°F to 95°F)
- تزرير Storage temperature: -10°C to 45°C (14°F to 113°F)
- � Humidity: 5% to 95% (non-condensing)
- าั¿½ Included in delivery: Phone unit, Footstand, Handset with cord, Ethernet cable, Quick Start

Guide, Colour: black or white

ï¿1/2 Warranty: 2 Years

Please Enquire