Atcom IP08 8-port Asterisk IP PBX



Product Name: Atcom IP08 8-port Asterisk IP PBX
Manufacturer: Atcom
Model Number: IP08

Atcom IP08 8-port Asterisk IP PBX

Please Note: An understanding of both Linux and Asterisk command line is required for the successful configuration of the Atcom IP0x. VoIPon offers paid for support options for customers who experience difficulty configuring this PBX, which can be selected from the options below.

The Atcom IP08 8-port Asterisk IP PBX is a complete Asterisk powered IP-PBX with eight FXO/FXS channels, It is an embedded system with built-in SIP/IAX proxy server and NAT functions. It provides a solid, uniform platform for traditional PSTN communications as well as VoIP communications.
Features

ï¿½ 8 FXO/FXS Ports
ï¿½ Supports SIP and IAX2 Protocol
ï¿½ Easy to configure and install
ï¿½ Smart IVR system
ï¿½ Paperless fax to email
ï¿½ Unlimited recording

Atcom IP08 - Technical Specification
PBX Features

ï¿½ Basic Features

ï¿½ Blacklist, Caller ID, Call Back, Call Detail Records (CDR), Call Pickup (Group Pickup & Directed Pickup),Call Parking, Call Queues, Call Recording, Call Routing, Call Transfer (Blind Transfer & Attend Transfer), Call Waiting,Conference, Do Not Disturb (DND), Follow me, Interactive Voice Response (IVR), Intercom/Paging, Music on Hold (MoH),Ring Group, Skype Integration (Skype for SIP), Voice Mail, Voice Mail to Email

ï¿½ Advanced Features:

ï¿½ Call Recording, Direct Inward System Access (DISA), Dual-OS Redundancy, External StorageSupported, IP Restriction, Personal Web Portal, Storage Quota, Privilege, Diagnosics Tool, Customised DialPlan, Auto Provisioning.

ï¿½ Audio Codec :G711(A/μ), G.722,G726,G729,GSM,Speex,ADPCM
ï¿½ Video Codec:H261, H263, H263P,H264
ï¿½ Fax Features: Fax to Email

Hardware Features

ï¿½ LAN Port:1 10 / 100Mbps
ï¿½ WAN Port:1 10 / 100Mbps
ï¿½ Analog Port:8 RJ11
ï¿½ ATCOM Telephony Module supported: Up to 8 Port FXO or 8 Port FXS

Network Features

Atcom IP08 8-port Asterisk IP PBX

ï¿½ DHCH Server / Client: Yes
ï¿½ DDNS: Yes
ï¿½ Static IP: Yes
ï¿½ VLAN (802.1Q):Yes
ï¿½ VPN: Yes (PPTP VPN supported)
ï¿½ Security: Yes (Firewall)
ï¿½ Port: Forward

SIP Features

ï¿½ SIP Compatibility:SIP(RFC3261),
ï¿½ IAX2(RFC5457)
ï¿½ Concurrent Calls:16
ï¿½ Maximum Registered Users
ï¿½ Supported:128

Installation & Configuration

ï¿½ Installation: Desktop or Wall mount
ï¿½ Configuration:Web-based configuration

Others

ï¿½ Power Consumption:5W
ï¿½ Storage Temperature:20°C - 65°C(-4°F - 149°F)
ï¿½ Operating Temperature:0°C - 40°C(32°F - 104°F)
ï¿½ Operating Humidity:10 - 90%,Non-condensing
ï¿½ Dimension:225 x 120 x 30mm
ï¿½ Weight:0.90 Kg

Please Enquire

Options available for Atcom IP08 8-port Asterisk IP PBX :

Port 1 - FXO/FXS

- IP Only -, 1 x Dual FXO (+£47.00), 1 x Single FXS (+£24.00), 1 x Dual FXS (+£47.00), 1 x Single FXO (+£24.00).

Port 2 - FXO/FXS

- IP Only -, 1 x Dual FXO (+£47.00), 1 x Single FXS (+£24.00), 1 x Dual FXS (+£47.00), 1 x Single FXO (+£24.00).

Port 3 - FXO/FXS

- IP Only -, 1 x Dual FXO (+£57.00), 1 x Single FXS (+£24.00), 1 x Dual FXS (+£57.00), 1 x Single FXO (+£24.00).

Port 4 - FXO/FXS

- IP Only -, 1 x Dual FXO (+£57.00), 1 x Single FXS (+£24.00), 1 x Dual FXS (+£57.00), 1 x Single FXO (+£24.00).

Atcom IP08 8-port Asterisk IP PBX

Warranty

IP04/IP08 12 Month Warranty, IP04/IP08 Additional 12 Month Warranty (+£90.00).

Annual Support Maintenance

- Not Required -, Require Annual Support (+£480.00).