



Product Name: Doro IP880dect IP Telephone

Manufacturer: Doro Model Number: -

Availability: Discontinued

Please note that the Doro IP880 has been discontinued. We recommend the Snom M3 as a good alternative.

Doro IP880dect

An expandable complement to wired VoIP systems, ip880dect provides greater user freedom with DECT wireless technology. Each ip880dect gateway can handle up to 8 SIP accounts and handsets, 2 SIP providers (e.g. external long distance service plus own SIP enabled PBX for internal/incoming calls) as well as regular PSTN service. Perfect for small businesses or individual departments within larger companies.

Main features:

1⁄2/5٪

LAN interface connection: 10BASE-T (RJ45 8/8)

2⁄ئ;ï

PSTN connection: RJ11

½ ځï

Double antenna for diversity

½ځ:

3 concurrent VoIP calls (SIP 2.0 - RFC3261)

2⁄ئ;ï

Call forward options (all, busy and no answer)

1⁄2′3٪

Voice mail support (provider dependant)



�
Call timer
ï¿1⁄2
Call transfer, call hold DECT
�
Call transfer (Attend and Blind), call hold SIP
ائن"∠ئ
Music on hold support (only via PBX)
Ϊ¿½
Call divert
اً ئِيْ اُلْ
Call park, call pick-up (only via PBX)
�
Call waiting / switching between calls
½′3٪
Redial
الناري ا
Caller ID with name from phonebook
½′3٪
VID ring tone (IP and PSTN)
�
Call log: incoming, outgoing and missed calls



Ï¿½
Call return (from call log)
�
Call swap (one handset toggles between two calls)
ىن. ئى:"
Internal call
�
Gateway phonebook
�
Speed dial
�
Automatic on hook when returning to charger
�
DTMF sending in call
٧٤; ٣
Emergency call routing to PSTN
½٪
CID; FSK and DTMF. Message waiting.
�
CODECSs: G.711, G729A/B



```
SIP features:
1⁄2′3٪
 RFC3261 compliant
½'¿ï
 Digest/basic authentication
2∕ئ;ï
 DNS SRV (RFC3263), redundant server support
2⁄ئ;ï
 Offer/Answer (RFC3264)
½'¿ï
 Message waiting indication reception (RFC3842)
2⁄ئ;ï
 Subscription for MWI (RFC3265)
2⁄ئ;ï
 In-Band DTMF/Out of band DTMF (RFC2833)
2∕ئ;ï
 STUN Client (NAT Traversal)
½ ځï
 rport (RFC3581)
1⁄2′3٪
 REFER (RFC3515)
1⁄2′3٪
```



8 SIP registrations with dual SIP server/registrar
រ៉ៃ2½ SIP configuration via http-page or from handset
Handset Features
�
Lithium battery 650mAH
�
Talk time 15h
�
Standby time 150h
�
Headset jack: 2,5mm
�
64K CSTN backlit Colour LCD display
�
5 levels battery indicator
�
Key lock
Ϊ¿½
Speakerphone



Ĩ¿½
Microphone mute
تر ¹ / ₂
Ringer off selection
�
Message indication
�
Phonebook
�
Alarm
�
Out of range warning
�
10 Selectable ringer melodies
�
Adjustable ringer volume
�
Adjustable handset, speaker and headset volume
�
Auto answer
�
Automatic encryption (DECT)



Ϊ¿½
Call reject option
اّ الْ
Date/Time from the network
Ϊ¿½
Key beep on/off
ن از کی از میران از م از میران از میران ا
Multi Language support: DE, EN, ES, FR, IT, NL, PL, PT and SE
ن.ن. آ ک ¹ کت
Redial
ن ن ا
Silent selection at incoming call

Price: £149.00