

Fanvil i16S SIP Intercom (i16S)



Product Name: Fanvil i16S SIP Intercom (i16S)

Manufacturer: Fanvil

Model Number: i16S

Fanvil i16S SIP Intercom (i16S)

The Fanvil i16S is designed for outdoor environments with high reliability, HD Audio, and IP65/IK10 protection grade. It combines security, audio intercom and broadcasting functionalities and offers the best communication solution for users.

Fanvil i16S Key Features

- IK10 anti-collision with robust die-cast aluminum frame
- Anti-tamper- alarming as long as the cover is apart from the housing, and reporting to the control center at the same time
- HD voice speech quality with built-in 3W speaker and Acoustic Echo Canceller
- Audio line out port, expandable external active speaker.
- Built-in 2 short-in detect port and 2 short-out control port
- Support built-in TF card slot for data storage or audio offline broadcasting.
- Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc.

Fanvil i16S Technical Specifications

General

- 2 SIP lines
- Speed dial
- Linkage with IP camera to realize video intercom
- Oral announcement of the IP address(in English)
- MP3 broadcasting
- Support programmable DSS key
- Support mono active speaker
- Talkback recording output
- Switch signal input and output
- Support TF card
- PoE enabled

Device function

- Auto-answering
- Programmable DSS keys
- Through button or web page volume adjustment
- Network time synchronization
- Time Plan (task management)
- Incoming call multicast
- Dynamic multicast function
- HTTP API
- Action URL / Active URI

Call functions

- Call out / answer / reject
- Call waiting
- Intercom, Multicast
- Speed dial
- Anonymous call (Hide caller ID)

Fanvil i16S SIP Intercom (i16S)

Audio

i16S 1/2 Narrowband codec: G.711A/U, G.729A/B, iLBC, G.723, G.726-32K
i16S 1/2 Wideband codec: G.722, Opus
i16S 1/2 Full-duplex hands-free speakerphone with AEC
i16S 1/2 DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)

Networking

i16S 1/2 Physical: 10/100 Mbps Ethernet
i16S 1/2 IP mode: IPv4/IPv6/IPv4&IPv6
i16S 1/2 IP configuration: Static IP / DHCP / PPPoE
i16S 1/2 VPN: L2TP / OpenVPN
i16S 1/2 VLAN
i16S 1/2 LLDP
i16S 1/2 Qos

Protocols

i16S 1/2 SIP2.0 over UDP/TCP/TLS
i16S 1/2 RTP/RTCP/SRTP
i16S 1/2 STUN
i16S 1/2 DHCP
i16S 1/2 IPv6
i16S 1/2 PPPoE
i16S 1/2 L2TP
i16S 1/2 OpenVPN
i16S 1/2 SNTP
i16S 1/2 FTP/TFTP
i16S 1/2 HTTP/HTTPS
i16S 1/2 TR-069

Physical Specification

i16S 1/2 1 DSS key (support LED)
i16S 1/2 RJ45 port x1: connect the network / Power over Ethernet (IEEE 802.3af), class 3
i16S 1/2 Line out port x1: connect the active speaker / Out: adjustable by volume, max up to 1.2Vpp. / Port: terminal socket
i16S 1/2 Recording output port x1: connect audio device / Out: mixed output of local microphone voice and call voice recording / Impedance: 15 Ohm / Port: terminal socket
i16S 1/2 Short circuit input and output port x2 (built-in relay) / Relay: MAX DC30V / 2A, AC125V / 0.5A / Active switching output: 12V/500mA DC(only 1 relay support) / Port: terminal socket
i16S 1/2 Tamper alarm switchx1
i16S 1/2 TF card slot x1: connect TF card
i16S 1/2 DC port x1: DC power input / DC power input: DC12V~24V/1A / Port: 2 Pin terminal socket
i16S 1/2 Protection level: IP65 and IK10
i16S 1/2 Housing material: aluminum alloy shell
i16S 1/2 Installation: wall-mounted
i16S 1/2 Working temperature: -30-60 degrees C
i16S 1/2 Storage temperature: -40-70 degrees C
i16S 1/2 Working humidity: 10~95%
i16S 1/2 Device dimensions: 195x120x40 mm
i16S 1/2 Gift box dimensions: 260x165x62 mm
i16S 1/2 Outer CTN dimensions: 348x328x280 mm (10 PCS)

Fanvil i16S SIP Intercom (i16S)

Price: £121.80
