

Grandstream GWN7624 In-Wall Wi-Fi Access Point



Product Name: Grandstream GWN7624 In-Wall Wi-Fi Access Point

Manufacturer: Grandstream

Model Number: GWN7624

Grandstream GWN7624 In-Wall Wi-Fi Access Point

The Grandstream GWN7624 is an in-wall Wi-Fi access point designed for small-to-medium-sized businesses, offices, residential and commercial locations, hotels, and more. The GWN7624 provides three Gigabit network ports to provide IP phones, IPTV, computers, and similar devices with Ethernet while also providing and uplink Gigabit network port with PoE/PoE+. The GWN7624 offers 2.4G 2×2, 5G 4×4 MU-MIMO technology, and a sophisticated antenna design for maximum network throughput and expanded Wi-Fi coverage range. Grandstream GWN7624 Key Features:

- ½ 2.03 Gbps wireless throughput and 4 Gigabit wireline ports 5GHz 4×4 MU-MIMO
- ½ Supports up to 200 concurrent Wi-Fi client devices
- ½ Advanced QoS to ensure real-time performance of low-latency applications
- ½ Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device
- ½ Self-power adaptation upon auto detection of PoE or PoE+
- ½ Embedded controller can manage up to 30 local GWN series APs;
- ½ GWN.Cloud offers unlimited AP management; GWN Manager offers premise-based software controller

This access point is designed to be mounted in-wall to provide a clean and professional installation that blends into the surrounding environment. To ensure easy installation and management, the GWN7624 uses a controller-less distributed network management design in which the controller is embedded within the product's web user interface. The GWN7624 is also supported by GWN.Cloud and GWN Manager, Grandstream's free cloud and on-premise Wi-Fi management platform. It is the ideal Wi-Fi AP for voice-over Wi-Fi deployments and offers a seamless connection with Grandstream's Wi-Fi capable IP phones. With support for advanced QoS, low-latency real-time applications, mesh networks, captive portals, and 200 concurrent clients per AP, the GWN7624 is an ideal Wi-Fi access point for medium wireless network deployments with medium user density.

Grandstream GWN7624 In-Wall Wi-Fi Access Point - Technical Specifications

½ Wi-Fi Standards: IEEE 802.11 a/b/g/n/ac

½ Antennas: Two 5G & two double frequency internal antennas, 2.4GHz, gain 3dBi; 5GHz, gain 5dBi

½ Wi-Fi Data Rates:

½ 5G: IEEE 802.11ac: 6.5 Mbps to 1733 Mbps IEEE 802.11n: 6.5Mbps to 600Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

½ 2.4G: IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps *Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network

½ Frequency Bands: 2.4GHz Radio: 2412 - 2484 MHz 5GHz Radio: 5180 - 5825 MHz *Not all frequency bands can be used in all regions

½ Channel Bandwidth: 2.4G: 20 and 40 MHz, 5G: 20, 40 and 80 MHz

½ Wi-Fi and System Security: WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical data/control lockdown via digital signatures, unique

Grandstream GWN7624 In-Wall Wi-Fi Access Point

security certificate and random default password per device

½ MIMO: 2×2 2.4GHz(MIMO), 4×4 5GHz(MU-MIMO)

½ Coverage Range: Up to 100 meters *coverage range can vary based on environment

½ Maximum TX Power: 2.4G: 23dBm, 5G: 25dBm *Maximum power varies by country, frequency band and MCS rate

½ Receiver Sensitivity:

½ 5G: 802.11a: -92dBm @6Mbps, -74dBm @54Mbps; 802.11n 20MHz: -74dBm @MCS7; 802.11n 40MHz: -71dBm @MCS7 802.11ac 20MHz: -67dBm @MCS8; 802.11ac: HT40: -63dBm @MCS9; 802.11ac 80MHz: -59dBm @MCS9
½ 2.4G: 802.11b: -96dBm @1Mbps, -88dBm @11Mbps; 802.11g: -93dBm @6Mbps, -75dBm @54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz: -70dBm @MCS7

½ SSIDs: 16 SSIDs total, 8 per radio (2.4GHz & 5GHz)

½ Concurrent Clients: Up to 200

½ Network Interfaces: 1x 10/100/1000M uplink Ethernet port with PoE/PoE+, 2x 10/100/1000M Ethernet port with PSE, 1x 10/100/1000M Ethernet port

½ Auxiliary Ports: 1x Reset Pinhole

½ Mounting: In-wall mountable

½ LEDs: 1 tri-color LED for device tracking and status indication

½ Network Protocols: IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM

½ QoS: 802.11e/WMM, VLAN, TOS

½ Network Management:

½ Embedded controller can manage up to 30 local GWN APs

½ GWN.Cloud offers a free cloud management platform for unlimited

½ GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs

½ Power and Green Energy Efficiency:

½ Support 802.3az

½ PoE 802.3af/ 802.3at;

½ PSE Maximum Output Per Port: 6W; Maximum Power Consumption: 25W

½ Environmental:

½ Operation -10°C to 50°C

½ Storage: -30°C to 60°C

½ Humidity: 5% to 95% Non-condensing

½ Physical: Unit Dimension: 135mm(L)×86mm(W)×38.5mm(H), Entire Package Dimension: 176mm(L)×118.5mm(W)×65mm(H)

½ Package Content: GWN7624 In-Wall Wireless AP, 4x Screws(KB 3.5*26), Quick Installation Guide

½ Compliance: FCC, CE, RCM, IC, UKCA

Price: £59.25