

Fanvil Linkvil W611W Portable WIFI Phone V2(W611W V2)



Product Name: Fanvil Linkvil W611W Portable WIFI Phone V2(W611W V2) Manufacturer: Fanvil Model Number: W611W V2

Please note: This product is the updated W611W Version 2 from Fanvil.

Fanvil Linkvil W611W Portable WI-FI Phone

The Fanvil Linkvil W611W is a portable, elegant Wi-Fi phone designed for mobile communication applications. Certified to IP67standard, the W611W is highly waterproof, dustproof, and can be dropped safely from a 1.8-meter height. It has excellent performance in different environments with humidity and dust. The W611W integrates Wi-Fi 6, bringing a superb wireless communication experience. Moreover, it integrates Bluetooth 5.0 for pairing with headsets and mobile devices. Fanvil Linkvil W611W-NFR Key Features:

ï¿1/2 2.4" 240 x 320 colour screen with intuitive user interface

- ï¿1/2 High protection level of IP67
- ï¿1/2 Dual-band Wi-Fi 802.11 a/b/g/n/ac/ax Wi-Fi (Wi-Fi 6, 2.4GHz & amp; 5GHz)
- ï¿1/2 IEEE802.11k/v/r roaming

i¿1/2 WPA / WPA2-PSK and 802.1X EAP encryption to ensure communications security

- ï¿¹/₂ Push-to-talk (PTT) button for quick dial
- ï¿1/2 Up to 9 hours' talk time and up to 200 hours standby time

Installed with a rechargeable 1900mAh battery, the W611W is ready for 9 hours' talk time or 200 hours standby time. The W611W is widely used in various wireless scenarios such as enterprises, shopping malls, residential areas, hotels and warehouses, providing users with high-quality mobile communication experience.

Fanvil Linkvil W611W Technical Specifications Generic

� 2.4-inch 240*320 color high-definition LCD display

- ï¿1/2 4 SIP lines
- � Caller ID
- ïزار Handset/Hands-free/Headset Mode• Support custom DSS keys
- � HD Voice

ï¿1∕2 Belt clip

- ï¿1/2 Desktop charging base
- ï¿1/2 Standard type-c interface
- ï¿1/2 Rechargeable Lithium Battery
- ï¿1/2 Support Wi-Fi 6
- ï¿¹/₂ Support Bluetooth 5.0
- iز1/2 Support multi language: English/Chinese/German/French/Italian/Portuguese/Russian/Spanish

Phone Features

ï¿1/2 Network time synchronization

- ï¿1/2 Local contacts
- ï¿1/2 Remote Phonebook (XML/LDAP, 1000 entries)
- ï¿1/2 Multi-language optional



Fanvil Linkvil W611W Portable WIFI Phone V2(W611W V2)

- � Call logs
- ï¿1/2 Blocked List/Allowed List

ï¿1/2 Screen saver

- ï¿1/2 Personalized ringtone settings
- ï¿1/2 Screen backlight adjustment

� Memorandum

- � SMS service
- ï¿1/2 Voicemail(MWI)
- ï¿1/2 Menu encryption settings
- ï¿1/2 Keypad lock/ backlight adjustment
- ï¿1/2 Volume adjustment

Call Features

ï¿1∕₂ Auto-Answering

- ï¿1/2 Call out/Answer/Reject
- ï¿1/2 Call waiting/Switch
- � Call forwarding
- � Speed Dial
- � Intercom
- � Anonymous calls
- ï¿1/2 3-way Conference
- i¿1/2 Restrict outgoing calls
- � IP direct dial � Speed Dial
- � Emergency call
- � Caller ID Display
- ï¿1/2 Inquiry (dialing, incoming and outgoing calls)
- � Do-Not-Disturb
- iز1⁄2 PTT one-key call
- ï¿1/2 Self-adaptive light-sensing screen off (during a call on the handset)

Audio

- ï¿1/2 Narrowband Codec: G.711a/u, G.729AB,iLBC
- ï¿1/2 Wideband Codec: G.722, Opus
- ï¿1/2 Acoustic Echo Cancellation (AEC)- maximum 96ms echo delay cancellation
- ï¿1/2 Voice Activity Detection(VAD)/ Comfort Noise
- Generation(CNG)/ Background Noise Estimation (BNE)
- ï¿1/2 Packet Loss Concealment
- ï¿1/2 Dynamic adaptive jitter cache up to 300ms
- ïزار DTMF: In-band, Out-of-Band DTMF-Relay(RFC2833) / SIPINFO

Network

i¿½ Built-in Wi-Fi, support 802.11 a/b/g/n/ac/ax protocol: 2.4GHz IEEE 802.11 b/g/n/ax 5GHz IEEE 802.11a/n/ac/ax Encryption:WPA /WPA2-PSK,802.1XEAP i¿½ Built-in Bluetooth 5.0 module

Power Management

- ï¿1/2 Reminder when charging
- ï¿1∕₂ Full reminder
- ï¿1/2 Low battery prompt
- ï¿1/2 After abnormal shutdown, the charging will automaticallystar



Fanvil Linkvil W611W Portable WIFI Phone V2(W611W V2)

ï¿1/2 Real-time statistics/display of system power

Protocols

� RTP/RTCP/SRTP � STUN � HCP � SNTP � FTP/TFTP � HTTP/HTTPS � TR-069

Deployment and Maintenance

i¿¼ Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCPOPT66/SIPPnP/TR-069 i¿¼ Web management interface i¿¼ Web-based Packet-dump i¿¼ Configuration export/import i¿¼ Firmware upgrade i¿¼ Syslog

Physical Specifications

- ï¿1/2 Protection class: IP67 ï¿1/2 Drop height: 1.8m i¿1/2 Shell material: plastic shell, two-color injection molding ï¿1/2 Charging Base x1 ï¿1/2 Belt Clip x1 ï¿1/2 Rechargeable Battery x1 1900mAh ï¿1/2 DC input: 5V/2A ï¿1/2 Charging port: Type-c ï¿1/2 Headphone jack: 3.5mm standard jack ï¿1/2 Installation method: Belt Clip /Desktop ï¿1/2 Operating temperature: 0℃~ 45℃ ï¿1/2 Storage temperature:-20℃~ 60℃ ï¿1/2 Relative humidity:10~95% ï¿1/2 Product size:160*53*16mm ï¿1/2 Product weight::156g ï¿1/2 Certificates:CE/FCC/UKCA/RoHS/SRRC ï¿1/2 Box size: 200*117*103mm
- � Outer box size: 437*254*220mm ((8PCS)

Price: £125.70

Options available for Fanvil Linkvil W611W Portable WIFI Phone V2(W611W V2) :

Headset

JPL Commander PM Wired Headset 575-365-003 (+£43.00), JPL BT500D Wireless Headset (+£121.50), Not Required.