

Product Name: Logitech Rally Bar Mini - Graphite (960-001340)



Manufacturer: Logitech Model Number: 960-001340

Logitech Rally Bar Mini - Graphite (960-001340)

Simplicity meets versatility with the Logitech Rally Bar Mini (960-001340), Logitech's most advanced all-in-one video bar for small meeting rooms and huddle spaces. With studioquality audio and video, Aldriven performance, and flexible deployment options, Rally Bar Mini sets a new standard for small room collaboration.

It's remarkably simple to use, manage, and deploy at scale, delivering the capabilities of larger video bars like Logitech Rally Bar in a compact form factor for smaller spaces. With studio-quality audio and video, motorized pan and tilt, and AI-powered performance, Rally Bar Mini sets new standards for video collaboration.

Logitech Rally Bar Mini Key Features

ï¿1/2 USB-Plug & Play

ï¿1/2 All-in-one design

� RightSense technologies

� Room-filling sound

� Ultra-HD video

� Al Viewfinder

Scalable across hundreds or thousands of rooms, Rally Bar Mini offers clutter-free cable management, multiple mounting options, and flexible deployment modes. Plug and play with virtually any PC or Mac, or run supported video conferencing applications on the device without a computer.

Logitech Rally Bar Mini Technical Specifications General

آذِنُ Built-in Components: 6 beamforming microphones, PTZ camera, 3 speakers, Al Viewfinder, cable management & Death (amp; retention system, table stand, Logitech CollabOS platform

آذِيً Enclosure: All-in-one enclosure with integrated table stand and patented speaker suspension system to eliminate vibration-induced camera shake and audio interference

īപ്2 Device Management: Logitech Sync

� Displays Supported: 2

� Display Resolution: Up to 4k

#### Camera

� Resolution: 4K, 1440p, 1080p, 900p, 720p, and SD at 30fps

ï¿1/2 Pan: Motorized ±25°

� Tilt: Motorized ±15°

� Zoom: 4X HD digital zoom

ï¿1/2 Diagonal Field of View: 120°

� Horizontal Field of View: 113°

� Vertical Field of View: 80.7°



าั¿½ Total Room Coverage (field of view + pan and tilt): 163° horizontal x 110° vertical

## **Dimensions**

� Height: 91.4 mm / 3.6 in � Width: 719 mm / 2.36 ft � Depth: 101 mm / 3.98 in � Lens Depth: 18.5 mm / 0.73 in � Weight: 4.03 kgs / 8.88 lbs

### **Speakers**

� Woofer: 70mm / 2.7in � Mid-range: 2x / 1.5in

� Output: 90dB SPL @1W, 99dB SPL @8.0W, both +/-2dB at ½ meter

� Sensitivity: 86+/-2dB SPL at 1W, ½ meter

� THD: 1kHz < 2%

ï¿⅓ Speaker Sampling Rate: 48 kHz

## RightSense Technologies

า๊¿½ RightLight™: Renders natural skin tones for each participant

T¿½ RightSight™: Maintains persistent room awareness and detects human figures to auto-frame participants

� RightSound™: Distinguishes speech from other sounds to auto-level voices while suppressing background noise and echo

## Microphones

T¿½ Frequency Response: 90Hz – 16kHz T¿½ Sensitivity: >-36dBFS +/-1dB @ 1Pa

ï¿1/2 Microphone Data Rate Output: 48 kHz

� Pickup Range: 4.5m / 15 ft

i¿½ Beamforming Elements: Six omnidirectional digital MEMS microphones forming five adaptive acoustic broadside beams

آذًا Audio Processing: AEC (Acoustic Echo Cancellation), VAD (Voice Activity Detector)

ï¿⅓ Noise Suppression: Al filter



� Add-on Mics: Supports up to 2 additional

ï¿⅓ Rally Mic Pods

#### Interfaces

ï¿⅓ HDMI Out: 2 ï¿⅓ HDMI In: 1

ī¿½ USB 3.0: 3x Type A, 1x Type C � Network: 10/100/1G Ethernet � WiFi: 802.11a/b/g/n/ac (MIMO)

าั¿½ External Mic Input: Yes (proprietary input supports optional Rally Mic Pod, Rally Mic Pod Hub,

and Rally Mic Pod Extension Cable)

า๊¿½ Remote Control: Bluetooth® Low Energy

� Power & Cables � Power Supply: Auto-sensing

� Operating Voltage/Power: 100-240V, 19V, 4.74A � Power Supply Dimensions: 127mm x 51mm x 30mm

� DC Cable: 1.5m / 4.9 ft � AC Cable: 1m / 3.28 ft � HDMI 1.4 Cable: 2m / 6.5 ft

ï¿1/2 USB A to USB C 3.0 Cable: 2.2m / 7.2 ft

## Environmental

� Operating Temperature: 0 to 40 °C � Storage Temperature: -40 to 70 °C

ï¿⅓ Humidity: 10 to 95%

ï¿1/2 BTU/hr: 57 idle, 64 in meeting

## Security

17:1/2 Full Disk Encryption: AES-128

� Data Encryption: Symmetric Keys, PKI

าั¿½ Device Identity: Protected by device attestation าั¿½ Device Access: Authenticated using API



� Key Protection: Arm TrustZone, RPMP

Price: £2,078.40