

## Fanvil X301W Entry Level IP Phone



Product Name: Fanvil X301W Entry Level IP Phone

Manufacturer: -

Model Number: X301W

### Fanvil X301W Entry Level IP Phone

The Fanvil X301W is a cost-effective Wi-Fi IP phone with multi-functionality. It features a 2.3-inch 128x48 pixel dot-matrix display, supports 2 SIP lines and local 6-party conferencing to render a user-friendly experience. The X301W has rich functions such as HD audio and built-in 2.4GHz & 5GHz Wi-Fi, providing an efficient and high-quality business communication experience for enterprises. Fanvil X301W Key Features:

- 2.3-inch 128x48 pixel dot-matrix display
- Supports audio codec G.722 and Opus, HD audio on speakerphone and handset
- Supports 6-party local conference
- Support EHS wireless headset
- Built-in 2.4GHz & 5GHz Wi-Fi, realizing more flexible connectivity
- Two installation methods of desktop stand and wall mountable

### Fanvil X301W - Technical Specifications

#### Generic

- 2 SIP Lines
- HD Voice
- PoE Enabled
- Built-in 2.4GHz & 5GHz Wi-Fi
- Dot-matrix display screen
- Handset / Hands-free / Headset mode
- Desktop Stand / Wall mountable (optional)
- Optional External Power Supply

#### Phone Functions

- Local Phonebook (1000 entries) Remote Phonebook (XML/LDAP, 1000 entries)
- Call logs (In/Out/Missed, 600 entries)
- Blocked List/Allowed List
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Built-in Wi-Fi 2.4GHz, 802.11 b/g/n 5GHz, 802.11 a/n/ac
- Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)
- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording (Through Server)
- Action URL / Active URI
- uaCSTA

#### Call Functions

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom

## Fanvil X301W Entry Level IP Phone

- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forward(Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (with server)
- 6-way Conference
- Hot Line
- Hot desking

### Audio

- HD Voice Microphone/Speaker
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.729A/B, iLBC
- Wideband Codec: G.722, Opus

### Network

- Physical: 10/100 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4/IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Wi-Fi Encryption: WPA / WPA2-PSK / 802.X EAP
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- QoS
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

### Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPV6
- LLDP
- PPPoE
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069
- AES128 & AES256

### Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIPPNP/TR-069

## Fanvil X301W Entry Level IP Phone

- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

### Physical Specifications

- LCD: 128x48 pixel graphical LCD with backlight
- Keypad: 33 keys, including
- 4 Soft-keys
- 9 Function keys (Hold/Transfer/Voicemail/Conference/Phonebook/MWI/Headset/Redial/Hands-free)
- 4 Navigation keys
- 1 OK key
- 12 Standard Phone Digits keys
- 3 Volume Control keys (Up/Down/Mute (Microphone))
- Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT.5E Ethernet Cable x1
- Desktop Stand x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- Security Slot x1
- DC Power Input: 5V/0.6A
- Power Consumption(Adapter): 0.8~1.29W
- Power Consumption(PoE): 1.25~1.86W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation: Desktop Stand/Wall mountable (optional)
- Color: Black
- N.W/CTN: 9.05kg(X301), 8.55kg(X301P)
- G.W/CTN: 9.76kg(X301), 9.26kg(X301P)
- Device Dimensions: Desktop Stand (45°): 169x201.1x177.4 mm Desktop Stand (50°): 169x191.9x185.8 mm Wall mountable: 169x120.1x213.7 mm
- Gift Box Dimensions: 250x220x55mm
- Outer CTN Dimensions: 460x300x270mm(10 PCS)

### Please Enquire

Options available for Fanvil X301W Entry Level IP Phone :

#### Need Product Setup / Training / Support?

Required - 30 minutes (+\$53.48), Not Required, Required - 1 Hour (+\$86.91).

#### Wired Headset

Fanvil HT202 (+\$57.50), Not Required, Fanvil HT201 (+\$41.45).

#### Wireless Headset

## Fanvil X301W Entry Level IP Phone

Not Required, [Jabra Pro 920 Mono DECT Headset \(+\\$218.75\)](#).