

## Fanvil X301G Entry Level IP Phone



Product Name: Fanvil X301G Entry Level IP Phone

Manufacturer: -

Model Number: X301G

Please Note: This product is end of life. For an alternative, see the other Fanvil VoIP Phones.

### Fanvil X301G Entry Level IP Phone

The Fanvil X301G is an entry level Gigabit SIP phone with multi-functionality. It features a 2.3-inch 128x48 pixel dot-matrix display, supports 2 SIP lines and local 6-party conferencing to render a user-friendly experience. The X301G has rich functions such as HD audio, dual 10/100/1000 Mbps network ports and integrated PoE, providing an efficient and high-quality business communication experience for enterprises. Fanvil X301G Key Features:

- 2.3-inch 128x48 pixel dot-matrix display
- Supports audio codec G.722 and Opus, HD audio on speakerphone and handset
- Supports 6-party local conference
- Support EHS wireless headset
- Dual 10/100/1000 Mbps network ports, integrated PoE
- Two installation methods of desktop stand and wall mountable

### Fanvil X301G - Technical Specifications

#### Generic

- 2 SIP Lines
- HD Voice
- PoE Enabled
- Dot-matrix display screen
- Handset / Hands-free / Headset mode
- Desktop Stand / Wall mountable (optional)
- Optional External Power Supply

#### Phone Functions

- Local Phonebook (1000 entries)
- Remote Phonebook (XML/LDAP, 1000 entries)
- Call logs (In/Out/Missed, 600 entries)
- Blocked List/Allowed List
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)
- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording (Through Server)
- Action URL / Active URI
- uaCSTA

#### Call Functions

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting

## Fanvil X301G Entry Level IP Phone

- 1/2 Intercom
- 1/2 Caller ID Display
- 1/2 Speed Dial
- 1/2 Anonymous Call (Hide Caller ID)
- 1/2 Call Forward(Always/Busy/No Answer)
- 1/2 Call Transfer (Attended/Unattended)
- 1/2 Call Parking/Pick-up (Depending on server)
- 1/2 Redial
- 1/2 Do-Not-Disturb
- 1/2 Auto-Answering
- 1/2 Voice Message (with server)
- 1/2 6-way Conference
- 1/2 Hot Line
- 1/2 Hot desking

### Audio

- 1/2 HD Voice Microphone/Speaker
- 1/2 Wideband ADC/DAC 16KHz Sampling
- 1/2 Narrowband Codec: G.711a/u, G.723.1, G.726, G.729A/B, iLBC
- 1/2 Wideband Codec: G.722, Opus
- 1/2 Full-duplex Acoustic Echo Canceller (AEC)
- 1/2 Voice Activity Detection (VAD) / Comfort Noise Generation (CNG)/ Background Noise Estimation (BNE) / Noise Reduction (NR) /Automatic Gain Control (AGC)
- 1/2 Packet Loss Concealment (PLC)
- 1/2 Dynamic Adaptive Jitter Buffer
- 1/2 DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)
- 1/2 VQM voice quality monitoring

### Network

- 1/2 Physical: 10/100 Mbps Ethernet, dual bridged port for PC bypass
- 1/2 IP Mode: IPv4/IPv6
- 1/2 IP Configuration: Static IP / DHCP / PPPoE
- 1/2 Network Access Control: 802.1x
- 1/2 VPN: L2TP / OpenVPN
- 1/2 VLAN
- 1/2 LLDP
- 1/2 QoS
- 1/2 RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

### Protocols

- 1/2 SIP2.0 over UDP/TCP/TLS
- 1/2 RTP/RTCP/SRTP
- 1/2 STUN
- 1/2 DHCP
- 1/2 IPV6
- 1/2 LLDP
- 1/2 PPPoE
- 1/2 802.1x
- 1/2 L2TP
- 1/2 OpenVPN
- 1/2 SNTP
- 1/2 FTP/TFTP

## Fanvil X301G Entry Level IP Phone

- HTTP/HTTPS
- TR-069
- AES128 & AES256

### Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIPPNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

### Physical Specifications

- LCD: 128x48 pixel graphical LCD with backlight
- Keypad: 33 keys, including
- 4 Soft-keys
- 9 Function keys  
(Hold/Transfer/Voicemail/Conference/Phonebook/MWI/Headset/Redial/Hands-free)
- 4 Navigation keys
- 1 OK key
- 12 Standard Phone Digits keys
- 3 Volume Control keys (Up/Down/Mute (Microphone))
- Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT.5E Ethernet Cable x1
- Desktop Stand x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- Security Slot x1
- DC Power Input: 5V/0.6A
- Power Consumption(Adapter): 0.8~1.29W
- Power Consumption(PoE): 1.25~1.86W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation: Desktop Stand/Wall mountable (optional)
- Color: Black
- N.W/CTN: 9.05kg(X301), 8.55kg(X301P)
- G.W/CTN: 9.76kg(X301), 9.26kg(X301P)
- Device Dimensions: Desktop Stand (45°): 169x201.1x177.4 mm Desktop Stand (50°): 169x191.9x185.8 mm Wall mountable: 169x120.1x213.7 mm
- Gift Box Dimensions: 250x220x55mm
- Outer CTN Dimensions: 460x300x270mm(10 PCS)

**Please Enquire**

Options available for Fanvil X301G Entry Level IP Phone :

## Fanvil X301G Entry Level IP Phone

### **Need Product Setup / Training / Support?**

[Required - 30 minutes \(+£40.00\)](#), [Not Required](#), [Required - 1 Hour \(+£65.00\)](#).

### **Wired Headset**

[Fanvil HT202 \(+£43.00\)](#), [Not Required](#), [Fanvil HT201 \(+£31.00\)](#).

### **Wireless Headset**

[Not Required](#), [Jabra Pro 920 Mono DECT Headset \(+£163.60\)](#).