



Product Name: Fanvil Linkvil W611W-NFR Portable WIFI Phone (Trial Offer)

Manufacturer: -

Model Number: W611W-NFR

This limited-quantity NFR version has now sold out. Please see the Fanvil W611W WiFi Phone to buy this product.

Fanvil Linkvil W611W-NFR Portable WI-FI Phone

The Fanvil Linkvil W611W is a portable, elegant Wi-Fi phone designed for mobile communication applications. Certified to IP67standard, the W611W is highly waterproof, dustproof, and can be dropped safely from a 1.8-meter height. It has excellent performance in different environments with humidity and dust. The W611W integrates Wi-Fi 6, bringing a superb wireless communication experience. Moreover, it integrates Bluetooth 5.0 for pairing with headsets and mobile devices. Fanvil Linkvil W611W-NFR Key Features:

าั¿½ 2.4" 240 x 320 colour screen with intuitive user interface

ï¿⅓ High protection level of IP67

تزير Dual-band Wi-Fi 802.11 a/b/g/n/ac/ax Wi-Fi (Wi-Fi 6, 2.4GHz & Tiches amp; 5GHz)

ï¿1/2 IEEE802.11k/v/r roaming

Ti, 1/2 WPA / WPA2-PSK and 802.1X EAP encryption to ensure communications security

� Push-to-talk (PTT) button for quick dial

าั¿½ Up to 9 hours' talk time and up to 200 hours standby time

Installed with a rechargeable 1900mAh battery, the W611W is ready for 9 hours' talk time or 200 hours standby time. The W611W is widely used in various wireless scenarios such as enterprises, shopping malls, residential areas, hotels and warehouses, providing users with high-quality mobile communication experience.

Fanvil Linkvil W611W Technical Specifications Generic

17.1/2 2.4-inch 240*320 color high-definition LCD display

ï¿1/₂ 4 SIP lines

� Caller ID

ī¿½ Handset/Hands-free/Headset Mode• Support custom DSS keys

ï¿⅓ HD Voice

ï¿⅓ Belt clip

� Desktop charging base

ï¿1/2 Standard type-c interface

� Rechargeable Lithium Battery

� Support Wi-Fi 6

ï¿1/2 Support Bluetooth 5.0

าั¿½ Support multi language: English/Chinese/German/French/Italian/Portuguese/Russian/Spanish



Phone Features

- � Network time synchronization
- � Local contacts
- تز½ Remote Phonebook (XML/LDAP, 1000 entries)
- � Multi-language optional
- ï¿⅓ Call logs
- ï¿1/2 Blocked List/Allowed List
- ï¿⅓ Screen saver
- ï¿⅓ Personalized ringtone settings
- � Screen backlight adjustment
- ï¿1/2 Memorandum
- ï¿1/2 SMS service
- ï¿1/2 Voicemail(MWI)
- � Menu encryption settings
- � Keypad lock/ backlight adjustment
- � Volume adjustment

Call Features

- ï¿1/2 Auto-Answering
- ï¿1/2 Call out/Answer/Reject
- � Call waiting/Switch
- ï¿⅓ Call forwarding
- ï¿⅓ Speed Dial
- ï¿⅓ Intercom
- � Anonymous calls
- ï¿1/2 3-way Conference
- � Restrict outgoing calls
- آز½ IP direct dial
- ï¿⅓ Speed Dial
- � Emergency call
- � Caller ID Display
- � Inquiry (dialing, incoming and outgoing calls)
- � Do-Not-Disturb
- � PTT one-key call
- าั¿1/2 Self-adaptive light-sensing screen off (during a call on the handset)

Audio

- ï¿1/2 Narrowband Codec: G.711a/u, G.729AB,iLBC
- Wideband Codec: G.722, Opus
- ī¿½ Acoustic Echo Cancellation (AEC)- maximum 96ms echo delay cancellation
- آزار Voice Activity Detection(VAD)/ Comfort Noise
- Generation(CNG)/ Background Noise Estimation (BNE)
- � Packet Loss Concealment
- � Dynamic adaptive jitter cache up to 300ms
- ī¿½ DTMF: In-band, Out-of-Band DTMF-Relay(RFC2833) / SIPINFO

Network

� Built-in Wi-Fi, support 802.11 a/b/g/n/ac/ax protocol: 2.4GHz IEEE 802.11 b/g/n/ax 5GHz IEEE 802.11a/n/ac/ax Encryption:WPA /WPA2-PSK,802.1XEAP π¿½ Built-in Bluetooth 5.0 module



Power Management

- � Reminder when charging
- آز½ Full reminder
- � Low battery prompt
- ī సైస్త After abnormal shutdown, the charging will automaticallystar
- า๊¿½ Real-time statistics/display of system power

Protocols

- � RTP/RTCP/SRTP
- ۲¿⅓ STUN % STUN
- ї¿⅓ НСР
- SNTP ½ SNTP
- آزٰ½ FTP/TFTP
- ï¿⅓ HTTP/HTTPS
- � TR-069

Deployment and Maintenance

- Ti21/2 Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCPOPT66/SIPPnP/TR-069
- � Web management interface
- � Web-based Packet-dump
- � Configuration export/import
- � Firmware upgrade
- ï¿⅓ Syslog

Physical Specifications

- � Protection class: IP67
- ï¿⅓ Drop height: 1.8m
- า๊ะ่½ Shell material: plastic shell, two-color injection molding
- � Charging Base x1
- ï¿⅓ Belt Clip x1
- ï¿1/2 Rechargeable Battery x1 1900mAh
- � DC input: 5V/2A
- � Charging port: Type-c
- ï¿1/2 Headphone jack: 3.5mm standard jack
- ï¿⅓ Installation method: Belt Clip /Desktop
- � Operating temperature: 0℃~ 45℃
- ï¿1/2 Storage temperature:-20℃~ 60℃
- � Relative humidity:10~95%
- � Product size:160*53*16mm
- ï¿1/2 Product weight::156g
- � Certificates:CE/FCC/UKCA/RoHS/SRRC
- � Box size: 200*117*103mm
- ï¿1/2 Outer box size: 437*254*220mm ((8PCS)

Please Enquire



Options available for Fanvil Linkvil W611W-NFR Portable WIFI Phone (Trial Offer):

Headset

JPL BT500D Wireless Headset (+\$125.28), Not Required, JPL Commander PM Wired Headset 575-365-003 (+\$61.98).