

## Grandstream GRP2636 12-Line Professional IP Phone



Product Name: Grandstream GRP2636 12-Line Professional IP Phone

Manufacturer: Grandstream

Model Number: GRP2636

### Grandstream GRP2636 12-Line Professional IP Phone

The Grandstream GRP2636 is an executive-quality 12-line model with a 4.3-inch color LCD screen designed with zero-touch provisioning for mass deployment and easy management. The GRP2636 features a sleek design and a suite of next-generation features including 5-way voice conferencing to maximize productivity, integrated PoE & Wi-Fi, full HD audio on both the speaker and handset to allow users to communicate with the utmost clarity.

Grandstream GRP2636 Key Features:

- 12 lines, 6 SIP accounts

- Supported by GDMS which provides a centralized interface to configure, provision, manage and monitor Grandstream devices

- RJ9 headset jack allowing EHS with Plantronics headsets, and integrated USB Headset support

- Full-duplex speakerphone with HD audio to maximize audio quality and clarity

- Equipped with noise shield technology to minimize background noise

The GRP series includes carrier-grade security features to provide enterprise-level security, including secure boot, dual firmware images, and encrypted data storage. For cloud provisioning and centralised management, the GRP2636 is supported by Grandstream's Device Management System (GDMS), which provides a centralised interface to configure, provision, manage and monitor deployments of Grandstream endpoints.

The GRP2636 is the perfect choice for busy professionals and receptionists who need to manage high call volumes, with advanced functionality. Designed for easy deployment by enterprises, service providers, and other high-volume markets, the GRP2636 offers an easy-to-use and easy-to-deploy voice endpoint.

### Grandstream GRP2636 Technical Specifications

#### General

- Protocols/Standards SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6

- Network Interfaces Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE

- Graphic Display 4.3inch(480x272) TFT color LCD

- Wi-Fi Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)

- Bluetooth Yes, integrated

- Feature Keys 12 line keys with up to 6 SIP accounts, 24MPK extension keys with paper slot, 5 XML programmable context sensitive softkeys, 5 navigation/menu keys, 8 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HEADSET, HOLD,MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL

- Auxiliary Port RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets

- Voice Codecs and Capabilities Support for G.729A/B, G.711µ/a-law, G.726, G.722(wide-band), G723, iLBC, OPUS, inband and out-of-band DTMF(in audio, RFC2833, SIP INFO)

- Telephony Features Hold, transfer, forward, 5-way conference, call park, call pickup, shared-callappearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call log(up to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over

## Grandstream GRP2636 12-Line Professional IP Phone

• HD Audio Yes, HD handset and speakerphone with support for wideband audio. Dual Microphone.

• Extension Module No

• Base Stand Yes, 2 angle positions available, Wall Mountable (Wall Mount \*sold separately)

• QoS Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS

• Security User and administrator level passwords, MD5 and MD5-session based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.

• Multi-language English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more

• Upgrade/Provisioning Firmware upgrade via FTP/TFTP/TFTPS/HTTP/HTTPS, mass provisioning using GDMS/ TR-069 or AES encrypted XML configuration file.

• Power & Green Energy Efficiency Universal power adapter included: Input:100-240V ; Output: +12V, 1A ; Integrated Power-over-Ethernet(802.3af) Max power consumption 3.2W(power adapter) or 4.3W(PoE)

• Temperature and Humidity Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing

• Package Content GRP2636 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license

• Physical Dimension: 220mmx 210mmx 82mm Unit Weight: 880g ; Package Weight:1260g

• GRP2636 Compliance FCC: FCC Part 15 Class B; FCC Part 15 Subpart C,15.247; FCC Part 15 Subpart E,15.407; FCC Part 68 HAC. CE: ETSI EN 301 893; ETSI EN 301 489-1/-17; ETSI EN 300 328; EN IEC 62311; EN 55032; EN 55035; EN 62368-1. IC: RSS-247 Issue 2; RSS-Gen Issue 5; ICES-003 Issue 7; CS-03, Part V. RCM: AS/NZS CISPR32; AS/NZS 4268; AS/NZS 2772.2; AS/NZS 62368.1; AS/CA S004. UKCA: ETSI EN 301 893; ETSI EN 301 489-1/-17; ETSI EN 300 328; BS EN IEC 62311; BS EN 55032; BS EN 55035; BS EN 62368-1.

**Price: Â£137.40**